

RFQ NO: 0019165

REQUEST FOR PROPOSAL TO - RENOVATIONS TO WITBANK LABORATORY IN MPUMALANGA

## **ISSUED BY:**

CONSTRUCTION INDUSTRY DEVELOPMENT BOARD 2 Dr LATEGAN ROAD GROENKLOOF 0075

## PREPARED BY:

SUPPLY CHAIN MANAGEMENT NHLS NHLS RESEPTION, BUILDING 23, GROUND FLOOR, CSIR PRETORIA CAMPUS, MEIRING NAUDE ROAD, BRUMMERIA, PRETORIA

Proposal Queries:	Technical Queries:	
Contact Name: Fikile Hope Xaba	Contact Name: Corrie Swart	
Telephone: 012 842 7579	Telephone: 082 809 5978	

NAME OF TENDERER: RFQ: 2025491 - RENOVATIONS TO WITBANK LABORATORY IN MPUMALANGA.

CLOSING DATE: 08 November 2024 @ 11h00

## **Contents**

	OSAL	
4	PROPOSAL PROCEDURES	PART E1: I
4	E AND INVITATION TO SUBMIT PROPOSAL	E1.1 NOTICI
	IISSION DATA	E1.2 TSUBM
17	RETURNABLE DOCUMENTS AND SCHEDULES	PART E2:
17	LIST OF RETURNABLE DOCUMENTS	E2.1
Error! Bookmark not defined.	RETURNABLE SCHEDULES	E2.2
Error! Bookmark not defined.	CERTIFICATE OF TENDERER'S ATTENDANCE OF BRIEFING SESSION, if applicable .	FORM A:
18	VENDOR NUMBER REGISTRATION WITH CENTRAL SUPPLIER DATABASE	FORM B:
19	TAX COMPLIANCE	FORM C:
20	PREFERENCE SCHEDULE	FORM D:
28	PROOF OF REGISTRATION WITH CIDB	FORM E:
29	DECLARATION OF INTEREST	FORM F:
	DECLARATION OF BIDDER'S PAST SUPPLY CHAIN MANAGEMENT PRACTICES	FORM G:
34	OHS ACT DECLARATION AND SUBMISSION	FORM H:
Error! Bookmark not defined.	COID CERTIFICATE ISSUED BY DEPARTMENT OF LABOUR	FORM I:
	SCHEDULE OF BIDDER'S EXPERIENCE IN FENCING PROJECTS	FORM J:
Error! Bookmark not defined.	MPLETED PROJECTS (to be completed for each individual project)	FORM K: CC
37	AGREEMENT AND CONTRACT DATA	PART C1:
37	OF OFFER AND ACCEPTANCE	C1.1: FORM
42	RACT DATA	C1.2 CONTR
Error! Bookmark not defined.	RUCTION GUARANTEE	C1.3 CONST
47	PRICING DATA AND BILL OF QUANTITIES	PART C2:
48	PRICING INSTRUCTIONS	C2.1
51	SCOPE OF WORK	PART C3:
Error! Bookmark not defined.	RIPTION OF WORKS	C3.1 DESCF
Error! Bookmark not defined.	/URES	C3.3 ANNEX

#### **RFQ**

### **PROPOSAL PROCEDURES**

#### 1.1 NOTICE AND INVITATION TO SUBMIT PROPOSALS

Construction Industry Development Board invites Proposal to RENOVATIONS TO WITBANK LABORATORY IN MPUMALANGA.

Preferences are offered to tenderers for Broad-Based Black Economic Empowerment (B-BBEE) Status Level of Contribution in terms of the Preferential Procurement Regulations, 2022. Exempted Micro Enterprises (EME) or Qualifying Small Enterprises (QSE) the specific goals will be applicable.

Only tenderers who are already registered in terms of the Construction Industry Development Regulations in cidb grading designation **2GB** or higher are eligible to submit proposal.

#### COMPULSORY BRIEFING AND SITE INSPECTION

## COMPULSORY SITE MEETING: WITBANK HOSPITAL, MEET AT NHLS RECEPTION ON THE 31 OCTOBER 2024 @ FROM 12HOO TILL 12H30

The tenderer shall inspect and examine the Site and its surroundings and shall satisfy himself/herself before submitting his/her proposal. The tenderer must be represented at the site inspection by a person who is suitably qualified and experiences to comprehend the implications of the work involved. Attendance of the site inspection is compulsory and a tender will be disqualified if the site inspection is not attended by a representative of the tenderer.

NOTE: No additional site visits will be allowed.

Tenderers shall submit in the technical proposals and pricing separate.

Technical proposal will be evaluated on Administrative / Mandatory Requirements and on Functionality.

Bidders who fail to meet requirements for Technical evaluation will not be considered further.

Financial proposal will be evaluated on price and B-BBEE as outlined in this document.

## THE CLOSING DATE AND TIME FOR RECEIPT OF PROPOSAL IS 08 November 2024 at 11h00am

Only Proposal complying with the following requirements will be considered:

- i) The request for proposal is for contractors who have a CIDB contractor grading as outlined above
- ii) Proposal submitted on the prescribed format
- iii) Proposal should be hand delivered to: NHLS RESEPTION, BUILDING 23, GROUND FLOOR, CSIR PRETORIA CAMPUS, MEIRING NAUDE ROAD, BRUMMERIA, PRETORIA RFQ Box.

## Telegraphic, telephonic, telex, facsimile and late proposal will not be accepted.

Requirements for sealing, addressing, delivery, opening and assessment of proposal are stated in the Submission Data.

# PART A REQUEST FOR PROPOSAL

YOU ARE HEREBY INVITED TO SUBMIT PROPOSAL FOR SUPPLYING AND INSTALLATION OS ALTERNATIVE POWER SUPPLY IN LETABA, INCLUDING SITE ASSESSMENT						
RFP NUMBER:						
DESCRIPTION RENOVATIONS TO WITBANK LABORATORY IN MPUMALANGA.						
THE SUCCESSFUL BIDDER WILL BE REQUIRED TO FILL IN AND SIGN A WRITTEN CONTRACT FORM (MBD7.1) OR AGRREMENT OF FORM OF OFFER AND ACCEPTANCE.						

SUPPLIER INFORMATION				
NAME OF BIDDER				
POSTAL ADDRESS				
STREET ADDRESS				
TELEPHONE NUMBER	CODE		NUMBER	
CELLPHONE NUMBER				
FACSIMILE NUMBER	CODE		NUMBER	
E-MAIL ADDRESS				
VAT REGISTRATION NUMBER				
TAX COMPLIANCE STATUS	TCS PIN:	OR	CSD No:	
B-BBEE STATUS LEVEL VERIFICATION CERTIFICATE [TICK APPLICABLE BOX]	☐ Yes ☐ No	B-BBEE STA	ATUS LEVEL FIDAVIT	☐ Yes ☐ No
[TION ALTEROADLE BOX]				

[A B-BBEE STATUS LEVEL VERIFICATION CERTIFICATE/ SWORN AFFIDAVIT (FOR EMES & QSEs) MUST BE SUBMITTED IN ORDER TO QUALIFY FOR PREFERENCE POINTS FOR B-BBEE]					
ARE YOU THE ACCREDITED     REPRESENTATIVE IN SOUTH     AFRICA FOR THE GOODS     /SERVICES /WORKS OFFERED?	☐ Yes ☐ No [IF YES ENCLOSE PROOF]	ARE YOU A FOREIGN BASED SUPPLIER FOR THE GOODS /SERVICES /WORKS OFFERED?	☐ Yes ☐ No [IF YES, ANSWER PART B:3]		
2. TOTAL NUMBER OF ITEMS OFFERED					
3. SIGNATURE OF BIDDER		4. DATE			
5. CAPACITY UNDER WHICH THIS BID IS SIGNED					
BIDDING PROCEDURE ENQUIRIES MA	AY BE DIRECTED TO:	TECHNICAL INFORMATION MAY BE DIRECTED TO:			
DEPARTMENT/ORGANIZATION	ARTMENT/ORGANIZATION National Health Laboratory Service		Corrie Swart		
CONTACT PERSON	Fikile Hope Xaba	TELEPHONE NUMBER	082 809 5978		
TELEPHONE NUMBER	012 842 7579	FACSIMILE NUMBER	N/A		
FACSIMILE NUMBER	N/A	E-MAIL ADDRESS	cornelius.swart@nhls.ac.za		
E-MAIL ADDRESS	Fikile.xaba@nhls.ac.za				

## **PART B**

## TERMS AND CONDITIONS FOR BIDDING

1.	BID SUBMISSION:
1.1.	BIDS MUST BE DELIVERED BY THE STIPULATED TIME TO THE CORRECT ADDRESS. LATE BIDS WILL NOT BE ACCEPTED FOR CONSIDERATION.
1.2.	ALL BIDS MUST BE SUBMITTED ON THE OFFICIAL FORMS PROVIDED-(NOT TO BE RE-TYPED)
1.3.	THIS BID IS SUBJECT TO THE PREFERENTIAL PROCUREMENT POLICY FRAMEWORK ACT AND THE PREFERENTIAL PROCUREMENT REGULATIONS, 2017
2.	TAX COMPLIANCE REQUIREMENTS
2.1.	BIDDERS MUST ENSURE COMPLIANCE WITH THEIR TAX OBLIGATIONS.
2.2.	BIDDERS ARE REQUIRED TO SUBMIT THEIR UNIQUE PERSONAL IDENTIFICATION NUMBER (PIN) ISSUED BY SARS TO ENABLE THE ORGAN OF STATE TO VIEW THE TAXPAYER'S PROFILE AND TAX STATUS.
2.3.	APPLICATION FOR THE TAX COMPLIANCE STATUS (TCS) CERTIFICATE OR PIN MAY ALSO BE MADE VIA E-FILING. IN ORDER TO USE THIS PROVISION, TAXPAYERS WILL NEED TO REGISTER WITH SARS AS E-FILERS THROUGH THE WEBSITE WWW.SARS.GOV.ZA.
2.4.	FOREIGN SUPPLIERS MUST COMPLETE THE PRE-AWARD QUESTIONNAIRE IN PART B: 3.
2.5.	BIDDERS MAY ALSO SUBMIT A PRINTED TCC CERTIFICATE TOGETHER WITH THE BID.
2.6.	IN BIDS WHERE CONSORTIA / JOINT VENTURES / SUB-CONTRACTORS ARE INVOLVED, EACH PARTY MUST SUBMIT A SEPARATE TCC CERTIFICATE / PIN / CSD NUMBER.
2.7.	WHERE NO TCC IS AVAILABLE BUT THE BIDDER IS REGISTERED ON THE CENTRAL SUPPLIER DATABASE (CSD), A CSD NUMBER MUST BE PROVIDED.
3.	QUESTIONNAIRE TO BIDDING FOREIGN SUPPLIERS
3.1.	IS THE ENTITY A RESIDENT OF THE REPUBLIC OF SOUTH AFRICA (RSA)?
3.2.	DOES THE ENTITY HAVE A BRANCH IN THE RSA?
3.3.	DOES THE ENTITY HAVE A PERMANENT ESTABLISHMENT IN THE RSA?
3.4.	DOES THE ENTITY HAVE ANY SOURCE OF INCOME IN THE RSA?
3.5.	IS THE ENTITY LIABLE IN THE RSA FOR ANY FORM OF TAXATION?
CON	HE ANSWER IS "NO" TO ALL OF THE ABOVE, THEN IT IS NOT A REQUIREMENT TO REGISTER FOR A TAX MPLIANCE STATUS SYSTEM PIN CODE FROM THE SOUTH AFRICAN REVENUE SERVICE (SARS) AND IF NOT SISTER AS PER 2.3 ABOVE.
	URE TO PROVIDE ANY OF THE ABOVE PARTICULARS MAY RENDER THE BID INVALID. WILL BE CONSIDERED FROM PERSONS IN THE SERVICE OF THE STATE.
SNATU	JRE OF BIDDER:
D 4 6 !=	TALINIDED MAILOU THIS DID IS SIGNED
PACIT	Y UNDER WHICH THIS BID IS SIGNED:
TE:	

### **IMPORTANT NOTICE**

Bidders should ensure that proposal are hand delivered to : NHLS RESEPTION, BUILDING 23, GROUND FLOOR, CSIR PRETORIA CAMPUS, MEIRING NAUDE ROAD, BRUMMERIA, PRETORIA . If the bid is late, it will not be accepted for consideration.

Proposal must be submitted on the official forms – (not to be re-typed)

The contractor will be responsible for final measurements.

Writing must be in block letters and black ink.

This bid is subject to the Preferential Procurement Policy Framework Act and the Preferential Procurement Regulations, 2017, The General Conditions of Contract for Construction Works and any other special conditions of contract specified by CIDB.

### **TECHNICAL ENQUIRIES**

Should you require any further information in this regard, please do not hesitate to contact:

Name: Corrie Swart

Office Telephone No.: 082 809 5978

E-mail: cornelius.swart@nhls.ac.za

## **SUBMISSION DATA**

Clause number	Submission Data
	This Request for Proposal is intended to allow the successful bidder to specify and present their skills and expertise for the above mentioned services to NHLS. Final acceptance of any proposal is not guaranteed, this being the exclusive right of NHLS.
	Terms and conditions of expression of interest (Annex D as published/ amended by CIDB in August 2019) contained in Annex D of the CIDB Standard for Uniformity in Engineering and Construction Works Contracts (August 2019) as published in Government Gazette No 42622, Board Notice 423 of 2019 of 08 August 2019. (See www.cidb.org.za).
	The standard conditions of expression of interest for procurements make several references to the submission data for details that apply specifically to this proposal. The submission data shall have precedence in the interpretation of any ambiguity or inconsistency between it and the standard conditions of tender.
	Each item of submission data given below is cross-referenced to the clause in the standard conditions of tender to which it mainly applies.
E.1.1	The employer is the <b>NHLS</b>
E.1.2	For this contract, the following documents will be adopted:
	The <b>single volume</b> procurement document issued by the employer comprises of the following:
	The Request for Proposal
	Part E1: Tendering procedures
	E1.1 - Notice and invitation to Submit Proposal E1.2 - Submission data
	Part E2: Returnable documents
	E2.1 - List of returnable documents
	E2.2 - Returnable schedules
	The Contract
	Part C1 - Agreements and Contract data
	C1.1 – Form of offer and acceptance C1.2 – Contract data
	Part C2 - Pricing Data
	C2.1 – Pricing Instructions
	Part C3 - Scope of Works
	C3.1 – Description of the works C3.3 - Annexures
	Part C4 - Site Information
E.1.4	The Employer's agent for the purpose of this proposal is deemed to be the authorised and designated representative of the Employer:  Name: Fikile Hope Xaba (SCM Representative)  Address: Fikile.xaba@nhls.ac.za
E 1 E	
E.1.5	Cancellation and Re-Invitation of Tenders

E.1.5.1	An employer may, prior to the award of the tender, cancel a tender if-
	a) due to changed circumstances, there is no longer a need for the engineering and construction works
	specified in the invitation; b) funds are no longer available to cover the total envisaged expenditure; or
	c) no acceptable tenders are received.
	d) there is a material irregularity in the tender process.
E.1.5.2	The decision to cancel request for proposal must be published in the same manner in which the original request for proposal was advertised
E.1.5.3	An employer may only with the prior approval of the relevant treasury cancel request for proposaln invitation for the second time.
E.1.6	Procurement procedures
E.1.6.1	Unless otherwise stated in the submission data, a contract will, subject to E.3.13, be concluded with the tenderer who in terms of E.3.11 is the highest ranked or the tenderer scoring the highest number of tender evaluation points, as relevant, based on the tender submissions that are received at the closing time for tenders.
E.1.6.2	Competitive negotiation procedure
E.1.6.2.1	Where the submission data require that the competitive negotiation procedure is to be followed, tenderers shall submit tender offers in response to the proposed contract in the first round of submissions. Notwithstanding the requirements of E.3.4, the employer shall announce only the names of the tenderers who make a submission. The requirements of E.8 relating to the material deviations or qualifications which affect the competitive position of tenderers shall not apply.
E.1.6.2.2	All responsive tenderers or at least a minimum of not less than three responsive tenderers that are highest ranked in terms of the evaluation criteria stated in the submission data shall be invited to enter into competitive negotiations based on the principle of equal treatment, keeping confidential the proposed solutions and associated information.  Notwithstanding the provisions of E.2.17, the employer may request that tenders be clarified, specified and fine-tuned in order to improve a tenderer's competitive position provided that such clarification, specification, fine-tuning or additional information does not alter any fundamental aspects of the offers or impose substantial new requirements which restrict or distort competition or have a discriminatory effect.
E.1.6.2.3	At the conclusion of each round of negotiations, tenderers shall be invited by the employer to revise their tender offer based on the same evaluation criteria, with or without adjusted weightings. Tenderers shall be advised when they are to submit their best and final offer.
E.1.6.2.4	The contract shall be awarded in accordance with the provisions of E.3.11 and E.3.13 after tenderers have been requested to submit their best and final offer.
E.2	Tenderer's obligations
E.2.1	Eligibility
	Only those tenderers who satisfy the following criteria are eligible to submit tenders:
	a) CIDB registration
I	Only tenderers who are already registered in terms of the Construction Industry Development Regulations

	the tendered value, the	and subject to satisfactory proof of a tende e Employer lists in the table below the margidered exceeds the margins shown then such	ins it considers reasonable. However, in		
	Category of tender	Upper limits per CIDB Regulation 17	Employer's allowable margins		
	1	R0.5 m	The Employer will use its		
	2	R1.0 m	discretion in terms of CIDB		
	3	R3.0 m	Practice Note 3 on allowable margins to be accepted		
	4	R6.0 m			
	5	R10.0 m			
	6	R20.0 m			
	7	R60.0 m			
	8	R200.0 m			
	<ul> <li>(b) Availability of skills to manage and perform the contract</li> <li>(c) Previous experience on contracts of a similar value and nature</li> <li>(d) A letter on the companies' letterhead stating that the contractor has sufficient capacity to execute the project</li> <li>(e) Material Data Sheet</li> </ul>				
E.2.2	Cost of Tendering				
E.2.2.1	The Employer will not compensate the tenderer for any costs incurred in attending interviews or making ar submissions in the office of the Employer				
E.2.2.2	The cost of the tender documents charged by the employer shall be limited to the actual cost incurred by the employer for printing the documents. Employers must attempt to make available the tender documents on it website so as not to incur any costs pertaining to the printing of the tender documents.				
E.2.3	Check documents				
	Check the tender documents on receipt for completeness and notify the employer of any discrepancy omission.				
E.2.4	Confidentiality and co	ppyright of documents			
		Il matters arising in connection with the tend ne purpose of preparing and submitting a ten	• •		
	Acknowledge addenda				
E.2.6	Ackilowieuge addelic	ıa			

	account.
E.2.7	Clarification meeting: WITBANK HOSPITAL, MEET AT NHLS RECEPTION ON THE 31 OCTOBER 2024 FROM 12HOO TILL 12H30.
E.2.8	Seek clarification
	Request clarification of the tender documents, if necessary, by notifying the employer at least five (5) working days before the closing time stated in the submission data.
E.2.9	Insurance
	Be aware that the extent of insurance to be provided by the employer (if any) might not be for the full cove required in terms of the conditions of contract identified in the contract data. The tenderer is advised to seel qualified advice regarding insurance.
E.2.10	Pricing the tender offer
E.2.10.3	This contract shall not be subject to Contract Price Adjustments, foreign fluctuations, etc and all rates and prices shall remain FIXED, final and binding for the full duration of this contract.
E.2.11	Alterations to documents
	Do not make any alterations or additions to the tender documents, except to comply with instructions issued by the employer, or necessary to correct errors made by the tenderer. All signatories to the tender offer shall initial all such alterations.
E.2.12	Alternative tender offers
	No alternative tender offers will be considered
E.2.13	Submitting a tender offer
E.2.13.1	Submit one tender offer only as a single tendering entity to provide the whole of the works identified in the contract data and described in the scope of works, unless stated otherwise in the submission data.
E.2.13.2	Return all returnable documents to the employer after completing them in their entirety, either electronically (in they were issued in electronic format) or by writing legibly in non-erasable ink.
E.2.13.3	Submit the parts of the tender offer communicated on paper as an original as stated in the submission data with an English translation of any documentation in a language other than English, and the parts communicated electronically in the same format as they were issued by the employer.
E.2.13.4	Sign the original and all copies of the tender offer where required in terms of the submission data. The employer will hold all authorized signatories liable on behalf of the tenderer. Signatories for tenderers proposing to contract as joint ventures shall state which of the signatories is the lead partner whom the employer shall hold liable for the purpose of the tender offer.
E.2.13.5	Seal the original and each copy of the tender offer as separate packages marking the packages as "Technical proposal". Each package shall state on the outside the employer's address and identification details stated in the submission data, as well as the tenderer's name and contact address.
E.2.13.6	Bidders are requested to deliver the submission in <b>one envelope</b> . The Employer's address for delivery contender offers and identification details to be shown on each tender offer package are:
	Title to appear on envelope :
	Title to appear on envelope.

	Call For proposal to RENOVATIONS TO WITBANK LABORATORY IN MPUMALANGA. This envelope must contain the Returnables, SCM Documentation and Relevant Annexures. This envelope must contain printed copies of all the pages in this document, duly completed and signed, but excluding the pricing schedules (schedule of quantities), which must be submitted in a separate envelope as detailed below.
	Title to appear on envelope or attachment two(2):
	2. RFP NO.: (FINANCIAL PROPOSALS)
	<b>Call For proposal to RENOVATIONS TO WITBANK LABORATORY IN MPUMALANGA.</b> This envelope will contain the Pricing Schedules (Bills of Quantities) and Contract Agreement
	For identification purposes, bidders are requested to ensure that the envelopes containing the company's bids are clearly marked, and are easily identifiable by the company's logo or name.
	Location of tender box no NHLS RESEPTION, BUILDING 23, GROUND FLOOR, CSIR PRETORIA CAMPUS, MEIRING NAUDE ROAD, BRUMMERIA, PRETORIA
	Physical address: NHLS RESEPTION, BUILDING 23, GROUND FLOOR, CSIR PRETORIA CAMPUS, MEIRING NAUDE ROAD, BRUMMERIA, PRETORIA
	Identification details: RFQ BOX
E.2.13.7	Seal the original tender offer in an outer package that states on the outside only the employer's address and identification details as stated in the submission data.
E.2.13.8	Accept that the employer will not assume any responsibility for the misplacement or premature opening of the tender offer if the outer package is not sealed and marked as stated.
E.2.13.9	Accept that tender offers submitted by <b>telegraphic</b> , <b>telephonic</b> , <b>telex</b> , <b>facsimile</b> and <b>late proposal will not be accepted</b> by the employer.
E.2.14	Information and data to be completed in all respects
	Accept that tender offers, which do not provide all the data or information requested completely and, in the form, required, may be regarded by the employer as non-responsive.
E.2.15	Closing time
	The closing time for submission of proposal Call for proposal to supply and install alternative power supply in Letaba including site assessment.On the <b>08 November 2024 at 11h00am</b> .
	NHLS is not obliged to accept the lowest or any tender and reserves the right to accept any tender in whole or in part.
E.2.16	The tender offer validity period is 12 weeks from the closing date.
E.2.17	Clarification of tender offer after submission  Provide clarification of request for proposal in response to a request to do so from the employer during the evaluation of tender offers. This may include providing a breakdown of rates or prices and correction of arithmetical errors by the adjustment of certain rates or item prices (or both). No change in the competitive position of tenderers or substance of the tender offer is sought, offered, or permitted.
E.2.18.2	The Tenderer shall, when requested by the Employer to do so, submit the names of all management and supervisory staff that will be employed to supervise the labour-intensive portion of the works together with satisfactory evidence that such staff members satisfy the eligibility requirements.
E.2.19	Inspections, tests and analysis  Provide access during working hours to premises for inspections, tests and analysis as provided for in the

	submission data.	
E.2.20	Submit securities, bonds and policies  If requested, submit for the employer's acceptance before formation of the contract, all securities, bond guarantees, policies and certificates of insurance required in terms of the conditions of contract identified in the contract data.	
	Provide access during working hours to premises for inspections, tests and analysis as provided for in the submission data.	
E.2.23	The Tenderer is required to submit with his/her tender all documents and schedules listed under E2.1 and E2.2.	
Add the following new clause E.2.24	Canvassing and obtaining of additional information by tenderers  The Tenderer shall not make any attempt either directly or indirectly to canvass any of the Employer's officials or the Employer's agent in respect of his tender, after the opening of the tenders but prior to the Employer arriving at a decision thereon.  The Tenderer shall not make any attempt to obtain particulars of any relevant information, other than that disclosed at the opening of tenders.	
Add the following new clause  E.2.25	Prohibitions on awards to persons in service of the state  The Employer is prohibited to award a proposal to a person -  a) who is in the service of the state; or  b) if that person is not a natural person, of which any director, manager, principal shareholder or stakeholder is a person in the service of the state; or  c) a person who is an advisor or consultant contracted with the Department.  In the service of the state means to be -  a) a member of:  any municipal council;  any provincial legislature; or  the National Assembly or the National Council of Provinces;  b) a member of the board of directors of any municipal entity;  c) an official of any municipality or municipal entity;  d) an employee of any national or provincial department;  e) provincial public entity or constitutional institution within the meaning of the Public Finance Management Act, 1999 (Act No.1 of 1999);  f) a member of the accounting authority of any national or provincial public entity; or  g) An employee of Parliament or a provincial legislature.  In order to give effect to the above, the questionnaire for the declaration of interests in the tender of persons in service of state in part E2 of this procurement document must be completed.	
E.3	The employer's undertakings	
E.3.1	Respond to requests from the tenderer	
	The Employer will respond to requests for clarification received up to five (5) working days before the tender	

	closing time.					
E.3.2	Issue Addenda					
	Addenda will be issued until five (5) working days before the tender closing time.					
E.3.9	Arithmetical errors, omissions and discrepancies					
E.3.9.1	Check the highest ranked tenders or tenderers with the highest number of tender evaluation points after the evaluation of tender offers in accordance with E.3.11 for:  a) the gross misplacement of the decimal point in any unit rate; b) omissions made in completing the pricing schedule or bills of quantities; or c) arithmetic errors in:  i) line item totals resulting from the product of a unit rate and a quantity in bills of quantities or schedules of prices; or the summation of the prices.					
E.3.9.2	The arithmetical errors shall be corrected in the following manner:					
E.3.3.2	<ul> <li>a) Where there is a discrepancy between the amounts in words and amounts in figures, the amount in words shall govern.</li> <li>b) If bills of quantities or pricing schedules apply and there is an error in the line item total resulting from the product of the unit rate and the quantity, the line item total shall govern and the rate shall be corrected. Where there is an obviously gross misplacement of the decimal point in the unit rate, the line item total as quoted shall govern, and the unit rate shall be corrected.</li> <li>c) Where there is an error in the total of the prices either as a result of other  Corrections required by this checking process or in the tenderer's addition of prices, the total of the prices shall govern and the tenderer will be asked to revise selected item prices (and their rates if bills of quantities apply) to achieve the tendered total of the prices.</li> <li>The Tender Offer will be rejected if the tenderer does not correct or accept the Correction of the arithmetical error in the manner described above.</li> </ul>					
E.3.11	Functionality, Price and Preference  The purpose of the evaluation is to ensure and promote compliance with the Constitution, specifically Section 217, which provides that when organs of state contract for goods or services, they must do so in accordance with a system which is fair, equitable, transparent, competitive and cost-effective. The evaluation of bids will be undertaken in 3 stages.					
	Technical Proposal					
	Administrative. / Mandatory Requirements					
	The Technical proposal will be evaluated on Administrative. / Mandatory Requirements and Functionality.					
	Bidders who fail to meet the minimum requirements for the Technical proposal will not be considered further.					
	Financial Proposal will be evaluated on price and B-BBEE specific goals as outlined in this document.					
	During this phase bid documents will be reviewed to determine the compliance with Standard Bidding Documents (SBD), SCM returnable, tax matters and contractor had registered on Central Data Base (CSD) and Construction Industry Development Board (CIDB). All returnable documents must be submitted with the bid documents at the closing date and time of the bid. Bids which do not satisfy the compliance criteria will be disqualified and will not be evaluated further on pre-qualification criteria.					
	The bid proposal will be screened for compliance with administrative requirements as indicated below and bidders must circle the correct answer					

Item No.	Administrative Requirements	Check/Compliance	Non- submission shall result in disqualificatio n
1	Master Bid Document	provided and bound	*YES
2	1 Copy of Bid Document	provided and bound	**N/A
Included in the E	lid Document		
4	SCM - SBD 1 - Invitation to Bid	Completed and signed	*YES
5	SCM - SBD 2 - Tax Clearance Certificate Requirements	Attached CSD registration number/SARS PIN and CSD summary report	*YES
6	SCM - SBD 4 - Declaration of Interest	Completed and signed	*YES
7	SCM - SBD 6.1 - Preference Points Claim Form in terms of the Preferential Procurement Regulations 2017	Completed and signed	*YES
8	SCM - SBD 8 – Declaration of Bidder's Past Supply Chain Management Practices	Completed and signed	*YES
9	SCM – SBD 7.1 – Contract form, purchase of good/ works	Completed and signed	*YES
10	SCM - SBD 9 - Certificate of Independent Bid Determination	Completed and signed	*YES
11	In case of bids where Consortia / Joint Ventures, Consortia/Joint Venture agreement signed by both parties must be submitted with bid proposal	JV agreement completed and signed, if applicable	*YES

<sup>\*</sup>YES – NHLS reserves the right to reject proposals that are not submitted in the prescribed format or where information presented is illegible or incomplete and will not be further evaluated for Mandatory Requirements (Phase 2)

## **Functionality**

The Functional Evaluation will be carried out to assess the Bidder's suitability to undertake the project, the Bidder's Company Experience, Key Personnel Experience, Proposal with project plan and delivery capacity will be evaluated.

<sup>\*\*</sup>NO – NHLS reserves the right to request such information during the evaluation process of the proposal and such information must be presented within short notice.

	Bidders who fail to obtain minimum requirements for functionality will not be considered further.
E.3.13.1	Request for proposal will only be accepted on condition that:
	<ul> <li>a) the tenderer is registered with the Construction Industry Development Board in an appropriate contractor grading designation;</li> </ul>
	b) the bidder or any of its directors is not listed in the Register of Bid Defaulters in terms of the Prevention and Combating of Corrupt Activities Act of 2004 as a person prohibited from doing business with the public sector;
	c) the bidder has not: i. abused the Employer's Supply Chain Management System; or
	ii. failed to perform on any previous contract and has been given a written notice to this effect.
	d) Has completed the Compulsory Enterprise Questionnaire, SBD4, 6.1, 7.1, 8,9 and there are no conflicts of interest which may impact on the tenderer's ability to perform the contract in the best interests of the employer or potentially compromise the tender process
	Has submitted the documentation listed in E2.21 and E2.22
E.3.18	The number of paper copies of the signed contract to be provided by the employer is ONE.

## PART E2: RETURNABLE DOCUMENTS AND SCHEDULES

## **E2.1 LIST OF RETURNABLE DOCUMENTS**

The following documents must be returned by the Bidder for evaluation purposes in addition to the Schedule listed in previous paragraphs.

(FA	THE FOLLOWING DOCUMENTS MUST BE FURNISHED AILURE TO SUBMIT COMPULSORY DOCUMENTATION WILL RESULT IN YOUR BID BEING DISQUALIFIED)	YES	NO
1	Tax Compliance (Provide PIN)	Yes 🗌	No 🗌
2	B-BEE Certificate issued by SANAS accredited verification agent/ OR AFFIDAVIT FOR EME/QSE ON DTI FORMAT	Yes	No 🗌
3	Proof of valid registration with CIDB	Yes 🗌	No 🗌
4	Signed Declaration of Interest	Yes 🗌	No 🗌
5	Certificate of Independent Bidder determination	Yes 🗌	No 🗌
6	Valid COID certificate issued by the Department of Labour	Yes 🗌	No 🗌
7	Submit an original Briefing session certificate of attendance	Yes 🗌	No 🗌
8	Fully Completed and Signed all other SBD forms	Yes 🗌	No 🗌

## FORM B: VENDOR NUMBER REGISTRATION WITH CENTRAL SUPPLIER DATABASE

- 1. Bidders must submit Vendor Number Registration with Central Supplier Database
- 2. Failure to submit the Vendor Number Registration with Central Supplier Database may result with the bidder being disqualified.

ENTITY NAME	
CSD REGISTRATION No:	
NAME	
SIGNATURE OF BIDDER	
DATE	
CAPACITY UNDER W	HICH

## FORM C: TAX COMPLIANCE

#### **CONDITIONS PERTAINING TO TAX**

### TAX CLEARANCE CERTFICATE REQUIREMENTS

It is a condition of bid that the taxes of the successful bidder <u>must</u> be in order, or that satisfactory arrangements have been made with South African Revenue Service (SARS) to meet the bidder's tax obligations.

- 1. Any person who requires his or her tax compliance status to be disclosed to a Government institution or department, for purposes of submitting a bid or to confirm its good standing after the phasing out of paper based TCCs must request a unique security personal identification number (PIN) from SARS.
- 2. Very important to note is that the disclosure of a bidder's tax compliance status is an express condition for all acceptable Government bids. Failure to make the relevant disclosures will invalidate your bid and your response will be null and void.
- 3. The Government institution or department must use the PIN referred to above to verify a person's tax compliance status with SARS.
- 4. Bidders to complete the table below and provide a unique security personal identification number (PIN) from SARS which will enable the MW to access online real-time verification of a person's tax compliance status with the electronic Tax Compliance Status (TCS) system. Failure to submit the PIN may result in the bid being disqualified.

Full name of bidder:	Electronic Tax Compliance Status  System PIN No:

NAME:
SIGNATURE OF BIDDER
DATE
CAPACITY UNDER WHICH BID IS SIGNED

#### FORM D: PREFERENCE SCHEDULE

## PREFERENCE POINTS CLAIM FORM IN TERMS OF THE PREFERENTIAL PROCUREMENT REGULATIONS 2017

This preference form must form part of all bids invited. It contains general information and serves as a claim form for preference points for Broad-Based Black Economic Empowerment (B-BBEE) Status Level of Contribution

NB: BEFORE COMPLETING THIS FORM, BIDDERS MUST STUDY THE GENERAL CONDITIONS, DEFINITIONS AND DIRECTIVES APPLICABLE IN RESPECT OF B-BBEE, AS PRESCRIBED IN THE PREFERENTIAL PROCUREMENT REGULATIONS, 2017.

#### 1. GENERAL CONDITIONS

- 1.1 The following preference point systems are applicable to all bids:
  - the 80/20 system for requirements with a Rand value of up to R50 000 000 (all applicable taxes included); and
  - the 90/10 system for requirements with a Rand value above R50 000 000 (all applicable taxes included).

1.2

- a) The value of this bid is estimated to be below R50 000 000 (all applicable taxes included) and therefore the 80/20 preference point system shall be applicable;
- 1.3 Points for this bid shall be awarded for:
  - (a) Price: and
  - (b) B-BBEE Status Level of Contributor.
- 1.4 The maximum points for this bid are allocated as follows:

	POINTS
PRICE	80
Specific Goals	20
Total points for Price and Specific Goals must not exceed	100

- 1.5 Failure on the part of a bidder to submit proof of B-BBEE Status level of contributor together with the bid, will be interpreted to mean that preference points for B-BBEE status level of contribution are not claimed.
- 1.6 The purchaser reserves the right to require of a bidder, either before a bid is adjudicated or at any time subsequently, to substantiate any claim in regard to preferences, in any manner required by the purchaser.

### 2. **DEFINITIONS**

- (a) **"B-BBEE"** means broad-based black economic empowerment as defined in section 1 of the Broad-Based Black Economic Empowerment Act;
- (b) "B-BBEE status level of contributor" means the B-BBEE status of an entity in terms of a code of good practice on black economic empowerment, issued in terms of section 9(1) of the Broad-Based Black Economic Empowerment Act;
- (c) "bid" means a written offer in a prescribed or stipulated form in response to an invitation by an organ of state for the provision of goods or services, through price proposal, advertised competitive bidding processes or proposals;
- (d) "Broad-Based Black Economic Empowerment Act" means the Broad-Based Black Economic Empowerment Act, 2003 (Act No. 53 of 2003);
- (e) "EME" means an Exempted Micro Enterprise in terms of a code of good practice on black economic empowerment issued in terms of section 9 (1) of the Broad-Based Black Economic Empowerment Act;
- (f) "functionality" means the ability of a tenderer to provide goods or services in accordance with specifications as set out in the tender documents.
- (g) "prices" includes all applicable taxes less all unconditional discounts;
- (h) "proof of B-BBEE status level of contributor" means:
  - 1) B-BBEE Status level certificate issued by an authorized body or person;
  - 2) A sworn affidavit as prescribed by the B-BBEE Codes of Good Practice;
  - 3) Any other requirement prescribed in terms of the B-BBEE Act;
- (i) "QSE" means a qualifying small business enterprise in terms of a code of good practice on black economic empowerment issued in terms of section 9 (1) of the Broad-Based Black Economic Empowerment Act;

## PART 1

(j) "rand value" means the total estimated value of a contract in Rand, calculated at the time of bid invitation, and includes all applicable taxes;

#### POINTS AWARDED FOR SPECIFIC GOALS

4.1.In terms of Regulation 4(2); 5(2); 6(2) and 7(2) of the Preferential Procurement Regulations, preference points must be awarded for specific goals stated in the tender. For the purposes of this tender the tenderer will be allocated points based on the goals stated in table 1 below as may be supported by proof/ documentation stated in the conditions of this tender:

4.2.In cases where organs of state intend to use Regulation 3(2) of the Regulations, which states that, if it is unclear whether the 80/20 or 90/10 preference point system applies, an organ of state must, in the tender documents, stipulate in the case of—

(a) an invitation for tender for income-generating contracts, that either the 80/20 or 90/10 preference point system will apply and that the highest acceptable tender will be used to determine the applicable preference point system; or

(b) any other invitation for tender, that either the 80/20 or 90/10 preference point system will apply and that the lowest acceptable tender will be used to determine the applicable preference point system,

then the organ of state must indicate the points allocated for specific goals for both the 90/10 and 80/20 preference point system.

Points awarded for historically disadvantaged individuals

Preference points for HDI's are calculated on their percentage shareholding in a business, provided that they are actively involved in and exercise control over the enterprise. The following formula is prescribed

Where:

NEP = Points awarded for equity ownership by an HDI

NOP = The maximum number of points awarded for equity by an HDI in that specific category

EP = The percentage of equity ownership by an HDI within the enterprise or business, determined in accordance with the definition of HDI's.

A consortium or joint venture (including unincorporated consortia and joint ventures) must submit a consolidated B-BBEE Status Level Verification certificate for every separate tender

Table 1: Specific goals for the tender and points claimed are indicated per the table below.

(Note to organs of state: Where either the 90/10 or 80/20 preference point system is applicable, corresponding points must also

be indicated as such.

Note to tenderers: The tenderer must indicate how they claim points for each preference point system. POINTS AWARDED FOR B-BBEE STATUS LEVEL OF CONTRIBUTOR

2.1 In terms of Regulation 6 (2) and 7 (2) of the Preferential Procurement Regulations, preference points must be awarded to a bidder for attaining the Specific Goals status level of contribution in accordance with the table below:

The specific goals allocated points in terms of this tender	Number of points allocated (90/10 system) (To be completed by the organ of state)	Number of points allocated (80/20 system) (To be completed by the organ of state)	Number of points claimed  (90/10 system)  (To be completed by the tenderer)	Percentage owned (To be completed by the tenderer)	points claim (80/20 system	be by
HDI		4		%		
WOMAN		4		%		
DISABLED		4		%		
YOUTH		4		%		

Locality	4		
• Limpopo - Mpumalanga = 4			
• National = 2			
TOTAL POINTS	20		

3.1	bluders	s who claim po		spect of Spe	ecific Goals Status	20101010001111		inplote the i	ollowing.
SPEC	CIFIC GO	ALS STATUS	S LEVEL	OF CONTRI	IBUTOR CLAIME	D IN TERMS O	F PARAGRAP	PHS 1.4 AND	O 4.1
4.1	Specific	c Goals	=	(maximum	of 10 or 20 points	)			
	,		•		7.1 must be in ac Goals status leve		the table reflec	cted in para	graph 4.1 and must b
SUB-	CONTRA	ACTING							
5.1	Will any	portion of the	e contract	be sub-con	tracted?				
(	Tick app	licable box)							
Γ	YES	NO	)						
<b>L</b>	lf v.o.o	indicate							
5.1.1	•	, indicate:						21	_
	i)	-			will be subcontrac				
	ii)	The name of	of the sub-	contractor					
	iii)	The B-BBEI	E status le	evel of the su	ub-contractor				
	iv)	Whether the	e sub-conf	tractor is an	EME or QSE				
	,	(Tick applicable box)							
				·					
		YES	N	10	to how if outboom			4 of D	on formatical Decomposition
	v)	YES	ticking th	10	te box, if subcon	tracting with ar	ı enterprise in	terms of Pr	referential Procuremen
ſ		YES Specify, by Regulations	ticking the	NO le appropria			EME	QSE	referential Procuremen
	Designate	YES Specify, by Regulations ed Group: An	ticking the	NO le appropria	te box, if subcon				referential Procuremen
E	Designate	YES Specify, by Regulations ed Group: An	ticking the s,2017:	NO le appropria			EME	QSE	referential Procuremen
E	Designate Black peo	YES Specify, by Regulations ed Group: An ople ople who are y	ticking the s,2017:  EME or Converted the syouth	NO le appropria			EME	QSE	referential Procuremen
E	Designate Black pec Black pec Black pec	YES Specify, by Regulations ed Group: An	ticking the s,2017:  EME or Converted women	NO le appropria			EME	QSE	referential Procuremen
E E	Designate Black peo Black peo Black peo Black peo	YES  Specify, by Regulations and Group: An ople ople who are your ople who are your ople with disaless.	ticking the s,2017:  EME or Convouth women bilities	e appropria		ed by:	EME	QSE	referential Procuremen
E E	Designate Black pec Black pec Black pec Black pec	YES  Specify, by Regulations and Group: An ople ople who are your ople who are your ople with disaless.	ticking the s,2017:  EME or Converted women bilities ural or und	e appropria	at last 51% owne	ed by:	EME	QSE	referential Procuremen
E E (	Designate Black pec Black pec Black pec Black pec Black pec	YES  Specify, by Regulations and Group: An ople ople who are yople with disall ople living in respectively.	ticking the s,2017:  EME or Converted women bilities ural or und black ped	derdevelope	at last 51% owne	ed by:	EME	QSE	referential Procuremen
E E (	Designate Black pec Black pec Black pec Black pec Black pec	YES  Specify, by Regulations and Group: An ople ople who are you ople with disallople living in rejive owned by	ticking the s,2017:  EME or Converted women bilities ural or und black ped	derdevelope	at last 51% owne	ed by:	EME	QSE	referential Procuremen
E E C C E E	Designate Black pec Black pec Black pec Black pec Cooperati Black pec	YES  Specify, by Regulations and Group: An ople ople who are you ople with disallople living in relive owned by ople who are relived to the population of th	ticking the s,2017:  EME or Converted women bilities ural or und black ped	derdevelope	at last 51% owne	ed by:	EME	QSE	referential Procuremen
E E C C E E	Designate Black pec Black pec Black pec Black pec Cooperati	YES  Specify, by Regulations and Group: An ople ople who are you ople with disallople living in relive owned by ople who are relived to the population of th	ticking the s,2017:  EME or Converted women bilities ural or und black ped	derdevelope	at last 51% owne	ed by:	EME	QSE	referential Procuremen
E E E C C F F F F F F F F F F F F F F F	Designate Black pec Black pec Black pec Black pec Cooperati Black pec Any EME Any QSE	YES  Specify, by Regulations and Group: An ople ople who are you ople with disallople living in relive owned by ople who are relived to the population of th	ticking the size of Control of Co	derdeveloped terans	d areas or townsh	ed by:	EME	QSE	referential Procuremen
E E E C C F F F F F F F F F F F F F F F	Designate Black peo Black peo Black peo Black peo Black peo Cooperati Black peo Any EME Any QSE	YES  Specify, by Regulations and Group: An ople ople who are yople who are yople with disalople living in rejive owned by ople who are refined and	ticking the s,2017:  EME or Convouth women bilities ural or und black peomilitary versions.	derdeveloper terans	d areas or townsh	ed by:	EME	QSE	referential Procuremen
E E C C F F F F F F F F F F F F F F F F	Designate Black peo Black peo Black peo Black peo Black peo Cooperati Black peo Any EME Any QSE  ARATIO	YES  Specify, by Regulations and Group: An ople ople who are you ople with disal ople living in relive owned by ople who are relived owned by ople who are relived to the country of the c	ticking the s,2017:  EME or Converted women bilities ural or und bilitiary version black peomilitary versions.	derdeveloper terans  COMPANY	d areas or townsh	ed by:	EME	QSE	referential Procuremen
E E E C C F F F F F F F F F F F F F F F	Designate Black peo Black peo Black peo Black peo Black peo Cooperati Black peo Any EME Any QSE  ARATIO Name of	YES  Specify, by Regulations and Group: An ople ople who are you ople with disallople living in relive owned by ople who are relive owned by ople who are relived of company/fin of company/fin of company/fin open with the compa	ticking the size of Control of Co	derdeveloper ple terans	d areas or townsh	ed by:	EME V	QSE	referential Procuremen

**BID DECLARATION** 

3.

4.

5.

6.

		Partnership/Joint Venture / Consortium
		One person business/sole propriety
		Close corporation
		Company
		(Pty) Limited
	[Tic	K APPLICABLE BOX]
6.5	DESC	RIBE PRINCIPAL BUSINESS ACTIVITIES
6.6	COM	PANY CLASSIFICATION
		Manufacturer
		Supplier
		Professional service provider
		Other service providers, e.g. transporter, etc.
	[TIC	K APPLICABLE BOX]
6.7	Total	number of years the company/firm has been in business:
6.8	based	the undersigned, who is / are duly authorised to do so on behalf of the company/firm, certify that the points claimed on the Specific Goals status level of contributor indicated in paragraphs 1.4 and 6.1 of the foregoing certificate es the company/ firm for the preference(s) shown and I / we acknowledge that:
	i)	The information furnished is true and correct;
	ii)	The preference points claimed are in accordance with the General Conditions as indicated in paragraph 1 of this form;
	iii)	In the event of a contract being awarded as a result of points claimed as shown in paragraphs 1.4 and 6.1, the contractor may be required to furnish documentary proof to the satisfaction of the purchaser that the claims are correct;
	iv)	If the B-BBEE status level of contributor has been claimed or obtained on a fraudulent basis or any of the conditions o contract have not been fulfilled, the purchaser may, in addition to any other remedy it may have –
		(a) disqualify the person from the bidding process;
		(b) recover costs, losses or damages it has incurred or suffered as a result of that person's conduct;
		(c) cancel the contract and claim any damages which it has suffered as a result of having to make less favourable arrangements due to such cancellation;
		(d) recommend that the bidder or contractor, its shareholders and directors, or only the shareholders and directors who acted on a fraudulent basis, be restricted by the National Treasury from obtaining business from any organ of state for a period not exceeding 10 years, after the <i>audi alteram partem</i> (hear the other side) rule has been applied; and
		(e) forward the matter for criminal prosecution.
0050		
SSES		
		SIGNATURE(S) OF BIDDERS(S)
		DΔTF

		ADDRESS
1.	<u>:</u>	
2.		
	<u> </u>	

## FORM E: PROOF OF REGISTRATION WITH CIDB

- 1. Attach proof of CIDB registration to this page.
- 2. In the case of a joint venture / consortium (excluding consulting engineering partners) parties must each attach original or certified copy of their CIDB registration certificate.

Firm	CRS Number	CIDB Grading	Lead Partner (Indicate with X)
Combined CIDB Grading for Joint Ve	nture / Consortium:		

(Calculator is available at <a href="https://registers.cidb.org.za/common/jvcalc.asp">https://registers.cidb.org.za/common/jvcalc.asp</a>)

•	/ she is duly authorised to do so on behalf of the enterprise, confirms that n my personal knowledge and are to the best of my belief both true and
Person authorized to sign the bid:	
Full name (in BLOCK letters):	
Signature:	
Date:	

## FORM F: DECLARATION OF INTEREST

- 1. No bid will be accepted from persons in the service of the state<sup>1</sup>.
- 2. Any person, having a kinship with persons in the service of the state, including a blood relationship, may make an offer or offers in terms of this invitation to bid. In view of possible allegations of favouritism, should the resulting bid, or part thereof, be awarded to persons connected with or related to persons in service of the state, it is required that the bidder or their authorised representative declare their position in relation to the evaluating/adjudicating authority.
- 3. In order to give effect to the above, the following questionnaire must be completed and submitted with the bid.
- 3.1 Full Name of bidder or his or her representative:
- 3.2 Identity Number:
- 3.3 Position occupied in the Company (director, trustee, shareholder<sup>2</sup>):
- 3.4 Company Registration Number:
- 3.5 Tax Reference Number:

'SCM Regulations: "in the service of the state" means to be –

- (a) a member of -
  - (i) any municipal council;
  - (ii) any provincial legislature; or
  - (iii) the national Assembly or the national Council of provinces;
- (b) a member of the board of directors of any municipal entity;
- (c) an official of any municipality or municipal entity;
- (d) an employee of any national or provincial department, national or provincial public entity or constitutional institution within the meaning of the Public Finance Management Act, 1999 (Act No.1 of 1999);
- (e) a member of the accounting authority of any national or provincial public entity; or
- (f) an employee of Parliament or a provincial legislature.
  - <sup>2</sup> Shareholder" means a person who owns shares in the company and is actively involved in the management of the company or business and exercises control over the company.
- 3.6 VAT Registration Number
- 3.7 The names of all directors / trustees / shareholders members, their individual identity numbers and state employee numbers must be indicated in paragraph 4 below.
- 3.8.1 If yes, furnish particulars

3.9	Have you been in the service of the state for the past twelve months?	YES / NO
3.9.1	If yes, furnish particulars	
3.10	Do you have any relationship (family, friend, other) with persons in the service of the state and who evaluation and or adjudication of this bid?	•
3.10.1	If yes, furnish particulars	
3.11	Are you, aware of any relationship (family, friend, other) between any other bidder and any persons who may be involved with the evaluation and or adjudication of this bid?	
3.11.1	If yes, furnish particulars.	
3.12	Are any of the company's directors, trustees, managers, principle shareholders or stakeholders in s	ervice of the state?
3.12.1	If yes, furnish particulars	-
3.13	Are any spouse, child or parent of the company's directors, trustees, managers, principle sharehold of the state?	lers or stakeholders in service YES / NO
3.13.1	If yes, furnish particulars	
3.14	Do you or any of the directors, trustees, managers, principle shareholders, or stakeholders of this cany other related companies or business whether or not they are bidding for this contract.	
3.14.1	If yes, furnish particulars	-

Full Name	Identity Number	State Employee Numl
Signature		Date
Capacity		Name of Bidder

## FORM G: DECLARATION OF BIDDER'S PAST SUPPLY CHAIN MANAGEMENT PRACTICES

- 1 This Standard Bidding Document must form part of all bids invited.
- It serves as a declaration to be used by institutions in ensuring that when goods and services are being procured, all reasonable steps are taken to combat the abuse of the supply chain management system.
- The bid of any bidder may be disregarded if that bidder, or any of its directors have
  - a. Abused the institution's supply chain management system;
  - b. committed fraud or any other improper conduct in relation to such system; or
  - c. failed to perform on any previous contract.
- In order to give effect to the above, the following questionnaire must be completed and submitted with the bid.

() ti p T ()	s the bidder or any of its directors listed on the National Treasury's Database of Restricted Suppliers as companies or persons prohibited from doing business with the public sector?  (Companies or persons who are listed on this Database were informed in writing of this restriction by the Accounting Officer/Authority of the institution that imposed the restriction after the audi alterampeartem rule was applied).  The Database of Restricted Suppliers now resides on the National Treasury's website ( <a href="www.treasury.gov.za">www.treasury.gov.za</a> ) and can be accessed by clicking on its link at the bottom of the home pg if so, furnish particulars:	Yes	No 🗌
ti p T ( <u>(</u>	the Accounting Officer/Authority of the institution that imposed the restriction after the audi alteram partem rule was applied).  The Database of Restricted Suppliers now resides on the National Treasury's website ( <a href="https://www.treasury.gov.za">www.treasury.gov.za</a> ) and can be accessed by clicking on its link at the bottom of the home pg		
.1.1	(www.treasury.gov.za) and can be accessed by clicking on its link at the bottom of the home pg		
	f co. furnish particulars:		
2 1	il 50, tuttisti particulais		
	s the bidder or any of its directors listed on the Register for Tender Defaulters in terms of section 29 of the Prevention and Combating of Corrupt Activities Act (No 12 of 2004)?	Yes	No
	The Register for Tender Defaulters can be accessed on the National Treasury's website (www.treasury.gov.za) by clicking on its link at the bottom of the home page.		
.2.1 If	f so, furnish particulars:		
	Was the bidder or any of its directors convicted by a court of law (including a court outside of the Republic of South Africa) for fraud or corruption during the past five years?	Yes	No
.3.1 If	f so, furnish particulars:		
.4 V	Was any contract between the bidder and any organ of state terminated during the past five years on account of failure to perform on or comply with the contract?	Yes	No
.4.1	f so, furnish particulars:		
	CERTIFICATION		
	RSIGNED (FULL NAME) CERTIFY THAT THE INFO	RMATION	1 FURNIS

POSITION	NAME OF BIDDER

## FORM H: OHS ACT DECLARATION AND SUBMISSION

The Bidder declares him/herself/herself to be conversant with the following:

- 1. All the requirements, regulations and standards of the Occupational Health and Safety Act (Act 85 of 1993), hereinafter referred to as "The Act", together with its amendments and with special reference to the following Sections of the Act:
  - i) Section 8: General duties of Employers to their employees
  - ii) Section 9: General duties of Employers and self-employed persons to persons other than employees.
  - iii) Section 13: Duty to Inform
  - iv) Section 37: Acts or omissions by employees or mandatories
  - v) Sub-section 37(2) relating to the purpose and meaning of this Agreement
- 2. Construction Regulations, 2014 (Government Notice R.84) pertaining to the Contractor and to all his Subcontractors, or any amendments thereto.
- 3. Bid document Volume 3: Project Specification PD: Supplement to Volume 5: Specification for Occupational Health and Safety.
- 4. Bid document Volume 3: C1.7 Agreement in terms of Occupational Health and Safety Act.

The Bidder declares that he has or will obtain the necessary knowledge, competence and resources to comply fully with all OHS requirements should he be awarded the contract.

The Bidder confirms that he has included with his bid a written proposal describing how he will comply with OHS requirements

Signature	 Date	
Name	 Capacity	
Bidder		

### FORM J: SCHEDULE OF BIDDER'S EXPERIENCE IN RENOVATIONS TO WITBANK LABORATORY IN MPUMALANGA.

NHLS shall not be held responsible for incorrect judgement misled by unclear written letters/words on the forms below, to be completed by the Bidder(s). Attachment shall strictly be made where specified and at the correct location, any attachment other than what has been requested by NHLS, shall be completely ignored, and scored zero, where points allocation is required.

When completing Forms, Bidder(s) may make copies of the original Forms, should the provided forms be inadequate for their completion of the information required. Forms must be hand completed in black ink, no computer regenerated forms will be accepted. Forms must be completed in full, forms not completed in full shall be rejected by scoring zero.

# PART C1: AGREEMENT AND CONTRACT DATA

# C1.1: FORM OF OFFER AND ACCEPTANCE (COMPULSORY)

**Acceptance** 

The employer, identified in the acceptance signature block, has solicited offers to enter into a contract for the procurement of:
The tenderer, identified in the offer signature block, has examined the documents listed in the submission data and addenda thereto a listed in the returnable schedules, and by submitting this offer has accepted the conditions of tender.
By the representative of the tenderer, deemed to be duly authorized, signing this part of this form of offer and acceptance, the tenderer offers to perform all of the obligations and liabilities of the contractor under the contract including compliance with all its terms and conditions according to their true intent and meaning for an amount to be determined in accordance with the conditions of contract identified in the contract data.
THE OFFERED TOTAL OF THE PRICES INCLUSIVE OF VALUE ADDED TAX IS:
Rand(in words);
R (in figures)
This offer may be accepted by the employer by signing the acceptance part of this form of offer and acceptance and returning one copy of this document to the tenderer before the end of the period of validity stated in the submission data, whereupon the tenderer becomes the party named as the contractor in the conditions of contract identified in the contract data.
Signature(s)
for the tenderer
(Name and
Name and signature of witness

By signing this part of this form of offer and acceptance, the employer identified below accepts the tenderer's offer. In consideration thereof, the employer shall pay the contractor the amount due in accordance with the conditions of contract identified in the contract data. Acceptance of the tenderer's offer shall form an agreement between the employer and the tenderer upon the terms and conditions contained in this agreement and in the contract that is the subject of this agreement.

The terms of the contract are contained in:

Part C1: Agreements and contract data (which includes this agreement)

Part C2: Pricing data
Part C3: Scope of work
Part C4: Site information

and drawings and documents or parts thereof, which may be incorporated by reference into the above listed Parts.

Deviations from and amendments to the documents listed in the submission data and any addenda thereto as listed in the returnable schedules as well as any changes to the terms of the offer agreed by the tenderer and the employer during this process of offer and acceptance, are contained in the schedule of deviations attached to and forming part of this form of offer and acceptance. No amendments to or deviations from said documents are valid unless contained in this schedule.

The tenderer shall within two weeks after receiving a completed copy of this agreement, including the schedule of deviations (if any), contact the employer's agent (whose details are given in the contract data) to arrange the delivery of any securities, bonds, guarantees, proof of insurance and any other documentation to be provided in terms of the conditions of contract identified in the contract data. Failure to fulfill any of these obligations in accordance with those terms shall constitute a repudiation of this agreement.

Notwithstanding anything contained herein, this agreement comes into effect on the date when the tenderer receives one fully completed original copy of this document, including the schedule of deviations (if any). Unless the tenderer (now contractor) within five working days of the date of such receipt notifies the employer in writing of any reason why he cannot accept the contents of this agreement, this agreement shall constitute a binding contract between the parties.

Name(s)	ONLY TO B	E COMPLETED
• •		TANCE STAGE
signature		
of witness		Date

#### **Schedule of Deviations**

#### Notes:

- 1. The extent of deviations from the tender documents issued by the Employer prior to the tender closing date is limited to those permitted in terms of the Conditions of Expression of Interest,
- 2. A Tenderer's covering letter shall not be included in the final contract document. Should any matter in such letter, which constitutes a deviation as aforesaid, become the subject of Agreements reached during the process of offer and acceptance, the outcome of such Agreement shall be recorded here,
- 3. Any other matter arising from the process of offer and acceptance either as a confirmation, clarification or change to the tender documents and which it is agreed by the Parties becomes an obligation of the contract shall also be recorded here,
- 4. Any change or addition to the tender documents arising from the above Agreements and recorded here, shall also be incorporated into the final draft of the Contract,

2 Subject	AT ACCEPTANCE STAGE	) -
3 Subject		
4 Subject		

By the duly authorised representatives signing this Schedule of Deviations, the Employer and the Tenderer agree to and accept the foregoing Schedule of Deviations as the only deviations from and amendments to the documents listed in the Submission data and Addenda thereto as listed in the Tender Schedules, as well as any confirmation, clarification or change to the terms of the offer agreed by the Tenderer and the Employer during this process of offer and acceptance.

It is expressly agreed that no other matter whether in writing, oral communication or implied during the period between the issue of the Tender Documents and the receipt by the Tenderer of a completed signed copy of this Agreement shall have any meaning or effect in the Contract between the parties arising from this Agreement.

FOR THE TENDERER:			
Signature(s)			
Name(s)			
Capacity			
	[Name and address of organisation	]	
Name and signature of witness			Date
FOR THE EMPLOYER:			
Signature(s)			
Name(s)			
Capacity			
	[Name and address of organisation	]	
Name and signature of witness			Date

# ONLY TO BE COMPLETED AT ACCEPTANCE STAGE

# **CONFIRMATION OF RECEIPT**

The Tenderer (now Contractor), identified in the Offer part of this Agreement, hereby confirms receipt from the Employer, identified in the Acceptance part of this Agreement, of one fully completed original copy of this Agreement, including the Schedule of Deviations (if any) today:

The[day]	
of	[month]
20[year]	
at	[place]
For the Contractor:	Signature
	Name
	Capacity
Signature and name of witness:	Signature
	Name

# ONLY TO BE COMPLETED AT ACCEPTANCE STAGE

# **C1.2 CONTRACT DATA**

PROJECT TITLE:	
CONTRACT NO:	

# C.1.2 Contract Data

The General Conditions of Contract for Construction Works, Third Edition (2015) published by the South African Institution of Civil Engineering, Private Bag X200, Halfway House, 1685, is applicable to this Contract and is obtainable from www.saice.org.za.

The General Conditions of Contract for Construction Works make several references to the Contract Data for specific data, which together with these conditions collectively describe the risks, liabilities and obligations of the contracting parties and the procedures for the administration of the Contract. The Contract Data shall have precedence in the interpretation of any ambiguity or inconsistency between it and the General Conditions of Contract.

Part 1: Data provided by the Employer

Olavia	Deta
Clause	Data
1.1.1.13	Clause 1.1.1.13: Defects Liability Period
	The Defeate Liebility Devied is 6 months, approximately the date of the Contiferate of Completion
1.1.1.14	The Defects Liability Period is <b>6 months</b> , measured from the date of the Certificate of Completion
1.1.1.14	Clause 1.1.1.14: Due Completion Date
	The time for achieving Practical Completion is 2 months after the Commencement Date
1.1.1.15	The name of the Employer is NHLS, represented by and/or such persons or person
	duly authorised to be the Employer in writing.
1.1.1.26	The Pricing Strategy is a bill of quantities
1.2.1.2	The Employer's address for receipt of communications is: NHLS RESEPTION, BUILDING 23,
	GROUND FLOOR, CSIR PRETORIA CAMPUS, MEIRING NAUDE ROAD, BRUMMERIA, PRETORIA
	Proposal should be submitted to the following add : CALL FOR PROPOSAL TO - RENOVATIONS TO
	WITBANK LABORATORY IN MPUMALANGA.
2.4.1	"in the event of any ambiguity, conflict or discrepancy between the various contract documents, lists
2. <del>4</del> .1	and schedules, the order of precedence (from highest to lowest) shall be as follows:
	• The form of offer and acceptance
	Contract forms
	The contract data
	General conditions of contract (GCC 2015)
	• Scope of Work
	SANS 1200 Standardised Specifications
	• Site Information
	Construction drawings
	Bill of quantities
	The returnable schedules
3.1.3	The Contractor shall obtain the specific approval of the Employer before executing any of his functions
	or duties according to the following Clauses of the General Conditions of Contract: GCC 2015 3rd

# Edition 1. Clause 5.8.1 Non-working times 2. Clause 5.11.1 Suspension of the Works 3. Clause 5.12.1 Approval of any extension of time for completion 4. Clause 5.12.4 Acceleration of progress instead of extension of time 5. Clause 5.13.2 Reduction of a penalty for delay 6. Clause 6.3.2 The issuing of variation orders 7. Clause 6.8.4 The determination of additional or reduced cost arising from changes in the legislation 8. Clause 6.11 The agreeing of the adjustment of the sums for general items 9. Clause 10.1.5 The giving of a ruling on a Contractor's claim 4.3.3 "The Employer and the Contractor hereby agree, in terms of the provisions of section 37 (2) of the Occupational Health & Safety Act, 1993 (Act 85 of 1993, hereinafter referred to as 'the Act') that the following arrangements and procedures shall apply between them to ensure compliance by the Contractor with the provisions of the Act, namely: a) The Contractor undertakes that the appropriate officials and employees of the Contractor will fully acquaint themselves with all relevant provisions of the Act and the Regulations promulgated in terms of the Act; b) The Contractor undertakes that all relevant duties, obligations and prohibitions imposed in terms of the Act and regulations will be fully complied with; c) The Contractor hereby accepts sole liability for such due compliance with the relevant duties, obligations and prohibitions imposed by the Act and Regulations, and expressly absolves the Employer from itself being obliged to comply with any of the aforesaid duties, obligations, and prohibitions; with the exception of such duties, obligations and prohibitions expressly assigned to the Employer in terms of the Act and its associated Regulations; d) The Contractor agrees that any duly authorised official of the Employer shall be entitled to take such steps as may be necessary to ensure that the Contractor has complied with his undertakings as set out more fully in paragraphs (a) and (b) above, which steps may include, but will not be limited to, the right to inspect any appropriate site or premises occupied by the Contractor, or to inspect any appropriate records or Safety Plans held by the Contractor; The Contractor shall be obliged to report forthwith to the Employer any investigation, e) complaint or criminal charge which may arise as a consequence of the provisions of the Act and regulations, pursuant to work performed in terms of this Contract, and shall, on written demand, provide full details in writing of such investigation, complaint or criminal charge; 5.3.1 Clause 5.3.1: Commencement of the Works

	The documenta	ation required befo	re commencem	ent with Works exe	ecution are:	
	a)	Health and Safe	ety Plan			
	b)	Initial programn	ne			
	c)	Security				
	d)	Insurance				
5.3.2	Clause 5.3.2: 7	Timeframe to deli	ver documenta	ition		
	The time to s		entation requir	ed before comme	encement with Works	execution is
5.4.4	him/her in con	nection with acces	ss to the Site.	The Contractor sha	temporary rights of war all also provide at his obses of the Works."	
5.8.1	Clause 5.8.1: I	Non-Working Tim	es			
	The non-working	ng days are Saturd	ays and Sunda	ys.		
	The special non-working days are:					
		•		de the year end bre December and en	eak. ding on 7 January (Prov	visional).
5.12.2.	Clause 5.12.2.: Some reasons for extension of time					
	Clause 5.12.2.2: Abnormal climatic conditions.					
	Regardless of the cause of any delay an extension of time will only be considered if it can be show that the activity delayed is on the critical path indicated on the Programme of Works (Clause 5.6.1).  No extension of time will be granted in respect of any delays attributed to normal climatic condition Normal climatic conditions shall be deemed to include normal rainfall and associated wet conditions are materials, strong winds and extremes of temperature. However, in the event that delays to critical activities exceed the number of working days listed below for each month, then abnormal climatic conditions shall be deemed to exist, and an extension of time shall be granted in accordance with the provisions of that clause.					
					onditions and ays to critical ormal climatic	
	The number of days quoted below shall be regarded as a fair estimate of the delays to be anticipat and allowed for under normal climatic conditions where inclement weather prevents or disrupts work the critical path.					•
	January	4 days	May	2 days	September	2 days
	February	4 days	June	2 days	October	2 days

	March	2 days	July	2 days	November	4 days
	April	2 days	August	2 days	December	4 days
	evidence, which	ch shall be submitt	ed timeously as	each day or half	ompanied by substantiat f-day delay is experience of time will be added to	ed. Should an
	climatic condit		er reason will be	entertained. Ra	ed, no extension of time ainfall of less than 2mm	
5.13.1	Clause 5.13.1	: Penalty for Dela	у			
		• .		• .	day based on the loss so atic termination will be e	
5.16.3	Clause 5.16.3	: Latent defect lia	bility			
	The latent defe	ect period is ten (10	0) years for civil e	engineering work	S.	
6.8.2	Clause 6.8.2:	Contract Price Ac	djustment			
	The Contract Price Adjustment <b>is not</b> applicable in this contract.					
6.8.3	Clause 6.8.3: Variation in Cost of Special Materials					
	Price adjustments for variations in the costs of special materials are not allowed					
6.10.1.5	Clause 6.10.1	.5: Interim Payme	nts - Materials	on Site		
	No percentage or will be paid.		erials on site but	not yet built into	the Permanent Works i	s allowed for,
6.10.4	Clause 6.10.4	: Delivery, dissati	sfaction with an	d payment of p	payment certificate	
	Add the follow	ring to clause 6.10.	4:			
	certificate unti	•	s complied with I	•	withhold the delivery of preport in terms of Claus	
8.6.1.1.2	Clause 8.6.1.	1.2: Insurance				
	The value of the	ne materials suppli	ed by the Employ	er to be include	d in the insurance sum is	s -Nil.
8.6.1.1.3	Clause 8.6.1.	1.3: Insurance				
	The amount to sum is Nil.	o cover professiona	l fees for repairin	g damage and l	oss to be included in the	insurance

8.6.1.3	Clause 8.6.1.3: Insurance
	The limit of indemnity for liability insurance is R5 million for any single claim – the number of claims to be unlimited during the construction.
9.2.1.3.8	The Contractor has furnished inaccurate information in the returnable documents completed at tender stage and forming part of the Contract.
9.2.1.3.9	An official or other role player committed any corrupt or fraudulent act during the procurement process or in the execution of the contract that benefited the Contractor.
10	Clause 10: Dispute Resolution
	"Dispute resolution shall initially be by means of ad-hoc adjudication as per Clause 10.5.2. Should adjudication not be successful, then the dispute shall be referred to Arbitration under the provisions of Clause 10.7.1."
10.4.1	The parties may at time agree to settle disputes with the help of an impartial third party
10.5.3	The number of Adjudication Board Members to be appointed is five (5).
11	Clause 12: Confidentiality
	The Contractor shall treat the details of the Works comprised in this Contract as private and confidential (save in so far as may be necessary for the purposes hereof) and shall not publish or disclose the same or any particulars thereof in any trade or technical paper elsewhere without prior written consent of the Engineer.
12	Clause 13: Amendments in writing
	No amendments of this Contract or of any provisions or terms hereof and no waiver or relaxation or suspension of any of the provisions or terms of this Contract shall be of any force or effect unless reduced to writing and signed by both the parties hereto.

# PART 2: DATA PROVIDED BY THE CONTRACTOR

The contractor is advised to read the *general conditions of contract for construction works, third edition, 2015* published by the South African institution of civil engineering, private bag x200, halfway house, 1685, in order to understand the implications of this data which is required to be completed. Copies of these conditions of contract may be obtained from www.saice.org.za.

Each item of data given below is cross-referenced to the clause in the Conditions of Contract to which it mainly applies.

Clause	Data
1.1.1.9	The name of the Contractor is:
1.2.1.2	The address of the Contractor is: Address (physical):
	Address (postal):
	Telephone:

# **PART C2: PRICING DATA**

C2.1 Pricing Instructions

# **C2.1 PRICING INSTRUCTIONS**

- 1. Measurement and payment clauses of the COLTO (1998)/SANS 1200 Standardised Specifications, as well as the Particular Specifications, shall be deemed to form part of and included in the pricing instructions.
- 2. The units of measurement described in the Bill of Quantities are metric units. Abbreviations used in the Bill of Quantities are as follows:

%	=	percent	m <sup>2</sup> .pass	=	square metre-pass
h	=	hour	m³	=	cubic metre
ha	=	hectare	m³.km	=	cubic metre-kilometre
kg	=	kilogram	MN	=	meganewton
kľ	=	kilolitre	MN.m	=	meganewton-metre
km	=	kilometre	MPa	=	megapascal
km-pass	=	kilometre-pass	No.	=	number
kPa	=	kilopascal	Prov sum	=	Provisional sum
kW	=	kilowatt	P C sum	=	Prime Cost sum
1	=	litre	sum	=	lump sum
m	=	metre	t	=	ton (1 000 kg)
mm	=	millimetre	W/day	=	Work day
m <sup>2</sup>	=	square metre	•		-

- 3. Unless otherwise stated, items are measured net in accordance with the drawings, and no allowance is made for waste.
- 4. The prices and rates to be inserted in the Bill of Quantities are to be the full inclusive prices for the work described under the items. Such prices and rates shall cover all costs and expenses that may be required in accordance with the provisions of the Scope of Work, and shall cover the cost of all general risks, liabilities, and obligations set forth or implied in the Contract Data, as well as overhead charges and profit. These prices shall be used as a basis for assessment of payment for additional work that may have to be carried out.
- 5. It will be assumed that prices included in the Bill of Quantities are based on Acts, Ordinances, Regulations, By-laws, International Standards and National Standards that were published 28 days before the closing date for tenders. (Refer to www.sabs.co.za or www.iso.org for information on standards).
- 6. Where the Scope of Work requires detailed drawings and designs or other information to be provided, all costs associated therewith are deemed to have been provided for and included in the unit rates and sum amount tendered for such items.
- 7. An item against which no price is entered will be considered to be covered by the other price s or rates in the Bill of Quantities. A single lump sum will apply should a number of items be grouped together for pricing purposes.
- 8. The quantities set out in the Bill of Quantities are approximate and do not necessarily represent the actual amount of work to be done. The quantities of work accepted and certified for payment will be used for determining payments due and not the quantities given in the Bills of Quantities.
- 9. Reasonable compensation will be received where no pay item appears in respect of work required in the Bills of Quantities in terms of the Contract and which is not covered in any other pay item.

- 10. The short descriptions of the items of payment given in the Bill of Quantities are only for the purposes of identifying the items. More details regarding the extent of the work entailed under each item appear in the Scope of Work.
- 11. The Bill of Quantities has been drawn up in accordance with the latest issue of the COLTO (1998)/SABS1200 Standardised Specifications. Descriptions in the Bill of Quantities are abbreviated and must be read in conjunction with the measurement and payment clauses of the applicable specifications.

#### SCHEDULE OF QUANTITIES PREAMBLE TO THE SCHEDULE OF QUANTITIES AND RATES

- The standard commercial terms and conditions, special terms and conditions, and specifications (including the project specification.
- The proposer is at liberty to insert a rate of his own choosing for each item in the schedule, and any
  item against which no quantity (where applicable) or rate is entered will be considered to be covered
  by other items in the schedule.
- The quantities and rates inserted in the schedule are to be inclusive prices to the employer for the
  work described under the several items. Such prices shall cover all costs and expenses that may be
  required in and for the works and shall cover the cost of all general risks, liabilities, and obligations
  set forth or implied in the documents on which the tender is based.
- All rates and amounts shall be net, exclusive of value-added tax (vat) and shall be carried to the summary page in their net form. Vat will then be calculated on the total of the nett amounts.
- All quantities and rates as set forth and inserted in the schedule and extended to the totals for each
  portion of the schedule shall be considered as being totally inclusive for the whole of the works as
  stipulated or as can reasonably be inferred from these documents.
- All product guarantees are deemed to be included in the rates, and installation and application rates will consist of all necessary inspections and approvals to maintain guarantees.
- "Complete" as it is used in the schedule means the complete system or unit as specified in the particular documents. Each item in the schedule that is priced shall be filled in black ink.
- All quantities shall be considered as final and sufficient for the work described. The proposer shall satisfy himself as to the sufficiency of quantities but may not change quantities. Quantities shall be re-measured, and payment shall be made according to the adjusted total only.

# 1 PART C3: TERMS OF REFERENCE / SPECIFICATION

# FORM OF QUOTATION SUPPLIER NAME:

RFQ NO: 0019165

DESCRIPTION: RENOVATIONS TO WITBANK LABORATORY IN MPUMALANGA.

# RFQ SCOPE OF WORK

No	Description	Unit	Quantity	Rates	Cost excl vat
	Reception/ Capturing area:				
1	Remove existing benches, cupboards, notice boards and make good		Item		
2	Break opening to double brick wall, plaster reveals and rhinolite to smooth finish, $1000^{mm}$ x $1000^{mm}$ between reception and Microbiology		Item		
3	Supply and fit 15 <sup>mm</sup> x 400 <sup>mm</sup> wide, counter top shall be off approved Phenolic Resin. Top shall be impervious core that is chemical and heat resistant similar to Fundermax tops to new opening	m	1		
4	Supply and fit aluminium frame with 6 <sup>mm</sup> safety laminated glass sliding window with locking mechanism, 1000 <sup>mm</sup> x 1000 <sup>mm</sup> , between Reception and Microbiology	No	1		
5	Supply and install 30 <sup>mm</sup> x 30 <sup>mm</sup> steel square tubing frame, 800 <sup>mm</sup> wide and 885 <sup>mm</sup> high, on adjustable inserts, must be powder coated as per specification	m	10		
6	Supply and fit 15 <sup>mm</sup> x 900 <sup>mm</sup> wide, top shall be off approved Phenolic Resin. Top shall be impervious core that is chemical and heat resistant fixed to steel frames, height 900 <sup>mm</sup> high like Fundermax tops	m	10		
7	Supply and install 30 <sup>mm</sup> x 30 <sup>mm</sup> steel square tubing frame, 600 <sup>mm</sup> wide and 750 <sup>mm</sup> high, on adjustable inserts, must be powder coated as per specification	m	15		
8	Supply and fit 15 <sup>mm</sup> x 700 <sup>mm</sup> wide, top shall be off approved Phenolic Resin. Top shall be impervious core that is chemical and heat resistant fixed to steel frames, height 765 <sup>mm</sup> high similar to Fundermax tops	m	15		
9	Supply and fit "Cabstrut Jupiter", steel, 2 Compartment type, allow for bends and end caps, power skirting from wire ways for power and data reticulation and will be able to accommodate future expansion	m	19		
10	Supply and install power skirting plug points wired from distribution board including 25-amp circuit breakers	No	18		
11	Supply and fit porcelain hand wash basin on pedestal with hospital elbow taps, connect to hot and cold supply and drainage, fit shut off valves to each water outlet, fit 600 <sup>mm</sup> x 200 <sup>mm</sup> wall tile above basin	No	1		
12	Supply and fit steel powder coated wall cupboards with doors, 750 <sup>mm</sup> high x 900 <sup>mm</sup> wide x 330 <sup>mm</sup> deep with shelve as per specification	No	4		
13	Supply and deliver steel powder coated under bench cupboards 700 <sup>mm</sup> high x 900 <sup>mm</sup> with 2 lockable drawers on top and doors and shelve at bottom on lockable castor wheels as per specification	No	4		
14	Supply and fit solid aluminium partition 1200mm high at reception	m	5		
15	Supply and fit aluminium frame with 6 <sup>mm</sup> safety laminated glass above aluminium partition up to ceiling height 2600 <sup>mm</sup>	m	5		
16	Create opening to new aluminium partition 1000 <sup>mm</sup> x 400 <sup>mm</sup> high at Reception to pass through specimens		Item		

17	Supply and fit 15 <sup>mm</sup> x 400 <sup>mm</sup> wide, counter top shall be off	m	1		
	approved Phenolic Resin. Top shall be impervious core that is				
	chemical and heat resistant similar to Fundermax tops to new				
10	opening	3.7			
18	Supply and fit aluminium frame with 6 <sup>mm</sup> safety laminated glass	No	1		
	door, fit industrial door handle with separate lockset, supply and fit				
	4 heavy duty hinges to door, bottom half of door must be solid				
19	aluminium and top half must be clear/ frosted glass  Supply and fit solid aluminium partition 1200mm high between	m	6		_
19	Capturing and Chemistry	m	O		
20	Supply and fit aluminium frame with 6 <sup>mm</sup> safety laminated glass	m	6		
20	above aluminium partition up to ceiling height 2600 <sup>mm</sup>	111	0		
21	Create opening to new aluminium partition 1000 <sup>mm</sup> x 400 <sup>mm</sup> high		Item		
21	between Capturing and Chemistry to pass through specimens		Item		
22	Supply and fit 15 <sup>mm</sup> x 400 <sup>mm</sup> wide, counter top shall be off	m	1		
	approved Phenolic Resin. Top shall be impervious core that is		_		
	chemical and heat resistant similar to Fundermax tops to new				
	opening				
23	Supply and fit aluminium frame with 6 <sup>mm</sup> safety laminated glass	No	1		
	door, fit industrial door handle with separate lockset, supply and fit				
	4 heavy duty hinges to door, bottom half of door must be solid				
	aluminium and top half must be clear/ frosted glass				
24	Supply and fit pigeonholes, each hole to accommodate A4 paper,	No	30		
	300 <sup>mm</sup> x 220 <sup>mm</sup> x 50 <sup>mm</sup> high, 3 sets off ten				
	Homotology/Chamistree				
	Haematology/ Chemistry:				
1	Remove existing benches, cupboards and make good		Item		
•	remo . o chisting concines, supposition and make good		10111		
2	Supply and install 30 <sup>mm</sup> x 30 <sup>mm</sup> steel square tubing frame, 800 <sup>mm</sup>	m	21		
	wide and 885 <sup>mm</sup> high, on adjustable inserts, must be powder coated				
	as per specification				
3	Supply and fit 15 <sup>mm</sup> x 900 <sup>mm</sup> wide, top shall be off approved	m	21		
5	Phenolic Resin. Top shall be impervious core that is chemical and	111	<i>2</i> 1		
	heat resistant fixed to steel frames, height 900 <sup>mm</sup> high similar to				
	Fundermax tops				
4	Supply and install 30 <sup>mm</sup> x 30 <sup>mm</sup> steel square tubing frame, 1100 <sup>mm</sup>	No	2		
	wide and 885 <sup>mm</sup> high x 2300 <sup>mm</sup> long on adjustable inserts, must be				
	powder coated as per specification for island bench				
5	Supply and fit 15 <sup>mm</sup> x 1200 <sup>mm</sup> wide x 900 high x 2300 <sup>mm</sup> long, top	No	2		
,	shall be off approved Phenolic Resin. Top shall be impervious core	140	۷		
	that is chemical and heat resistant fixed to steel frames, height				
	900 <sup>mm</sup> high similar to Fundermax tops				
6	Supply and fit Black staining integral sink, 560mm x 360mm x	No	1		
-	230mm deep with waste grate and Polypropylene bottle trap,		-		
	connect to cold water supply and drainage, fit shut off valve to				
	water outlet				
7	Supply and fit movable swan neck serrated nozzle tap to sink,	No	1		
	connect to cold water supply	<u> </u>			
8	Supply and fit porcelain hand wash basin on pedestal with hospital	No	1		
	elbow taps, connect to hot and cold supply and drainage, fit shut off				
	valves to each water outlet, fit 600mm x 200mm wall tile above basin				
9	Supply and fit steel powder coated wall cupboards with doors,	No	6		
	750 <sup>mm</sup> high x 900 <sup>mm</sup> wide x 330 <sup>mm</sup> deep with shelve as per				
	specification				
10		.,			
10	Supply and deliver steel powder coated under bench cupboards	No	8		
	840 <sup>mm</sup> high x 900 <sup>mm</sup> with 2 lockable drawers on top and doors and				
	shelve at bottom on lockable castor wheels as per specification				
11	Supply and fit "Cabatant Junitar" at al. 2 Commontment toma -11	- m	20		
11	Supply and fit "Cabstrut Jupiter", steel, 2 Compartment type, allow for bends and end caps, power skirting from wire ways for power	m	28		
	and data reticulation and will be able to accommodate future				
	expansion				
12	Supply and install power skirting plug points wired from	No	21		
12	distribution board including 25 amp circuit breakers	140	<i>2</i> 1		
				ı	
13		No	1		
13	Supply and fit 3 pin 32 amp IP44 male and female socket wired from distribution board with 4mm wire 3 core and 30 amp circuit	No	1		

	breaker			
	Micro:			
1	Remove existing benches, cupboards and make good		Item	
2	Supply and install 30 <sup>mm</sup> x 30 <sup>mm</sup> steel square tubing frame, 800 <sup>mm</sup>	m	18	
-	wide and 885 <sup>mm</sup> high, on adjustable inserts, must be powder coated	111	10	
	as per specification		10	
3	Supply and fit 15 <sup>mm</sup> x 900 <sup>mm</sup> wide, top shall be off approved Phenolic Resin. Top shall be impervious core that is chemical and	m	18	
	heat resistant fixed to steel frames, height 900 <sup>mm</sup> high similar to			
	Fundermax tops			
4	Supply and install 30 <sup>mm</sup> x 30 <sup>mm</sup> steel square tubing frame, 1100 <sup>mm</sup>	No	1	
	wide and 885 <sup>mm</sup> high x 2300 <sup>mm</sup> long on adjustable inserts, must be powder coated as per specification for island bench			
5	Supply and fit 15 <sup>mm</sup> x 1200 <sup>mm</sup> wide x 900 high x 2300 <sup>mm</sup> long, top	No	1	
	shall be off approved Phenolic Resin. Top shall be impervious core			
	that is chemical and heat resistant fixed to steel frames, height			
6	900 <sup>mm</sup> high similar to Fundermax tops Supply and fit Black staining integral sink, 560mm x 360mm x	No	1	
J	230mm deep with waste grate and Polypropylene bottle trap,	110	1	
	connect to cold water supply and drainage, fit shut off valve to			
	water outlet	3.7		
7	Supply and fit movable swan neck serrated nozzle tap to sink, connect to cold water supply	No	1	
8	Supply and fit porcelain hand wash basin on pedestal with hospital	No	1	
	elbow taps, connect to hot and cold supply and drainage, fit shut off			
	valves to each water outlet, fit 600 <sup>mm</sup> x 200 <sup>mm</sup> wall tile above basin			
9	Supply and fit steel powder coated wall cupboards with doors, 750 <sup>mm</sup> high x 900 <sup>mm</sup> wide x 330 <sup>mm</sup> deep with shelve as per	No	4	
	specification			
10	Supply and deliver steel powder coated under bench cupboards	No	6	
	840 <sup>mm</sup> high x 900 <sup>mm</sup> with 2 lockable drawers on top and doors and			
11	shelve at bottom on lockable castor wheels as per specification  Supply and fit "Cabstrut Jupiter", steel, 2 Compartment type, allow		22	
11	for bends and end caps, power skirting from wire ways for power	m	22	
	and data reticulation and will be able to accommodate future			
	expansion			
12	Supply and install power skirting plug points wired from distribution board including 25 amp circuit breakers	No	17	
13	Remove existing door and door frame, break opening bigger to	No	1	
	accommodate a door and half plaster reveals and rhinolite to			
1.4	smooth finish	N.T.		
14	Supply and fit aluminium frame with 6 <sup>mm</sup> safety laminated glass door and half, fit industrial door handles with separate lockset,	No	1	
	supply and fit 4 heavy duty hinges to each door, bottom half of door			
	must be solid aluminium and top half must be clear/ frosted glass			
	TD Lab.			
	TB Lab:			
1	Remove existing benches, cupboards and make good		Item	
2	Cymply and install 20mm v 20mm -tl ( 1' C 000mm		1.4	
2	Supply and install 30 <sup>mm</sup> x 30 <sup>mm</sup> steel square tubing frame, 800 <sup>mm</sup> wide and 885 <sup>mm</sup> high, on adjustable inserts, must be powder coated	m	14	
	as per specification			
3	Supply and fit 15 <sup>mm</sup> x 900 <sup>mm</sup> wide, top shall be off approved	m	14	
4	Supply and install 30 <sup>mm</sup> x 30 <sup>mm</sup> steel square tubing frame, 1100 <sup>mm</sup>	No	1	
	wide and 885 <sup>mm</sup> high x 2300 <sup>mm</sup> long on adjustable inserts, must be			
5	powder coated as per specification for island bench	NT_	1	
5		No	1	
	that is chemical and heat resistant fixed to steel frames, height			
	Supply and fit 15 <sup>mm</sup> x 900 <sup>mm</sup> wide, top shall be off approved Phenolic Resin. Top shall be impervious core that is chemical and heat resistant fixed to steel frames, height 900 <sup>mm</sup> high similar to Fundermax tops  Supply and install 30 <sup>mm</sup> x 30 <sup>mm</sup> steel square tubing frame, 1100 <sup>mm</sup> wide and 885 <sup>mm</sup> high x 2300 <sup>mm</sup> long on adjustable inserts, must be powder coated as per specification for island bench  Supply and fit 15 <sup>mm</sup> x 1200 <sup>mm</sup> wide x 900 high x 2300 <sup>mm</sup> long, top shall be off approved Phenolic Resin. Top shall be impervious core			

	900mm high similar to Fundermax tops				
6	Supply and fit Black staining integral sink, 560mm x 360mm x 230mm deep with waste grate and Polypropylene bottle trap, connect to cold water supply and drainage, fit shut off valve to water outlet	No	1		
7	Supply and fit movable swan neck serrated nozzle tap to sink, connect to cold water supply	No	1		
8	Supply and fit porcelain hand wash basin on pedestal with hospital elbow taps, connect to hot and cold supply and drainage, fit shut off valves to each water outlet, fit 600 <sup>mm</sup> x 200 <sup>mm</sup> wall tile above basin	m	1		
9	Supply and fit steel powder coated wall cupboards with doors, 750 <sup>mm</sup> high x 900 <sup>mm</sup> wide x 330 <sup>mm</sup> deep with shelve as per specification	No	3		
10	Supply and deliver steel powder coated under bench cupboards 840 <sup>mm</sup> high x 900 <sup>mm</sup> with 2 lockable drawers on top and doors and shelve at bottom on lockable castor wheels as per specification	No	6		
11	Supply and fit "Cabstrut Jupiter", steel, 2 Compartment type, allow for bends and end caps, power skirting from wire ways for power and data reticulation and will be able to accommodate future expansion	m	22		
12	Supply and install power skirting plug points wired from distribution board including 25 amp circuit breakers	No	18		
13	Remove existing door and door frame, break opening bigger to accommodate a door and half plaster reveals and rhinolite to smooth finish	No	1		
14	Supply and fit aluminium frame with 6 <sup>mm</sup> safety laminated glass door and half, fit industrial door handles with separate lockset, supply and fit 4 heavy duty hinges to each door, bottom half of door must be solid aluminium and top half must be clear/ frosted glass	No	1		
	Male and Female Toilets:				
1	Remove existing toilets, basins, and make good		Item		
2	Supply and fit new Porcelain handwash basins, allow for piping and waste to new position, re-connect to water and waste, supply new hot and cold elbow taps to basins, fit shut off valve to each outlet	No	2		
3	Build single brick wall to create new space for toilet in Ladies bathroom, 2100 high to match existing, plaster and rhinolite to smooth finish	m	3		
4	Supply and fit new steel door frame to new brick wall, plaster reveals, fit new wooden door to new door frame	No	2		
5	Supply and fit new Ceramic toilet including cistern, enamel coated wooden toilet seat, connect to existing water supply and drain, allow for additional piping to new toilet	No	3		
6	Supply and fit steel lockable toilet paper holder to accommodate 3 rolls at a time	No	3		
7	Supply and fit new vacant/engaged lockset to new doors	No	3		
8	Supply and fit new Porcelain Urinal against wall, connect to water and drainage with push button flush system	No	1		
			1	I	

1	Remove existing sink, cupboards, shelves and make good		Item	
2	Supply and fit 20 <sup>mm</sup> x 600 <sup>mm</sup> Rustenburg Granite top	m	4	
3	Supply and fit 750 <sup>mm</sup> wide wall cupboards including shelve, hinges and chrome door handles on 100 <sup>mm</sup> x 50 <sup>mm</sup> chrome legs, mahogany	No	2	
4	Supply and fit 900 <sup>mm</sup> wide floor standing cupboards including shelve, hinges and chrome door handles on 100 <sup>mm</sup> x 50 <sup>mm</sup> chrome legs, mahogany	No	3	
5	Supply and fit 450 <sup>mm</sup> wide floor standing cupboards with drawers, hinges and chrome door handles on 100 <sup>mm</sup> x 50 <sup>mm</sup> chrome legs, mahogany	No	1	
6	Supply and fit double bowl stainless steel sink to granite top, 1800 <sup>mm</sup> x 500 <sup>mm</sup> wide, supply and fit 600 <sup>mm</sup> x 200 <sup>mm</sup> wall tiles above sink	No	1	
7	Supply and fit Goose neck sink mixer tap, connect to hot and cold water supply, supply drainage for sink and connect	No	1	
8	Supply and fit microwave shelve, mahogany, 650 <sup>mm</sup> wide x 400 <sup>mm</sup> high x 400 <sup>mm</sup> deep	No	1	
9	Supply and fit 15 amp Crabtree double plug points wired from distribution board, allow for PVC trunking and wiring and circuit breakers	No	4	
10	Supply and fit new 7L Hydroboil, connect to water supply and drainage, all pipes to be chased into wall	No	1	
11	Supply and fit 30 amp isolator next to Hydroboil, wired from distribution board, including ducting, wiring and 25 amp single pole circuit breaker	No	1	
12	Supply and deliver 900 <sup>mm</sup> diameter Syona- round café table moist and abrasion and stain resistant	No	4	
13	Supply and deliver chair made of mild steel, ERW pipes, the backrest and seat are moulded from PP material	No	12	
	Lab Manager Office:			
1	Supply and fit Mahogany office desks (Desk Shell 1500 <sup>mm</sup> x 750 <sup>mm</sup> )	No	1	
2	Supply and fit Mahogany 90 Degree link 750 <sup>mm</sup> x 600 <sup>mm</sup>	No	1	
3	Supply and fit Mahogany lockable sliding door Credenza $1000^{\mathrm{mm}}\mathrm{x}$ 600 with shelve	No	1	
4	Supply and fit Mobile pedestal top draw locking with 4 drawers and pen/pencil tray	No	1	
5	Supply and deliver floor standing filing cabinet, with lockable glass doors, $1800^{mm} \times 900^{mm} \times 450^{mm}$ with 5 shelves	No	1	
	Supervisor Office:			
1	Supply and fit Mahogany office desks (Desk Shell 1500 <sup>mm</sup> x 750 <sup>mm</sup> )	No	1	
2	Supply and fit Mahogany 90 Degree link 750 <sup>mm</sup> x 600 <sup>mm</sup>	No	1	

3	Supply and fit Mahogany lockable sliding door Credenza 1000 <sup>mm</sup> x 600 with shelve	No	1	
4	Supply and fit Mobile pedestal top draw locking with 4 drawers and pen/pencil tray	No	1	
	Admin Officer:			
1	Supply and fit Mahogany office desks (Desk Shell 1500 <sup>mm</sup> x 750 <sup>mm</sup> )	No	1	
2	Supply and fit solid aluminium partition 1200 <sup>mm</sup> high at reception	m	4	
3	Supply and fit aluminium frame with 6 <sup>mm</sup> safety laminated glass above aluminium partition up to ceiling height 2600 <sup>mm</sup>	m	4	
4	Supply and fit aluminium frame with 6mm safety laminated glass door, fit industrial door handle with separate lockset, supply and fit 4 heavy duty hinges to door, bottom half of door must be solid aluminium and top half must be clear/ frosted glass	No	1	
	Store Room:			
1	Supply and fit Krost shelving powder coated against the wall, 915 <sup>mm</sup> wide x 2000 <sup>mm</sup> high x 305 <sup>mm</sup> deep, shelves must be 350 <sup>mm</sup> apart	No	10	
	General to complete lab:			
1	Supply and fit 6 aluminium coat hooks per set on aluminium rail	No	4	
2	Supply and fit 1200 <sup>mm</sup> x 1000 <sup>mm</sup> notice board with aluminium frame	No	2	
3	Supply and fit 1200 <sup>mm</sup> x 1000 <sup>mm</sup> white board with aluminium frame	No	2	
4	Supply and fit Oak lockers against wall, 350 <sup>mm</sup> x 350 <sup>mm</sup> x 350 <sup>mm</sup> deep each with lock and knob	No		
5	Remove existing vinyl sheeting and skirting, prepare floor to smooth finish using self-levelling screed, supply and install 2 <sup>mm</sup> Eclipse PUR or Classic Mystique PUR vinyl sheeting with welded joints, vinyl must go up the wall 120 <sup>mm</sup> high include cove fillet and capping as per specification, most of the work will have to be done after hours and weekends	m <sup>2</sup>	310	
6	Remove all loose and peeling paint from walls, where necessary rhinolite walls to smooth finish, Prepare and paint walls, 2 coats, Plascon Double Velvet, as per specification, note all notices and white boards, pictures, plug and switch covers ext. must be removed before painting commence and must be re-fitted after painting walls, most off the work will have to be done after hours and weekends	m <sup>2</sup>	745	
7	Remove all loose and peeling paint from ceiling, Prepare and paint ceiling 2 coats, Plascon Double Velvet, as per specification, most off the work will have to be done after hours and weekends	m <sup>2</sup>	300	
8	Prepare and paint door frames 2 coats Plascon Enamel as per specifications	No	16	
9	Remove existing light fittings, supply and fit 5ft LED light fittings with clip on cover including LED lamps	No	36	

10	Supply and install surface mounted distribution board 3 rows of 30 and 200 <sup>mm</sup> deep, from Switch Board Manufacturers with lockable doors, mild steel and power coated, including two earth bars and 6 neutral bars	No	1	
	100 amp 3 phase main switch 15KA, in distribution board in laboratory	No	1	
11	60 amp single phase earth leakages 5 KA	No	3	
12	25 amp single phase circuit breakers 5 KA, plug circuits	No	30	
13	15 amp single phase circuit breakers 5 KA, light circuits	No	6	
14	25 amp single phase circuit breakers 5 KA, air con circuits	No	15	
15	Lightning arrestors	No	3	
16	20 amp single phase circuit breakers 5 KA, geyser circuits	No	1	
17	All circuits must be marked on the cover plate and distribution board legend card		Item	
18	Remove toilet and basin next to Tea room, close off all pipes and fit shut off valves to create store room facility, Remove all wall tiles and rhinolite to smooth finish		Item	
19	Remove existing door and door frame including security gate, supply and fit new door frame, plaster and rhinolite to smooth finish for emergency exist facility	No	1	
20	Supply and fit new Chromadeck door including new hinges and emergency Push Bar handle for emergency exit	No	1	
21	Supply and fit 16 <sup>mm</sup> Oak lockers against wall, 350 <sup>mm</sup> x 350 <sup>mm</sup> x 350 <sup>mm</sup> deep each with lock and knob	No	30	
22	Remove existing windows, plaster reveals and rhinolite to smooth finish, supply and install Aluminium windows, with 2 top hung (opening outwards) on either side of the window with aluminium handles, measurements are indicative and must be re-measured before manufacturing (1500mm x 1640mm)	No	15	
23	Remove existing windows, plaster reveals and rhinolite to smooth finish, supply and install Aluminium windows, with 2 top hung ( opening outwards) on either side of the window with aluminium handles, measurements are indicative and must be re-measured before manufacturing ( 1200mm x 500mm)	No	18	
24	Remove existing windows, plaster reveals and rhinolite to smooth finish, supply and install Aluminium windows, with 2 top hung ( opening outwards) on either side of the window with aluminium handles, measurements are indicative and must be re-measured before manufacturing ( 1500mm x 900mm)	No	3	
25	Remove existing windows, plaster reveals and rhinolite to smooth finish, supply and install Aluminium windows, with 2 top hung ( opening outwards) on either side of the window with aluminium handles, measurements are indicative and must be re-measured before manufacturing ( $1000^{mm} \times 900^{mm}$ )	No	1	
26	Remove existing windows, plaster reveals and rhinolite to smooth finish, supply and install Aluminium windows, with 1 top hung ( opening outwards) on either side of the window with aluminium handles, measurements are indicative and must be re-measured before manufacturing ( $600^{mm}$ x $600^{mm}$ )	No	2	

finish, supply and install Aluminium windows, with 2 top bung ( opening outwards) on either side of the window with aluminium handles, neasurements are indicative and must be re-measured before manufacturing (1500°° x 1500°° x)  Remove existing windows, plaster reveals and rhinolite to smooth finish, supply and install Aluminium windows, with 2 top bung ( opening outwards) on either ado of the window with aluminium handles, neasurements are indicative and must be re-measured before manufacturing (900°° x 500°° x)  Supply and lit burglar proofing using 20°° square tubing 100°° apart vertical and 800°° apart horizontal, burglar proofing must be powder coared white and bolled with 10°° are bolts, measurements are indicative and must be re-measured before manufacturing ( 1500°° x 1640°° apart horizontal, burglar proofing must be powder coated white and bolted with 10°° are bolts, measurements are indicative and must be re-measured before manufacturing ( 1200°° x 500°° apart horizontal, burglar proofing must be powder coated white and bolted with 10°° are bolts, measurements are indicative and must be re-measured before manufacturing ( 1200°° x 500°° apart horizontal, burglar proofing must be powder coated white and bolted with 10°° rave bolts, measurements are indicative and must be re-measured before manufacturing ( 1300°° x 500°° apart horizontal, burglar proofing must be powder coated white and bolted with 10°° rave bolts, measurements are indicative and must be re-measured before manufacturing ( 1300°° x 500°° apart horizontal, burglar proofing must be powder coated white and bolted with 10°° rave bolts, measurements are indicative and must be re-measured before manufacturing ( 1300°° x 500°° apart horizontal, burglar proofing must be powder coated white and bolted with 10°° rave bolts, measurements are indicative and must be re-measured before manufacturing ( 1300°° x 500°° apart horizontal, burglar proofing must be powder coated white and bolted with 10°° rave bolts, measurements are indicative and must be re					
finish, supply and install Aliminium windows, with 2 top hung ( opening outwards) or either side of the window with aliminium handles, measurements are indicative and must be re-measured  before manufacturing ( 900 m s, 500 m square tobing 100 m apart vertical and 800 m apart horizontal, burglar proofing must be  powder coated white and botted with 10 m system bolts, measurements  are indicative and must be re-measured before manufacturing ( 1500 m x 1640 m)  Supply and fit burglar proofing using 20 m square tobing 100 m apart vertical and 800 m apart horizontal, burglar proofing must be  prowder coated white and botted with 10 m square tobing 100 m apart vertical and 800 m apart horizontal, burglar proofing must be  prowder coated white and botted with 10 m square tobing 100 m apart vertical and 800 m apart horizontal, burglar proofing must be  prowder coated white and botted with 10 m square tobing 100 m apart vertical and 800 m apart horizontal, burglar proofing must be  prowder coated white and botted with 10 m square tobing 100 m apart vertical and 800 m apart horizontal, burglar proofing must be  prowder coated white and botted with 10 m square tobing 100 m apart vertical and 800 m apart horizontal, burglar proofing must be  prowder coated white and botted with 10 m square tobing 100 m apart vertical and 800 m apart horizontal, burglar proofing must be  powder coated white and botted with 10 m square tobing 100 m apart vertical and 800 m apart horizontal, burglar proofing must be  powder coated white and botted with 10 m square tobing 100 m apart vertical and 800 m apart horizontal, burglar proofing must be  powder coated white and botted with 10 m square tobing 100 m apart vertical and 800 m apart horizontal, burglar proofing must be  powder coated white and botted with 10 m square tobing 100 m apart vertical and 800 m apart horizontal, burglar proofing must be  powder coated white and botted with 10 m square tobing 100 m apart vertical and 800 m apart horizontal, burglar proofing must be  powder coated	27	opening outwards) on either side of the window with aluminium handles, measurements are indicative and must be re-measured	No	4	
apart vertical and 800° apart horizontal, burglar proofing must be powder coated white and bolted with 10° apart working apart horizontal, burglar proofing must be powder coated white and bolted with 10° apart vertical and 800° apart horizontal, burglar proofing must be powder coated white and bolted with 10° apart vertical and 800° apart horizontal, burglar proofing must be powder coated white and bolted with 10° apart vertical and 800° apart horizontal, burglar proofing must be powder coated white and bolted with 10° apart vertical and 800° apart horizontal, burglar proofing must be powder coated white and bolted with 10° and bolted with 10° apart vertical and 800° apart horizontal, burglar proofing must be powder coated white and bolted with 10° apart vertical and 800° apart horizontal, burglar proofing must be powder coated white and bolted with 10° apart vertical and 800° apart horizontal, burglar proofing must be powder coated white and bolted with 10° apart vertical and 800° apart horizontal, burglar proofing must be powder coated white and bolted with 10° apart vertical and 800° apart horizontal, burglar proofing must be powder coated white and bolted with 10° apart vertical and 800° apart horizontal, burglar proofing must be powder coated white and bolted with 10° apart vertical and 800° apart horizontal, burglar proofing must be powder coated white and bolted with 10° apart vertical and 800° apart horizontal, burglar proofing must be powder coated white and bolted with 10° apart vertical and 800° apart horizontal, burglar proofing must be powder coated white and bolted with 10° apart vertical and 800° apart horizontal, burglar proofing must be powder coated white and bolted with 10° apart vertical and 800° apart horizontal, burglar proofing must be powder coated white and bolted with 10° apart vertical and 800° apart horizontal apart horizontal apart horizontal apart horizontal opart apart horizontal	28	finish, supply and install Aluminium windows, with 2 top hung ( opening outwards) on either side of the window with aluminium handles, measurements are indicative and must be re-measured	No	4	
apart vertical and 8000mm apart horizontal, burglar proofing must be powder coated white and bolted with 10mm raw bolts, measurements are indicative and must be re-measured before manufacturing ( 1200mm x 5000mm)  31 Supply and fit burglar proofing using 20mm square tubing 100mm apart vertical and 800mm apart horizontal, burglar proofing must be powder coated white and bolted with 10mm raw bolts, measurements are indicative and must be re-measured before manufacturing ( 1500mm x 900mm)  32 Supply and fit burglar proofing using 20mm square tubing 100mm apart vertical and 800mm apart horizontal, burglar proofing must be powder coated white and bolted with 10mm raw bolts, measurements are indicative and must be re-measured before manufacturing ( 1000mm x 9000mm)  33 Supply and fit burglar proofing using 20mm square tubing 100mm apart vertical and 800mm apart horizontal, burglar proofing must be powder coated white and bolted with 10mm raw bolts, measurements are indicative and must be re-measured before manufacturing ( 600mm x 600mm)  34 Supply and fit burglar proofing using 20mm square tubing 100mm apart vertical and 800mm apart horizontal, burglar proofing must be powder coated white and bolted with 10mm raw bolts, measurements are indicative and must be re-measured before manufacturing ( 1500mm x 1500mm)  35 Supply and fit burglar proofing using 20mm square tubing 100mm apart vertical and 800mm apart horizontal, burglar proofing must be powder coated white and bolted with 10mm raw bolts, measurements are indicative and must be re-measured before manufacturing ( 900mm x 500mm)  36 Supply and deliver Zelda High back chair- Full Syncro Mechanism No No No Supply and deliver Zelda High back chair- Full Syncro Mechanism No No No Supply and deliver Zelda High back chair- Full Syncro Mechanism No No No Supply and deliver Zelda High back chair- Full Syncro Mechanism No N	29	apart vertical and $800^{mm}$ apart horizontal, burglar proofing must be powder coated white and bolted with $10^{mm}$ raw bolts, measurements are indicative and must be re-measured before manufacturing (	No	15	
apart vertical and 800 mm apart horizontal, burglar proofing must be powder coated white and holted with 10 mm raw bolts, measurements are indicative and must be re-measured before manufacturing (  1500 mm x 900 mm)  32 Supply and fit burglar proofing using 20 mm square tubing 100 mm apart vertical and 800 mm apart horizontal, burglar proofing must be powder coated white and bolted with 10 mm raw bolts, measurements are indicative and must be re-measured before manufacturing (  1000 mm x 900 mm)  33 Supply and fit burglar proofing using 20 mm square tubing 100 mm apart vertical and 800 mm apart horizontal, burglar proofing must be powder coated white and bolted with 10 mm raw bolts, measurements are indicative and must be re-measured before manufacturing (  600 mm x 600 mm)  34 Supply and fit burglar proofing using 20 mm square tubing 100 mm apart vertical and 800 mm apart horizontal, burglar proofing must be powder coated white and holted with 10 mm raw bolts, measurements are indicative and must be re-measured before manufacturing (  1500 mm x 1500 mm)  35 Supply and fit burglar proofing using 20 mm square tubing 100 mm apart vertical and 800 mm apart horizontal, burglar proofing must be powder coated white and bolted with 10 mm raw bolts, measurements are indicative and must be re-measured before manufacturing (  900 mm x 500 mm)  36 Supply and deliver Zelda High back chair- Full Syncro Mechanism and supply and deliver Zelda High back chair- Full Syncro Mechanism and supply and deliver Zelda High back chair- Full Syncro Mechanism and supply and deliver Zelda High back chair- Full Syncro Mechanism and supply and deliver Zelda High back chair- Full Syncro Mechanism and supply and deliver Zelda High back chair- Full Syncro Mechanism and supply and deliver Zelda High back chair- Full Syncro Mechanism and supply and deliver Zelda High back chair- Full Syncro Mechanism and supply and deliver Zelda High back chair- Full Syncro Mechanism and supply and fit Syncm measurements are indicative and must be re-measured be	30	apart vertical and $800^{mm}$ apart horizontal, burglar proofing must be powder coated white and bolted with $10^{mm}$ raw bolts, measurements are indicative and must be re-measured before manufacturing (	No	18	
apart vertical and 800 <sup>mm</sup> apart horizontal, burglar proofing must be powder coated white and bolted with 10 <sup>mm</sup> raw bolts, measurements are indicative and must be re-measured before manufacturing ( 1000 <sup>mm</sup> x 900 <sup>mm</sup> )  33 Supply and fit burglar proofing using 20 <sup>mm</sup> square tubing 100 <sup>mm</sup> apart vertical and 800 <sup>mm</sup> apart horizontal, burglar proofing must be powder coated white and bolted with 10 <sup>mm</sup> raw bolts, measurements are indicative and must be re-measured before manufacturing ( 600 <sup>mm</sup> x 600 <sup>mm</sup> )  34 Supply and fit burglar proofing using 20 <sup>mm</sup> square tubing 100 <sup>mm</sup> apart vertical and 800 <sup>mm</sup> apart horizontal, burglar proofing must be powder coated white and bolted with 10 <sup>mm</sup> raw bolts, measurements are indicative and must be re-measured before manufacturing ( 1500 <sup>mm</sup> x 1500 <sup>mm</sup> )  35 Supply and fit burglar proofing using 20 <sup>mm</sup> square tubing 100 <sup>mm</sup> apart vertical and 800 <sup>mm</sup> apart horizontal, burglar proofing must be powder coated white and bolted with 10 <sup>mm</sup> raw bolts, measurements are indicative and must be re-measured before manufacturing ( 900 <sup>mm</sup> x 500 <sup>mm</sup> )  36 Supply and deliver Zelda High back chair- Full Syncro Mechanism —Nylon Base —Y600 Arms, Sitting height  37 Supply and deliver Zelda High back chair- Full Syncro Mechanism —Nylon Base —Standing Height  38 Remove existing blinds, supply and fit 50 <sup>mm</sup> PVC wood alike to windows including rails, 1500 <sup>mm</sup> x 1640 <sup>mm</sup> measurements are indicative and must be re-measured before manufacturing  90 Remove existing blinds, supply and fit 50 <sup>mm</sup> PVC wood alike to windows including rails, 1200 <sup>mm</sup> x 500 <sup>mm</sup> measurements are indicative and must be re-measured before manufacturing  40 Remove existing blinds, supply and fit 50 <sup>mm</sup> PVC wood alike to windows including rails, 1200 <sup>mm</sup> x 500 <sup>mm</sup> measurements are indicative and must be re-measured before manufacturing  40 Remove existing blinds, supply and fit 50 <sup>mm</sup> PVC wood alike to windows including rails, 1200 <sup>mm</sup> x 500 <sup>mm</sup> measurements are indicative and must be re-measured before manufacturing	31	apart vertical and 800 <sup>mm</sup> apart horizontal, burglar proofing must be powder coated white and bolted with 10 <sup>mm</sup> raw bolts, measurements are indicative and must be re-measured before manufacturing (	No	3	
apart vertical and 800mm apart horizontal, burglar proofing must be powder coated white and bolted with 10mm raw bolts, measurements are indicative and must be re-measured before manufacturing ( 600mm x 600mm)  34 Supply and fit burglar proofing using 20mm square tubing 100mm apart vertical and 800mm apart horizontal, burglar proofing must be powder coated white and bolted with 10mm raw bolts, measurements are indicative and must be re-measured before manufacturing ( 1500mm x 1500mm)  35 Supply and fit burglar proofing using 20mm square tubing 100mm apart vertical and 800mm apart horizontal, burglar proofing must be powder coated white and bolted with 10mm raw bolts, measurements are indicative and must be re-measured before manufacturing ( 900mm x 500mm)  36 Supply and deliver Zelda High back chair- Full Syncro Mechanism -Nylon Base -Y600 Arms, Sitting height  37 Supply and deliver Zelda High back chair- Full Syncro Mechanism -Nylon Base -Standing Height  38 Remove existing blinds, supply and fit 50mm PVC wood alike to windows including rails, 1500mm x 1640mm measurements are indicative and must be re-measured before manufacturing  39 Remove existing blinds, supply and fit 50mm PVC wood alike to windows including rails, 1200mm x 500mm measurements are indicative and must be re-measured before manufacturing  40 Remove existing blinds, supply and fit 50mm PVC wood alike to windows including rails, 1200mm x 500mm measurements are indicative and must be re-measured before manufacturing	32	apart vertical and $800^{mm}$ apart horizontal, burglar proofing must be powder coated white and bolted with $10^{mm}$ raw bolts, measurements are indicative and must be re-measured before manufacturing (	No	1	
apart vertical and 800mm apart horizontal, burglar proofing must be powder coated white and bolted with 10mm raw bolts, measurements are indicative and must be re-measured before manufacturing ( 1500mm x 1500mm x 1500mm)  Supply and fit burglar proofing using 20mm square tubing 100mm apart vertical and 800mm apart horizontal, burglar proofing must be powder coated white and bolted with 10mm raw bolts, measurements are indicative and must be re-measured before manufacturing ( 900mm x 500mm)  Supply and deliver Zelda High back chair- Full Syncro Mechanism —Nylon Base —Y600 Arms, Sitting height  Supply and deliver Zelda High back chair- Full Syncro Mechanism —Nylon Base —Standing Height  Remove existing blinds, supply and fit 50mm PVC wood alike to windows including rails, 1500mm x 1640mm measurements are indicative and must be re-measured before manufacturing  Remove existing blinds, supply and fit 50mm PVC wood alike to windows including rails, 1200mm x 500mm measurements are indicative and must be re-measured before manufacturing  Remove existing blinds, supply and fit 50mm PVC wood alike to windows including rails, 1200mm x 500mm measurements are indicative and must be re-measured before manufacturing  Remove existing blinds, supply and fit 50mm PVC wood alike to windows including rails, 150mm x 500mm measurements are indicative and must be re-measured before manufacturing  Remove existing blinds, supply and fit 50mm PVC wood alike to No  Remove existing blinds, supply and fit 50mm PVC wood alike to No  Remove existing blinds, supply and fit 50mm PVC wood alike to No  Remove existing blinds, supply and fit 50mm PVC wood alike to No  Remove existing blinds, supply and fit 50mm PVC wood alike to No  Remove existing blinds, supply and fit 50mm PVC wood alike to No	33	apart vertical and 800 <sup>mm</sup> apart horizontal, burglar proofing must be powder coated white and bolted with 10 <sup>mm</sup> raw bolts, measurements are indicative and must be re-measured before manufacturing (	No	2	
apart vertical and 800 <sup>mm</sup> apart horizontal, burglar proofing must be powder coated white and bolted with 10 <sup>mm</sup> raw bolts, measurements are indicative and must be re-measured before manufacturing ( 900 <sup>mm</sup> x 500 <sup>mm</sup> )  36 Supply and deliver Zelda High back chair- Full Syncro Mechanism —Nylon Base —Y600 Arms, Sitting height  37 Supply and deliver Zelda High back chair- Full Syncro Mechanism —Nylon Base — Standing Height  38 Remove existing blinds, supply and fit 50 <sup>mm</sup> PVC wood alike to windows including rails, 1500 <sup>mm</sup> x 1640 <sup>mm</sup> measurements are indicative and must be re-measured before manufacturing  39 Remove existing blinds, supply and fit 50 <sup>mm</sup> PVC wood alike to windows including rails, 1200 <sup>mm</sup> x 500 <sup>mm</sup> measurements are indicative and must be re-measured before manufacturing  40 Remove existing blinds, supply and fit 50 <sup>mm</sup> PVC wood alike to No  3 Remove existing blinds, supply and fit 50 <sup>mm</sup> PVC wood alike to	34	apart vertical and $800^{mm}$ apart horizontal, burglar proofing must be powder coated white and bolted with $10^{mm}$ raw bolts, measurements are indicative and must be re-measured before manufacturing (	No	4	
-Nylon Base -Y600 Arms, Sitting height  37 Supply and deliver Zelda High back chair- Full Syncro Mechanism -Nylon Base - Standing Height  38 Remove existing blinds, supply and fit 50 <sup>mm</sup> PVC wood alike to windows including rails, 1500 <sup>mm</sup> x 1640 <sup>mm</sup> measurements are indicative and must be re-measured before manufacturing  39 Remove existing blinds, supply and fit 50 <sup>mm</sup> PVC wood alike to windows including rails, 1200 <sup>mm</sup> x 500 <sup>mm</sup> measurements are indicative and must be re-measured before manufacturing  40 Remove existing blinds, supply and fit 50 <sup>mm</sup> PVC wood alike to No  3 Remove existing blinds, supply and fit 50 <sup>mm</sup> PVC wood alike to No  3 Remove existing blinds, supply and fit 50 <sup>mm</sup> PVC wood alike to No  3 Remove existing blinds, supply and fit 50 <sup>mm</sup> PVC wood alike to No  3 Remove existing blinds, supply and fit 50 <sup>mm</sup> PVC wood alike to No  3 Remove existing blinds, supply and fit 50 <sup>mm</sup> PVC wood alike to No  3 Remove existing blinds, supply and fit 50 <sup>mm</sup> PVC wood alike to No  3 Remove existing blinds, supply and fit 50 <sup>mm</sup> PVC wood alike to No  3 Remove existing blinds, supply and fit 50 <sup>mm</sup> PVC wood alike to No  3 Remove existing blinds, supply and fit 50 <sup>mm</sup> PVC wood alike to No  3 Remove existing blinds, supply and fit 50 <sup>mm</sup> PVC wood alike to No	35	apart vertical and $800^{mm}$ apart horizontal, burglar proofing must be powder coated white and bolted with $10^{mm}$ raw bolts, measurements are indicative and must be re-measured before manufacturing (	No	4	
-Nylon Base - Standing Height  38 Remove existing blinds, supply and fit 50 <sup>mm</sup> PVC wood alike to windows including rails, 1500 <sup>mm</sup> x 1640 <sup>mm</sup> measurements are indicative and must be re-measured before manufacturing  39 Remove existing blinds, supply and fit 50 <sup>mm</sup> PVC wood alike to windows including rails, 1200 <sup>mm</sup> x 500 <sup>mm</sup> measurements are indicative and must be re-measured before manufacturing  40 Remove existing blinds, supply and fit 50 <sup>mm</sup> PVC wood alike to No 3	36	–Nylon Base –Y600 Arms, Sitting height		_	
windows including rails, 1500 <sup>mm</sup> x 1640 <sup>mm</sup> measurements are indicative and must be re-measured before manufacturing  39 Remove existing blinds, supply and fit 50 <sup>mm</sup> PVC wood alike to windows including rails, 1200 <sup>mm</sup> x 500 <sup>mm</sup> measurements are indicative and must be re-measured before manufacturing  40 Remove existing blinds, supply and fit 50 <sup>mm</sup> PVC wood alike to No 3	37	-Nylon Base - Standing Height			
Remove existing blinds, supply and fit 50 <sup>mm</sup> PVC wood alike to windows including rails, 1200 <sup>mm</sup> x 500 <sup>mm</sup> measurements are indicative and must be re-measured before manufacturing  40 Remove existing blinds, supply and fit 50 <sup>mm</sup> PVC wood alike to No 3	38	windows including rails, 1500 <sup>mm</sup> x 1640 <sup>mm</sup> measurements are	No	15	
40 Remove existing blinds, supply and fit 50 <sup>mm</sup> PVC wood alike to windows including rails, 1500 <sup>mm</sup> x 900 <sup>mm</sup> measurements are	39	Remove existing blinds, supply and fit 50mm PVC wood alike to windows including rails, 1200mm x 500mm measurements are indicative and must be re-measured before manufacturing			
	40	Remove existing blinds, supply and fit 50 <sup>mm</sup> PVC wood alike to windows including rails, 1500 <sup>mm</sup> x 900 <sup>mm</sup> measurements are	No	3	

	indicative and must be re-measured before manufacturing			
41	Remove existing blinds, supply and fit 50 <sup>mm</sup> PVC wood alike to windows including rails, 1000 <sup>mm</sup> x 900 <sup>mm</sup> measurements are indicative and must be re-measured before manufacturing	No	1	
42	Remove existing blinds, supply and fit 50 <sup>mm</sup> PVC wood alike to windows including rails, 600 <sup>mm</sup> x 600 <sup>mm</sup> measurements are indicative and must be re-measured before manufacturing	No	2	
43	Remove existing blinds, supply and fit 50 <sup>mm</sup> PVC wood alike to windows including rails, 1500 <sup>mm</sup> x 1500 <sup>mm</sup> measurements are indicative and must be re-measured before manufacturing	No	4	
44	Remove existing blinds, supply and fit 50 <sup>mm</sup> PVC wood alike to windows including rails, 900 <sup>mm</sup> x 500 <sup>mm</sup> measurements are indicative and must be re-measured before manufacturing	No	4	
45	Remove exiting door, break opening bigger to accommodate 1200 <sup>mm</sup> wide door, plaster reveals and rhinolite to smooth finish, supply and fit aluminium frame with 6 <sup>mm</sup> safety laminated glass door, fit industrial door handle with separate lockset, supply and fit 4 heavy duty hinges to door, bottom half of door must be solid aluminium and top half must be clear/ frosted glass, door must be 1100 <sup>mm</sup> wide	No	1	
46	Remove exiting doors, supply and fit aluminium frame with 6 <sup>mm</sup> safety laminated glass door, fit industrial door handle with separate lockset, supply and fit 4 heavy duty hinges to door, bottom half of door must be solid aluminium and top half must be clear/frosted glass	No	14	
	Plumbing certificate on completion for complete lab		Item	
	Electrical certificate COC on completion for complete lab		Item,	
	Remove all rubble from site		Item	
	Allow the amount of R 50 000-00 (Fifty Thousand Rand) for contingency to be used at the discretion of the Principal Agent and deducted in whole or in part if not required			R50,000.00
	TOTAL			
	PLUS 15% VAT			
	GRAND TOTAL			
	Estimated time to complete work above			

# NOTE:

"Provide details and registration confirmation with CIDB in terms of the CIDB Act 38 of 2000.

Provide proof of grading level 2 GB or Higher

# Technical mandatory documents which should be included on submission

no	Certificate and or license	comply	Do not comply
1	Air conditioners trade test certificate (where air conditioners included)	N/A	
2	Electrical Wire man's license		
3	Specify air conditioner brand	N/A	
4	Plumbing Trade test certificate		
5	Provide copy of CV and Certificate of experienced project manager to manage the project		

# **Important Note:**

- Always read specification in conjunction with Bill of Quantities and Plan (if plan is applicable and supplied).
- All Quantities measured are indicative and will be re-measured on completion.
- Specific products to be used, to be confirmed in Bill of Quantities.
- All materials and products to be used, to be ISO 9001 accredited.
- Due to the nature of our labs (operation 24 hours) the contractor will be expected to work after hours and over the weekend.
- Variation orders can only be approved in writing (via the email) by the NHLS Project Manager
- No additional or extra work done will be paid for unless the project manager has issued a variation order.
- NHLS Project Manager will conduct all inspections.
- The contractor should be required to move the equipment (furniture, benches, etc.) and put them back requested.
- Only material installed will be paid and not for any wastage (no material on site will be paid).
- NHLS delegates can also and contact the client or visit the work done as referred on the completion certificate.
- Contractor will be requested to **provide comprehensive safety file**; work will be only allowed to commence after the file has been formally approve by NHLS.
- A contractor is expected to sign a 37(2) Agreement (Form FMI 0008) before commencing with the project.
- No progress payment will be made less than R200,000.00.

# **References:**

- NHLS delegates can also and contact the client or visit the work done as referred on the reference or completion certificate
- All the contractors will be requested to provides NHLS with the following signed of stamped references or completion certificates of similar work done on company or departments letter head, not more than five years (5) old as per the table below

If QUOTE	REQUIRED REFERENCE OR COMPLETION	CONTRACT VALUE OF
VALUE	CERTIFICATES	PROJECT PREVIOUSLY
		DONE
	One(1) copy of contactable reference or completion certificate, on	
R0-	client's letterhead, with contact details, valid e-mail address, office	
R50,000.00	telephone, cell phone and business address	N/A
	Two(2) copies of contactable reference or completion certificate, , on	
R50,000.00 -	client's letterhead, with contact details, valid e-mail address, office	
R100.000.00	telephone, cell phone and business address	N/A
R100,000.00	Three(3) copies of contactable reference or completion certificate, ,	
-	on client's letterhead, with contact details, valid e-mail address,	At least 1x R100,000.00 and
R200.000.00	office telephone, cell phone and business address	above
	Three(3) copies of contactable reference or completion certificate, ,	At least 3x R200,000.00 and

#### GUARANTEE, MAINTENANCE, PENALTY AND RETENTION PERIOD

The Guarantee and Maintenance period shall be for 12 months commencing on the date of Practical completion and acceptance of the Installation. During the Guarantee period the Contractor shall repair all defects in the Installation which may arise as a result of inferior quality materials or faulty workmanship. 5% retention of the contract price will be held back for a period of 3 months after date of Practical completion and acceptance of the installation

The fact that the Installation will be used and occupied by the Employer during the guarantee period shall in no way exempt the Contractor from his responsibility under this clause

Should a non-urgent fault occur during the guarantee period the Contractor will be advised and he shall repair the fault in good time

Should a fault occur during the guarantee period, that is in the opinion of the Project Manager of an urgent nature, then the Contractor will be advised and shall proceed immediately to rectify the fault

Should a fault occur during the guarantee period, that is in the opinion of the Project Manager of an urgent nature, and the Contractor is not available, the Employer shall reserve the right to obtain the services of any available Contractor to repair the fault. The cost of such repair work shall be borne by the Contractor in accordance with the escalated rates. In such a case the faulty equipment shall be kept for scrutiny by the Contractor. If this occurs during the retention period and retention money is still due to the Contractor, such claim from the Alternative Contractor, will be deducted from the Retention fund

Should the frequency and breakdown/s, in the opinion of the Project Manager, become so regular as to constitute and unacceptable state of affairs or should the installation or portions thereof prove to be unacceptable, the Contractor shall upon receipt of a written instruction from the Project Manager, replace portions/components or even the entire installation if need be, at his own cost as prescribed by the Project Manager

Where the practical completion is not reached by the date stated in the Tender/RFQ document or by the revised date granted by the Project Manager, the Contractor shall be liable to a Penalty determent by the Project Manager, which is in this instance .1% (point 1 percent) of the Tender/RFQ Total value, Per Day

#### **PRELIMINARIES**

Tenderer's attention is drawn to the fact that the Hospital and Laboratory will be fully operational during the building process. The work will have to be carried out in phases and at times that must be liaised and agreed to with the Business Manager and Hospital Management. This might result in certain work being carried out at certain times only, even after hours of weekends. Also note that sensitive electronic equipment are in use and no work that cause a vibration can be carried out when these equipment are in operation. Operating theaters in the vicinity of the building work will also be in use during the building program and the Contractor must liaise closely with the Hospital Management and obtain their written consent and permission, before removing and/or servicing equipment/structures, that might interfere with the running of the theaters or any other service/s. The use of certain lifts for moving of material will also have to be agreed to with the Hospital Management. The tenderer must allow for this in his prices since no additional claim will be entertained in this regard

#### TENDERS SHOULD BE BASED ON THE FOLLOWING SPECIFICATIONS

#### SITE APPLICATION

#### Repair to cracks

Repairs to cracks 0.2mm to 2mm

Rake out with a scraped blade.

Remove dust and debris.

Fill with pure acrylic, paintable, flexible crack filler.

#### Cracks over 2mm

Open out with a carborundum disk into a V shape minimum 3<sup>mm</sup> wide.

Remove dust and debris.

Wet the crack and fill with damp 1:4 cement/sand mortar properly compacted into the cracks.

#### **Repairs to Mortar Joints**

Scrape out unsound mortar

Point solidly with 1:3 cement/sand mortar properly compacted into the joints

#### **Repairs to Painted Wall Surface Coating**

Remove loose paint with a sharp paint a scraper or hand-held pneumatic engraving tools fitted with flat chisel heads Feather edges of tightly bonded paint with a rough to medium grit paper

Built up paint covering flush with general surface area

#### **Preparation - Generally**

Materials used in preparation to be types recommended by their manufacturers and the coating manufacturer for the situation and surfaces being prepared.

Apply in strict accordance with the manufacturers specification.

Apply oil based stoppers/fillers after priming. Apply water based stoppers/fillers before priming unless recommended otherwise by manufacturer. Patch prime water based stoppers/fillers when applied after priming.

Ensure that doors and opening windows, etc, are "eased" as necessary before coating. Prime any resulting bare areas.

Plastered surfaces and fibre cement boards to be washed down and allowed to dry completely.

Unfinished concrete surfaces clean with 1:4 solution of spirit of salts: water.

All floors where painting is to be carried out to be swept clean, walls dusted down and unpainted surfaces protected.

#### **Efflorescence**

Remove surface salts and other loose material with a stiff brush or coarse dry cloth.

Leave for 48 hours and repeat process if further efflorescence occurs.

Sand glossy surfaces to provide a key for finish.

#### **Ironmongery**

Remove from surfaces to be coated and re-fit on completion. Do not remove hinges unless instructed to do so

#### **Previously Uncoated Timber**

Ensure that large and loose knots are removed and made good with sound timber of the same species. Sand down flush Ensure that surfaces are clean and remove all oil, grease and excessive natural oils with suitable solvents

Sand to a smooth, even finish with arrises rounded or eased

Remove resinous bleeding by heat, apply two coats of knotting to resinous areas and all knots and allow to dry

Ensure that head of fasteners is countersunk sufficiently to hold stopping/filling. Fill nail and screw holes, joints, cracks, holes, depressions, open or coarse grain with matching coloured stopper/filler worked well in and finished off flush with surface. Sand smooth and remove dust

Sand down to remove all plaster stains pencil marks and other blemishes from timber that is to be oiled or stained

#### **Previously Coated Timber**

Strip any existing cracked or flaking varnish back to fresh wood

Sand down any discoloured areas to fresh wood

Ensure that surfaces are clean and remove all oil, grease and excessive natural oils with suitable solvents

Sound varnish to be sanded with 360 grit paper

#### **Uncoated Masonry/Render**

Remove dirt, surface deposits, loose and faking material with a stiff brush

Fill holes and cracks flush with surface, rub down

#### **Unpainted Plaster**

Remove dirt and surface deposits with a stiff brush

Rub down to remove nibs, trowel marks and plaster splashes

Lightly rub over trowelled glossy plaster with worn abrasive paper

Fill depressions, holes and cracks and lightly rub down flush with surface

#### **Steel Generally**

Remove all loose and faking paint

Feather edges of tightly bonding paint

#### **Rusted Areas**

Clean disk sand and wire brush to remove rust

Clean bare steel patches with a solvent wash

Rust convertor only to be used on small areas where hand cleaning is ineffective

Apply with a stiff brush ensuring penetration into any pitting

Inspect after two hours and recoat areas showing unconverted red rust

Prime surfaces as soon as possible after cleaning, and in any case within four hours

#### **Coating**

## **Painting Generally**

Operatives must be appropriately skilled and experienced in the use of specified materials and methods of application Do not use materials that show any bittiness when applied. Do not thin or intermix unless specified or recommended otherwise. If materials are found to have been thinned without authorization, the Project Manager may require an additional application of additional coats

Any priming as soon as possible on the same day as preparation is completed, ensure that coats are of adequate thickness and suit surface porosity

Adjacent coats of the same material must be of a different tint to ensure that each coat provides complete coverage

Apply coatings to clean, dust free, suitable dry surfaces in dry atmospheric conditions and after any previous coats have hardened. Lightly abrade between coats as necessary

Apply coatings evenly to give a smooth finish of uniform colour, free from brush marks, nibs, sags, runs and other defects. Cut in neatly and cleanly. Do not splash or mark adjacent surfaces

Keep all surfaces clean and free from dust during coating and drying. Adequately protect completed work from damage

#### Painted Joinery/woodwork

Before priming preservative treated timber, any cut surfaces to be retreated and all end grain to be liberally coated allowing it to soak in before recoating it

Pre-primed woodwork to be lightly rubbed down and patch prime to match existing

Prime: One coat primer, two coats to end grain which will be painted

Finish: Two coats Alkyd gloss, sanded down between coats

#### **Staining**

Check with stain manufacturer if primer is required for the species of timber and type of previously applied treatment. Apply stain in flowing coats. Redistribute excess material by brushing before stain has set. Allow not less than 12 hours between coats

#### Varnishing

Thin first coat with white spirits according to manufacturer's recommendations

Brush well in avoiding aeration and lay off

Apply further coats of varnish, rubbing down lightly between coats along the grain

#### **Bead Glazing to Coated Timber**

Before Glazing: Apply first two coats to rebates and beads

#### **Concealed Joinery Surfaces**

Inaccessible parts of joinery constructions are to be primed and/or coated before assembly

Where one or more additional coats are specified to be applied, they must be applied to all surfaces, including those that will be concealed when incorporated into the building

#### **Wooden Doors**

Varnish or paint bottom edges before hanging

#### Completion

Ensure that opening lights/windows/hinges and other moving parts move freely. Remove all masking tape and temporary coverings afterwards

#### **Protection**

Adequately protect all surfaces that are not to be coated

Protect all surfaces from dust and damp

Where doors are delivered to site in a finished condition, provide all necessary protection to the doors when applying coatings to the frames

#### **Air-conditioners**

Contractor to provide adequate power supply to air con unit

12-month warrantee to be included

Contractor is liable for any damages to structure

All work must be SABS approved

Each air con to be separately wired via isolator from the DB board and connected with a circuit breaker (see size and Phase requirements as stipulated in Bill)

D/P Isolator to be installed and connected adjacent to air-con unit internally (see size and Phase requirements as stipulated in Bill)

Electrical Certificate of Compliance to be issued on completion

Allow for drilling through wall and plaster/ patch and paint afterwards. Piping to installed through walls only, never glass panes

All piping/cabling to be in PVC trunking / ducting. Allow for correct lengths

Units always to be heating and cooling (unless otherwise stipulated in Bill)

All piping, brackets, gas up to commissioning to be included in pricing

Supply units of the following Manufacturers: Samsung, LG, Carrier, Daiken, York or similar (in warrantee and guarantee)

All Air-cons to be Inverter type, unless specified of the BOQ

# **Plumbing**

Only registered Plumbers to be employed for any plumbing & drainage work

Allow for  $\pm 2m^2$  tiling above each basin and sink

Allow for A Grade Glazed white tiles, 152 x 152mm, 5 – 6.5mm thick

Sinks size: 1350mm x 535mm unless otherwise specified in bill of quantities

Sink mixer for tea room sink to be 15mm chrome plated brass cobra mixer type tap

All basins to be white glazed, each fitted with an approved 32mm chrome plated brass waste fitting with screwed outlet, and a 15mm chrome plated brass elbow action tap connected to water supply

All sinks to be standalone stainless steel sink, work area, splash back on Pre-manufactured  $40 \times 32^{mm}$  stainless steel square tubing frames, 4 legs on adjustable pedestals. Exposed surfaces having a smooth finish, each fitted with an approved 32mm chrome plated brass waste fitting with screwed outlet, and a 15mm chrome plated brass Hospital goose neck tap

Stainless steel grade 316 or Type 304 to be used for stainless steel sinks

All material to be SABS approved

Make sure all existing water pipes and waste is in good working condition

All existing basins and sinks to be washed and cleaned

On each water supply line, a ball valve need to be installed as close as possible to outlet, this includes basins, sinks, toilets


Each tap to be visibly marked with "H" or a "Red" mark for Hot water and "C" or a "Blue" mark for Cold water **Geysers**: Install makes such as Franky, Kwikhot or similar. Install on a drip tray with drain pipe to outside, pressure valve, safety valve, shut off valve, overflow pipe. Isolator to be installed at least 1m from Geyser, hot and cold water supply lines to be bonded and earthed. Isolator to be wired to DB with dedicated double pole circuit breaker.

**Toilets**: these shall be deemed to include the following: WC Pan, flush valve or 11-liter cistern with flushing apparatus, float valve and flush pipe and all finishing's to pipes and cistern. To be the wash down type, approximately 400 high manufactured of white glazed fireclay or vitreous china, each provided with the compatible "P" or "S" –Traps, jointed to Pan. Pans and traps to be set on and encased in Class B concrete not less than 100mm thick at any point or position

**Wall mounted bowl urinals**: to be of white glazed fireclay or vitreous china, approximately 700 x 380mm in size with back flush entry, secured to wall with at least 2 concealed hanger brackets. Each urinal to be fitted with 38mm chrome plated domical grating, urinal complete with push button assembly, exposed type flush valve with ball-o-stop and wall flange. • Chrome plate finish. • Additional toilet piston screw • Non-hold open feature, spreader and all other necessary chrome plated brass fittings as well as a chrome plated brass bottle trap

**Hydro boil installations**: Install always above sink (see bill of quantities for size)

**Emergency shower:** complete body shower with eye station. Flow rate to be 60 liters per minute. At floor level, 700mm below shower head, the radius of water reaching the floor should be 200mm. At the eye station flow rate should be 6 liters per minute at a flow pressure safe enough not to injure the User. This unit to be 1 meter from floor level. Make use of emergency showers as supplied by Broen, Bull Maurice Trading or similar



Water tanks Pumps



#### Electrical

Only registered Electricians to be employed for any electrical work

Wires to be used for sockets outlets; 2.5mm<sup>2</sup> PVC

Colour for 2- compartment steel/PVC power skirting unless differently specified in bill of quantities (colour to be confirmed)

Normal plugs to be white and dedicated plugs to be red

Electrician to consult with Lab Manager regarding lab equipment when circuit are installed to prevent overloading, new plug points to be wired from distribution board and marked properly

Legend card in DB to be up to date

Electrical Certificate of Completion to be issued on completion

All material to be SABS approved

All installations to comply with SANS10142 installation rules

All additional /replaced plugs, isolators and light switches must be labelled on the cover and Distribution Board Circuit breakers to be SABS approved and type and size to be confirmed with Project Manager before installation Hydroboils: wire from DB Board with 30Amp double pole isolator next to Unit (at least 1m away) and 20Amp circuit breaker in DB board

#### **Shade ports**

Item	Single	Double	Triple
Pitch Height	900	1350	1350
Clearance	2100	2100	2100
Width	3000	5000	7500
Length of span	5500	5500	5500
Cross	50 x 2	50 x 2	57 x 2
Cable	6mm galvanized in all cases		
Hoops	42 x 2	42 x 2	50 x 2
Cantilever (bottom)	50 x 2		
Cantilever (top arm)	42 x 2		
Cantilever (brace)	34 x 2		
Columns	165 x 3.5 x 4000		
Columns	50 x 2	76 x 2	76 x 2
Foundations	500 x 600 x 900		
Concrete	20 MPA for all		

The hanging braces must be braced

The hanging brace must have a 12.5-degree angle

The hoops must be rolled on a rolling machine and not cranked/bend

Colour green

The cotton used for sewing the nets must be UV resistant

#### **Workbenches & Tops**

Worktops to be 32<sup>mm</sup> thick, either 600mm, 900mm or 1200mm, Formica brand post form - white (unless otherwise stipulated in Bill)

Where necessary 75mm holes must be drilled in worktops to accommodate computer cables and power supply to machinery and be made good with a plastic grommet

Pre-manufacture 30<sup>mm</sup> x 30<sup>mm</sup> steel square tubing frames as supplied by SA Lab or similar, sections of 1 000mm wide and 500mm deep or 1000mm wide and 800mm deep, for post form tops. All 4 legs to be on lockable castors or adjustable inserts as per BOQ wheel diameter 100mm. Bench Units to be equipped with water, basins, sinks, to be om adjustable pedestals. Benches could be 730mm or 900mm high (see bill of quantities) Sections to be bolted together, not welded. All steelwork to be epoxy powder coated in dove grey colour.

#### **Cupboards**

#### steel laboratory cupboards

Steel epoxy powder coated white cupboards to be manufactured and assembled as follows. Units specified in bill will be either a 4 drawer (450mm wide) or 2 doors with 1 shelve unit (750mm wide). Exterior and Interior to be White powder coated. Doors to be affixed with 2 brass heavy duty piano hinges each and drawers to be mounted on runners. Each drawer and door to be equipped with a PVC recessed handle. All floor cupboards to be on 4 castors each, front wheels to be lockable. All doors to be double paneled for stability and no wobbly door and cupboards will be accepted. See bill of quantities for sizes and combinations.

#### wooden cupboards

In kitchens timber cupboards to be manufactured and installed with 16mm melamine covered pressed wood. All cupboards to be on 100mm pedestals. Exterior to be Oak finish and Interior to be white finish. All visible exterior edges to be finished in Oak and internally white. Each drawer faces and door to have wrap around finish. Doors to be affixed on 2 hinges each and drawers on runners. Each drawer and door to be equipped with an aluminium handle

#### **Doors**

All doors to be hung in such a way that the clearance gap between door and frame after hanging shall not exceed 2mm at sides and head. The floor clearance to be preferably 2mm but may be increased to accommodate an uneven floor finish. Exterior doors shall be hung on brass hinges. Aluminium frame glass doors to have 6mm safety laminated glass fitted, to be hung on aluminium hinges, not less than 4 hinges on a 2 100mm high door. On higher doors at least 5 hinges should be fitted. The glass door must have a mid-rail with bottom half either glass or solid aluminium, the aluminium door profile must be 90mm all-round All exterior doors to be fitted with an aluminium and rubber weather strip at the bottom. Each door to be equipped with 2 door handles. Type to be confirmed by Project Manager. Behind every door a door stop should be installed on top of the floor to prevent the door handle making contact with the wall – clearance between wall and door handle to be approximately 20mm.

#### **Paint**

Two final coats of White paint to all surfaces, ceiling and walls. Door colours to be confirmed by Project Manager, if not varnished

Existing pipes against wall must be colour coded painted, for example gas, water, oxygen

Rhino board surface to receive Rhinolite to a smooth finish on dry walls

Before painting can commence, every defect/uneven surface must be repaired

Patch prime new and exposed plaster areas with 1 coat and allow drying. Coat 1 may be thinned up to 10% with mineral turpentine to aid absorption. Allow 4 hours drying time at  $23^{\circ}$  c . Three (3) coats of paint to dry wall. Paint texture and type to match existing, Colour for walls and steel frames to be white unless otherwise confirmed by Project Manager

One coat metal primer to steel work and two coats final oil based enamel

Paint to be Plascon double velvet, Dulux, Prominent or similar

#### **VINYL Floors**

Only use Heavy duty safety Vinyl flooring which should be slip resistant and factory sealed with Polyurethane as supplied by Marley or Polyfloor. Roll to be at least 2 metres wide and vinyl 2 - 2.5 mm thick. Colour to be confirmed by Project Manager. Sample to be signed off by Project Manager before installation commences

Ensure that the sub-floor is completely smooth, level, hard, dry and clean before laying commences

Joints to be butted, grooved and heat welded ensuring that the welding rod bonds to more than 70% of the sheet thickness. It is essential that on completion the installation be rolled, in both directions with an articulated 68kg three sectional metal floor roller.

Skirting; install coving where wall meets floor and continue with vinyl floor 100mm high. Finish off with Vinyl/PVC Ribbon

Installation to be done by an approved Installer in accordance with the Manufacturers specifications

#### **TILE Floors**

Ensure that the sub-floor is completely smooth, level, hard, dry and clean before laying commences

Only use A Grade Acid resisting Ceramic/ porcelain tiles, 10mm thick,  $600^{mm}$  x  $600^{mm}$  for floors and  $600^{mm}$  x  $200^{mm}$  for walls in size or as per BOQ

All tiles need to have "Aluminium Tile Edge Trim" where necessary. Bull nose or square one may be used

Use SABS approved tile cement and apply as per Manufacturers instructions (colour to be confirmed by Project Manager)

Use SABS approved water proof Acid resistant grout. Gaps 5 – 10mm (colour grey)

Skirtings to be 100mm high where required, coved at junction with floor and rounded on top edge

#### **CARPET Floors**

Ensure that the sub-floor is completely smooth, level, hard, dry and clean before laying commences. Installation to be done by an approved Installer in accordance with the Manufacturer's specifications

### **TILE Walls**

Ensure that the wall is completely smooth, level, hard, dry and clean before laying commences

Only use A Grade Acid resisting Ceramic tiles, 10mm thick, 600 x 200mm in size

Use SABS approved tile cement and apply as per Manufacturers instructions (colour to be confirmed by Project Manager)

All tiles need to have "Aluminium Tile Edge Trim" where necessary. Bull nose or square one may be used

Use SABS approved water proof Acid resistant grout. Gaps 5 – 10mm (colour grey)

All edges and corners to be finished off with PVC edging strips. Colour to be confirmed per job depending on tile colour.

#### Glazing

All Internal glass in panes not exceeding 1.5m<sup>2</sup> of surface area shall be 4mm clear float glass

All Internal glass in panes exceeding 1.5m<sup>2</sup> of surface area shall be 6mm laminated safety glass with a Manufacturer's warranty against defects and discoloration

All Exterior glass up to a height of 10m in panes not exceeding 2.9m<sup>2</sup>of surface area shall be 6.38mm PVB Laminated annealed safety glass. Above 10m the Project Manager should appoint a Glazing Competent Person

Mirrors to comply with SABS requirements. Unframed mirrors to have polished edges

All glass in aluminium doors and frames to be fitted with 6mm laminated safety glass

All exterior facing windows to be tinted with Klingshield or similar product, unless otherwise stipulated. Colour to be confirmed by Project Manager

#### **Blinds**

Vertical Group 3 blinds to be installed (colour to be confirmed by Project Manager)

Blinds to be re-measured on site before manufacturing and installation

Vertical blinds to be 127mm

Horizontal blinds 50mm

Horizontal blinds to be either Aluminium/ Wood Venetian conformation on the BOQ

Measurements given is only for tendering purpose

#### **Suspended ceilings**

Install suspended ceilings as per Manufacturers instructions such as Donn Products or similar. Panels to be vinyl cladded smooth white panels, 1200 x 600 x 12.5mm on suspended pre-painted exposed tee trusses, including main and cross tees, hangers, grids, etc., all level and properly secured. At edges use 25mm pre-painted shadow line aluminium cornices

#### **Partitioning**

Drywall partitioning construction and support frame system including finishes to be as per Manufacturer's specifications

Minimum requirement GPG Gypsum Gyproe Standard 40 Db, ½ hour fire rating with a stud (63.5mm) and track system. Positioning at 600mm cc fixed to 63.5mm top & bottom track clad on both sides with 12.5mm taper edged rhino board affixed with 25mm drywall screws at 220mm cc

All corners to be finished off with drywall corner strips. All joints to be taped, jointed and smoothed before painting Aluminium skirtings to be affixed to all drywall partitioning unless otherwise specified

Door and window frames fitted in drywall partitioning to be installed as per Manufacturer's specifications

## Lockers (Timber)

Timber lockers to be manufactured and assembled with 16mm melamine covered pressed wood. Exterior to be Oak melamine finish, including all visible edges. Interior to be White melamine finish, including all visible edges and backing. If the back side of any cupboard will be visible after installation, those exposed areas or entire area should be cladded with white melamine. Inside dimensions of each cubicle to be 300mm². Units to be assembled 3 on top of each other. Each locker to have a wrap around Oak melamine finished door, affixed with piano hinges. Each locker to be equipped with a lock and 2 keys as well as an aluminium handle (no plastic handles). Each stack of 3 to be assembled as 1 unit and 100mm adjustable chrome plated legs to be affixed underneath bottom locker.

#### **Lab Coat Hooks**

Lab coat hooks must be aluminium base and hooks with a minimum of three per set

### Lockers (Steel)

Solid steel lockers which should be epoxy powder coated to be supplied. Sets to be single 4 tier lockers. Colour to Ivory/Beige/Karoo. Each door to be lockable and correct size padlocks with 2 keys each, per locker, to be provided

#### Locks

All exterior door locks to have 4 lever mortice locks with 2 keys each fitted (unless otherwise specified in bill)

All interior door locks to have 2 lever mortice locks with 2 keys each fitted (unless otherwise specified in bill)

All security type gates to have 7 lever locks with 2 keys each fitted

All timber lockers to have normal cupboard locks with 2 keys each fitted

All steel lockers to have padlocks with 2 keys each fitted

#### **Steel shelving**

Only powder coated grey steel shelving to be installed in storage areas, archives & wash up areas (no wood allowed). Shelving to be of an adjustable type with each shelve at least 500mm wide and 450mm deep. Bottom shelve to be at least 200mm from the floor and top shelve not higher than 2 100mm. In between top and bottom another 3 shelves, evenly spaced, to be fitted (in total 5 tier shelving). Each vertical steel supports to be affixed to the wall at, at least 2 positions in the top half. As supplied by Krost shelving or similar

#### Signage

Colour code:

All interior signs to be White Perspex with smooth edges, with vinyl (7 year) applied onto the Perspex All exterior signs to be White Chromadek , with vinyl (7 year) applied onto the metal

Pantone: Coated - 383C / Uncoated - 397 U

CMYK - C:40 M:0 Y:100 K0

PLEASE TAKE NOTE THAT THE ABOVE SPECIFICATIONS AND MEASUREMENTS ARE SUBJECT TO CHANGE AS MAY BE DETERMINED BY THE FINAL APPROVED DRAWINGS OR COMPULSARY SITE MEETING FOR THE JOB IN QUESTION

#### **WORKS AGREEMENT**

## **Contractor: The contactor shall:**

- Provide adequate supervision and management of the works at all times.
- Provide toilet facilities for use by his workers except where provided by the client (NHLS).
- Storage space is not always available for material and sufficient arrangements should be catered for and included in pricing.
- Submit all local authority notices by the works.
- Comply with all statutes, regulations and bylaws of local or other authorities having jurisdiction regarding the execution of the works and obtain all certificates and other documents required by such authorities.
- Notify the Project Manager where compliance with any statute, regulation or bylaw requires a change or variation to the works upon which such change shall be deemed to be a contract instruction.
- Immediately begin the works and continue at a rate of progress satisfactory to the Project Manager in terms of the agreement.
- Comply with all contract instructions in good time.
- Bring the works, within the constructed period, to practical completion in terms of completion.
- Bring the works to final completion.
- Surplus material and waste to be carted away to a suitable dumping site to be found by the Contractor, outside the boundary of the site

#### **Completion**

#### **Practical Completion**

- The Project Manager shall inspect the works from time to time to give the contractor interpretations and guidance on the standard and state of completion of the works which he will require the contractor to achieve for practical completion
- The contractor shall inform the Project Manager of the date on which he expects to achieve practical completion
- The Project Manager shall inspect the works on or before the date requested by the contractor

#### Where the works:

- Has reached practical completion the Project Manager shall at once issue a certificate of practical completion to the contractor
- Has not reached practical completion the Project Manager shall issue a practical completion list to the contractor detailing the outstanding work to be done and defects to be rectified to achieve practical completion
- Is not ready for practical completion inspection the Project Manager shall issue a list as a general guide to the contractor of the outstanding areas of work and defects to be attended to before he can request a further inspection

# **Final Completion**

- Within seven calendar days of practical completion the Project Manager shall prepare and issue to the contractor a final completion list detailing the incomplete work and defects to be rectified within a reasonable period
- The defects liability period of fourteen calendar days shall start on the date of practical completion
- On the expiry of the defects liability period the Project Manager shall immediately inspect the works for final completion. Where the works:
- Has reached final completion the Project Manager shall at once issue a certificate of final completion to the contractor

- Has not reached final completion the Project Manager shall issue a defects list to the contractor detailing any incomplete work and defects to be rectified before the Project Manager will undertake a further inspection
- Where the contractor has achieved final completion the latent defects liability period shall end three years from the date of final completion

#### **Employer:** The employer shall:

- Hand over the site to the contractor by the date stated in the schedule. The construction period and latent defects liability period shall commence with the handover of the site.
- Arrange for water, sewer and electrical connections as required and pay all fees concerning this
- Provide water and electricity as required for the execution of the works free of charge.
- Not issue instructions to, interfere with, hinder or obstruct any of the contractor's workers or any other persons employed or acting on behalf of the contractor.

#### **Risk and Insurance**

- The Contractor indemnifies the NHLS against any loss in respect of claims from other parties arising out of or due to the execution of the works or occupation of the site by the contractor consequent upon:
  - Death or bodily injury or illness of any person.
  - o Physical loss and damage to any property other than the works.
  - o Removal of or interference with lateral support of an adjoining property.
- The contractor shall take out insurances in respect of his employees as are required by law.
- Where, in the opinion of the Project Manager, loss and damage to the works due to the contractor's negligence the contractor shall be liable for such loss and damage.
- The contractor shall in all circumstances be at risk for loss of, or damage to his construction plant or vehicles.
- The contractor shall enclose the site along the facades where work is being done. He shall furthermore allow for all the required scaffolding, gantries, hoarding, etc. to safeguard pedestrian traffic on the sidewalks or paths as well as vehicular traffic in the streets
- The form of scaffolding, gantries, hoardings, etc., must be fully detailed in his "method statement" as previously required. It is not the intention to prohibit or deviate pedestrians or traffic during construction and Tenderers are to account for this when pricing the Tender
- Adequate warning signs/ lights/ etc. are to be employed where required. If the Tenderer requires the full pavement
  width and even part of the adjacent street, then he must make all the necessary arrangements with local authorities
  for the pavement and street closure as well as pay for all fees in connection therewith including the loss of income
  due to parking meters
- The existing premises will be occupied at all times and the Contractor will be required to keep all noise to a minimum

#### **Safety**

- From the date of site handover to the Contractor until the completed work is handed back to the Employer, the Contractor shall be responsible for maintaining safe working conditions on site
- The Contractor shall be responsible in terms of the Occupational Health and Safety Act, 1993 (Act No 85 of 1993) and the regulations promulgated in terms of the Act or Factories, Machinery and Buildings Work Act, whichever is applicable
- The Contractor shall be responsible for supplying and installing the required safety signs as determined by the Occupational Health and Safety Act, 1993 (Act No 85 of 1993) All safety signs shall comply with the requirements of the latest edition of SANS 11861 as Applicable

#### Programme

• The Contractor shall submit his programme of work to the Project Manager not later than 14 days after the Contractor has been notified of the acceptance of his tender. If necessary, the Project Manager may instruct the Contractor to adjust his programme to suit other activities