Centrifuge with large visible display, Bio-safe rotor & rotor easy to clean, Anti sample overflow that will prevent accidental leakage during the process & prevent contamination. 2 Rotor that can be fully autoclaved for unlimited time, Quick acces to samples with snap lid, Active imbalance indentification & cut off, Max speed 4000rpm with speed accuracy 3 Rotor capacity btwn 2 & 15 ml of total of 64 serum / plasma sample tubes, run time 30 sec-99min/continuous, Noise level <60 Dba at 2130xg. 4 Manufactured according to international Std/Regulations, Over speed & Teemperature detection safety measures. 5 Automatic internal diagnosis safety devices Comply Not Comply installation records .	RFQ NON REFRIDGERATED CENTRIFUGE		Glen Grey	
Centrifuge with large visible display, Bio-safe rotor & rotor easy to clean, Anti sample overflow that will prevent accident alleakage during the process & prevent contamination. 2 Rotor that can be fully autoclaved for unlimited time, Quick acces to samples with snap Ild, Active imbalance indentification & cut off, Max speed 4000rpm with speed accuracy 3 Rotor capacity btwn 2 & 15 ml of total of 64 serum / plasma sample tubes, run time 30 sec-99min/continuous, Noise level <60 Dba at 2130xg. Comply Not Comply Not Comply Not Comply Not Comply Not Comply Not Comply Not Comply Comply Not Comply Not Comply Not Comply Not Comply Not Comply Comply Not Comply Not Comply Comply Not Comply Not Comply Comply Not Comply Section 1 of 1	The state of the s		Glen Grey	
Centrifuge with large visible display, Bio-safe rotor & rotor easy to clean, Anti sample overflow that will prevent accident alleakage during the process & prevent contamination. 2 Rotor that can be fully autoclaved for unlimited time, Quick acces to samples with snap Ild, Active imbalance indentification & cut off, Max speed 4000rpm with speed accuracy 3 Rotor capacity btwn 2 & 15 ml of total of 64 serum / plasma sample tubes, run time 30 sec-99min/continuous, Noise level <60 Dba at 2130xg. Comply Not Comply Not Comply Not Comply Not Comply Not Comply Not Comply Not Comply Comply Not Comply Not Comply Not Comply Not Comply Not Comply Comply Not Comply Not Comply Comply Not Comply Not Comply Comply Not Comply Section 1 of 1				
Centrifuge with large visible display, Bio-safe rotor & rotor easy to clean, Anti sample overflow that will prevent accident alleakage during the process & prevent contamination. 2 Rotor that can be fully autoclaved for unlimited time, Quick acces to samples with snap Ild, Active imbalance indentification & cut off, Max speed 4000rpm with speed accuracy 3 Rotor capacity btwn 2 & 15 ml of total of 64 serum / plasma sample tubes, run time 30 sec-99min/continuous, Noise level <60 Dba at 2130xg. Comply Not Comply Not Comply Not Comply Not Comply Not Comply Not Comply Not Comply Comply Not Comply Not Comply Not Comply Not Comply Not Comply Comply Not Comply Not Comply Comply Not Comply Not Comply Comply Not Comply Section 1 of 1	4			
to clean, Anti sample overflow that will prevent accident al leakage during the process & prevent contamination. 2 Rotor that can be fully autoclaved for unlimited time, Quick acces to samples with snap Ild, Active imbalance indentification & cut off, Max speed 4000rpm with speed accuracy 3 Rotor capacity btwn 2 & 15 ml of total of 64 serum / plasma sample tubes, run time 30 sec-99min/continuous, Noise level <60 Dba at 2130xg. 4 Manufactured according to international Std/Regulations, Comply Not Comply Over speed & Teemperature detection safety measures. 5 Automatic internal diagnosis safety devices Comply Not Comply installation records .				
leakage during the process & prevent contamination. 2 Rotor that can be fully autoclaved for unlimited time, Quick acces to samples with snap lid, Active imbalance indentification & cut off, Max speed 4000rpm with speed accuracy 3 Rotor capacity btwn 2 & 15 ml of total of 64 serum / plasma sample tubes, run time 30 sec-99mln/continuous, Noise level <60 Dba at 2130xg. 4 Manufactured according to international Std/Regulations, Comply Not Comply Over speed & Teemperature detection safety measures. 5 Automatic internal diagnosis safety devices Comply Not Comply installation records .			Comply	Not Comply
Rotor that can be fully autoclaved for unlimited time, Quick acces to samples with snap Ild, Active imbalance indentification & cut off, Max speed 4000rpm with speed accuracy 3 Rotor capacity btwn 2 & 15 ml of total of 64 serum / plasma sample tubes, run time 30 sec-99min/continuous, Noise level <60 Dba at 2130xg. 4 Manufactured according to international Std/Regulations, Comply Not Comply Over speed & Teemperature detection safety measures.		al		
Rotor that can be fully autoclaved for unlimited time, Quick acces to samples with snap lld, Active imbalance indentification & cut off, Max speed 4000rpm with speed accuracy 3 Rotor capacity btwn 2 & 15 ml of total of 64 serum / plasma sample tubes, run time 30 sec-99min/continuous, Noise <60 Dba at 2130xg. 4 Manufactured according to international Std/Regulations, Comply Not Comply Over speed & Teemperature detection safety measures.	leakage during the process & prevent contamination.	ĺ		
Rotor that can be fully autoclaved for unlimited time, Quick acces to samples with snap Ild, Active imbalance indentification & cut off, Max speed 4000rpm with speed accuracy 3 Rotor capacity btwn 2 & 15 ml of total of 64 serum / plasma comply sample tubes, run time 30 sec-99min/continuous, Noise comply sample tubes, run time 30 sec-99min/continuous, Noise comply comply comply comply comply comply devel comply				
Rotor that can be fully autoclaved for unlimited time, Quick acces to samples with snap lld, Active imbalance indentification & cut off, Max speed 4000rpm with speed accuracy 3 Rotor capacity btwn 2 & 15 ml of total of 64 serum / plasma sample tubes, run time 30 sec-99min/continuous, Noise <60 Dba at 2130xg. 4 Manufactured according to international Std/Regulations, Comply Not Comply Over speed & Teemperature detection safety measures.				
to samples with snap lid,Active imbalance indentification & cut off, Max speed 4000rpm with speed accuracy 3 Rotor capacity btwn 2 & 15 ml of total of 64 serum / plasma Comply Not Comply sample tubes, run time 30 sec-99min/continuous, Noise level <60 Dba at 2130xg. 4 Manufactured according to international Std/Regulations, Comply Not Comply Over speed & Teemperature detection safety measures.	2			
to samples with snap lid,Active imbalance indentification & cut off, Max speed 4000rpm with speed accuracy 3 Rotor capacity btwn 2 & 15 ml of total of 64 serum / plasma Comply Not Comply sample tubes, run time 30 sec-99min/continuous, Noise level <60 Dba at 2130xg. 4 Manufactured according to international Std/Regulations, Comply Not Comply Over speed & Teemperature detection safety measures.	Rotor that can be fully autoclaved for unlimited time. C	uick acces	Comply	Not Comply
3 Rotor capacity btwn 2 & 15 ml of total of 64 serum / plasma Comply Not Comply sample tubes, run time 30 sec-99min/continuous, Noise <60 Dba at 2130xg. Comply Not Comply Manufactured according to international Std/Regulations, Comply Over speed & Teemperature detection safety measures. 5 Automatic internal diagnosis safety devices Comply Not Comply Installation records . Comply Not Comply				not compry
Rotor capacity btwn 2 & 15 ml of total of 64 serum / plasma				
Rotor capacity btwn 2 & 15 ml of total of 64 serum / plasma sample tubes,run time 30 sec-99min/continuous, Noise 4 Manufactured according to international Std/Regulations, Over speed & Teemperature detection safety measures. S Automatic internal diagnosis safety devices Installation records. Comply Not Comply Not Comply Not Comply Not Comply				
Rotor capacity btwn 2 & 15 ml of total of 64 serum / plasma sample tubes,run time 30 sec-99min/continuous, Noise 4 Manufactured according to international Std/Regulations, Over speed & Teemperature detection safety measures. S Automatic internal diagnosis safety devices Installation records. Comply Not Comply Not Comply Not Comply Not Comply				
Rotor capacity btwn 2 & 15 ml of total of 64 serum / plasma sample tubes,run time 30 sec-99min/continuous, Noise 4 Manufactured according to international Std/Regulations, Over speed & Teemperature detection safety measures. S Automatic internal diagnosis safety devices Installation records. Comply Not Comply Not Comply Not Comply Not Comply	3			
sample tubes, run time 30 sec-99min/continuous, Noise level			Committee	
4 Manufactured according to international Std/Regulations, Over speed & Teemperature detection safety measures. S Automatic internal diagnosis safety devices Installation records . Comply Not Comply Not Comply			Comply	Not Comply
Manufactured according to international Std/Regulations, Comply Over speed & Teemperature detection safety measures. 5 Automatic internal diagnosis safety devices Comply Not Comply Installation records .	· · · · · · · · · · · · · · · · · · ·	level		
Manufactured according to international Std/Regulations, Over speed & Teemperature detection safety measures. 5 Automatic internal diagnosis safety devices Installation records . Comply Not Comply Not Comply	COU DDA at 2130xg.			
Manufactured according to international Std/Regulations, Over speed & Teemperature detection safety measures. 5 Automatic internal diagnosis safety devices Installation records . Comply Not Comply Not Comply				
Manufactured according to international Std/Regulations, Over speed & Teemperature detection safety measures. 5 Automatic internal diagnosis safety devices Installation records . Comply Not Comply Not Comply				
Over speed & Teemperature detection safety measures. 5 Automatic internal diagnosis safety devices Comply Not Comply Installation records .	<u> </u>			
5 Automatic internal diagnosis safety devices Comply Not Comply Installation records .	,		Comply	Not Comply
Automatic internal diagnosis safety devices Comply Not Comply Installation records .	Over speed & Teemperature detection safety measures			
Automatic internal diagnosis safety devices Comply Not Comply Installation records .				
Automatic internal diagnosis safety devices Comply Not Comply Installation records .				
Automatic internal diagnosis safety devices Comply Not Comply Installation records .				
Installation records .	5			
Installation records .	Automatic internal diagnosis safety devices		Comply	Not Comply
	Installation records.	ŀ		
Calibration certificate by SANAS accredited supplier.	Calibration certificate by SANAS accredited supplier.			

Wispola autory