



REQUEST FOR QUOTATION (RFQ)

RFQ NO: 1698165

DESCRIPTION: REQUEST FOR RENOVATIONS FOR IT MAIN BUILDING AT NHLS SANDRINGHAM CAMPUS

ISSUED BY:

PREPARED BY:

SUPPLY CHAIN MANAGEMENT NATIONAL HEALTH LABORATORY SERVICE 1 MODDERFONTEIN ROAD SANDRINGHAM 2092 SUPPLY CHAIN MANAGEMENT NATIONAL HEALTH LABORATORY SERVICE NO.1 MODDERFONTEIN ROAD SANDRINGHAM 2092

Quotation Queries:	Technical Queries:
CONTACT NAME: PROCUREMENT OFFICE	CONTACT NAME: PROCUREMENT OFFICE
E-MAIL ADDRESS: procurementcorporate@nhls.ac.za	E-MAIL ADDRESS: procurementcorporate@nhls.ac.za

NAME OF A BIDDER:.....

CLOSING DATE: 24 JUNE 2025 AT 11:00 QUOTATION VALIDITY PERIOD: The quotation validity period is 90 days.



CO	NTENTS	PAGE
1.	PART A INVITATION TO QUOTE (RFQ) SBD 1	3
2.	TERMS AND CONDITIONS OF THE REQUEST FOR QUOTATION (RFQ)	6
3.	SCOPE OF WORK	8
4.	PRICING SCHEDULE	25
5.	FORM OF OFFER (SBD 7)	26
6.	RFQ EVALUATION PROCESS AND CRITERIA	27
7.	SCHEDULE OF WORK CARRIED OUT BY THE BIDDER	29
8.	STANDARD BIDDING DOCUMENTATION (SBDs)	30
	AUTHORITY FOR SIGNATORY	



1. PART A INVITATION TO BID

SBD 1

		A INVITATION T					
YOU ARE HEREB SERVICE (NHLS)	SY INVITED TO BI	ID FOR REQUIRE	MENTS OF	THE N	NATIONAL	HEALTH L	ABORATORY
BID NUMBER: F	RFQ NO: 1698165	CLOSING DATE:	24 JUNE	2025	CLOS	ING TIME:	11:00AM
DESCRIPTION C	AMPUS	NOVATIONS FOR					
BID RESPONSE D							
NHLS RECEPTION	N: RFQ BOX: NO.	1 MODDERFONTE	EIN ROAD,	SAND	RINGHAM,	JOHANNE	SBURG
BIDDING PROC DIRECTED TO	EDURE ENQUI	RIES MAY BE	TECHNIC	CAL EN	QUIRIES N	MAY BE DIF	RECTED TO:
CONTACT PERSON	PROCUREMEN		CONTAC PERSON		PROCUI	REMENT O	FFICE
E-MAIL ADDRESS	procurementcorp	orate@nhls.ac.za	E-MAIL A	DDRES	SS procuren	nentcorpora	te@nhls.ac.za
SUPPLIER INFOR							
NAME OF BIDDEF	₹						
POSTAL ADDRESS							
STREET ADDRESS							
TELEPHONE NUMBER	CODE				NUMBER		
CELLPHONE NUMBER							
FACSIMILE NUMBER	CODE				NUMBER		
E-MAIL ADDRESS	3						
VAT REGISTRATION NUMBER							
SUPPLIER COMPLIANCE STATUS	TAX COMPLIANCE SYSTEM PIN:		O R	CENT RAL SUPP LIER DATA BASE No:	MAAA	Λ.	
B-BBEE STATUS LEVEL VERIFICATION		LICABLE BOX]	B-BBEE LEVEL AFFIDAV	S	TATUS SWORN	[TICK BOX]	APPLICABLE
CERTIFICATE	Yes	No				Yes	No
[A B-BBEE STAT MUST BE SUBMIT	US LEVEL VERI	FICATION CERTING QUALIFY FOR	FICATE/ S PREFERE	WORN NCE P	AFFIDAV	IT (FOR E	



	Yes No [IF YES ENCLOSE PROOF]	ARE YOU A FOREIGN BASED SUPPLIER FOR THE GOODS /SERVICES /WORKS OFFERED?	□ _{Yes} □ _{No} [IF YES, ANSWER THE QUESTIONNAIRE BELOW]
QUESTIONNAIRE TO	BIDDING FOREIGN SUPPLIE	RS	
DOES THE ENTITY H DOES THE ENTITY H DOES THE ENTITY H	SIDENT OF THE REPUBLIC OF HAVE A BRANCH IN THE RSA? HAVE A PERMANENT ESTABLI HAVE ANY SOURCE OF INCOM LE IN THE RSA FOR ANY FORI	SHMENT IN THE RSA? IE IN THE RSA?	YES NO YES NO YES NO YES NO YES NO
IF THE ANSWER IS " A TAX COMPLIANCI	NO" TO ALL OF THE ABOVE, E STATUS SYSTEM PIN COD REGISTER AS PER 2.3 BELOV	THEN IT IS NOT A REQUIREM E FROM THE SOUTH AFRIC	MENT TO REGISTER FOR

PART B

TERMS AND CONDITIONS FOR BIDDING

1. BID SUBMISSION:

- 1.1. BIDS MUST BE DELIVERED BY THE STIPULATED TIME TO THE CORRECT ADDRESS. LATE BIDS WILL NOT BE ACCEPTED FOR CONSIDERATION.
- 1.2. ALL BIDS MUST BE SUBMITTED ON THE OFFICIAL FORMS PROVIDED-(NOT TO BE RETYPED) OR IN THE MANNER PRESCRIBED IN THE BID DOCUMENT.
- 1.3. THIS BID IS SUBJECT TO THE PREFERENTIAL PROCUREMENT POLICY FRAMEWORK ACT, 2000 AND THE PREFERENTIAL PROCUREMENT REGULATIONS, 2017, THE GENERAL CONDITIONS OF CONTRACT (GCC) AND, IF APPLICABLE, ANY OTHER SPECIAL CONDITIONS OF CONTRACT.
- 1.4. THE SUCCESSFUL BIDDER WILL BE REQUIRED TO FILL IN AND SIGN A WRITTEN CONTRACT FORM (SBD7).
- 2. TAX COMPLIANCE REQUIREMENTS
- 2.1 BIDDERS MUST ENSURE COMPLIANCE WITH THEIR TAX OBLIGATIONS.
- 2.2 BIDDERS ARE REQUIRED TO SUBMIT THEIR UNIQUE PERSONAL IDENTIFICATION NUMBER (PIN) ISSUED BY SARS TO ENABLE THE ORGAN OF STATE TO VERIFY THE TAXPAYER'S PROFILE AND TAX STATUS.
- 2.3 APPLICATION FOR TAX COMPLIANCE STATUS (TCS) PIN MAY BE MADE VIA E-FILING THROUGH THE SARS WEBSITE WWW.SARS.GOV.ZA.
- 2.4 BIDDERS MAY ALSO SUBMIT A PRINTED TCS CERTIFICATE TOGETHER WITH THE BID.
- 2.5 IN BIDS WHERE CONSORTIA / JOINT VENTURES / SUB-CONTRACTORS ARE INVOLVED, EACH PARTY MUST SUBMIT A SEPARATE TCS CERTIFICATE / PIN / CSD NUMBER.
- 2.6 WHERE NO TCS PIN IS AVAILABLE BUT THE BIDDER IS REGISTERED ON THE CENTRAL SUPPLIER DATABASE (CSD). A CSD NUMBER MUST BE PROVIDED.
- 2.7 NO BIDS WILL BE CONSIDERED FROM PERSONS IN THE SERVICE OF THE STATE, COMPANIES WITH DIRECTORS WHO ARE PERSONS IN THE SERVICE OF THE STATE, OR CLOSE CORPORATIONS WITH MEMBERS PERSONS IN THE SERVICE OF THE STATE."

NB: FAILURE	TO PROVIDE /	OR COMPLY WIT	H ANY OF THE	ABOVE PARTICU	LARS MAY RENDER
THE BID INVA	ALID.				

DATE:		
CAPACITY UNDER WHICH THIS BID IS SIGNED: (Proof of authority must be submitted e.g. company re	esolution)	
SIGNATURE OF BIDDER:		
SIGNATURE OF BIDDER:		



2. TERMS AND CONDITIONS OF REQUEST FOR QUOTATION (RFQ)

- This document may contain confidential information that is the property of the NHLS and the Client.
- b) No part of the contents may be used, copied, disclosed or conveyed in whole or in part to any party in any manner whatsoever other than for preparing a proposal in response to this RFQ, without prior written permission from NHLS and the Client.
- All Copyright and Intellectual Property herein vests with NHLS and its Client.
- d) Late and incomplete submissions will not be accepted.
- e) SDB 7 (form of offer) must be completed, and should the total RFQ prices differ, the one indicated on the form of offer shall be considered the correct price.
- f) Any bidder who has reasons to believe that the RFQ specification is based on a specific brand must inform NHLS before RFQ closing date
- g) Bidders are required to submit a valid Tax Clearance Certificate and Tax clearance verification PIN, Failure to submit the Tax Pin and valid Tax Clearance Certificate will result in the invalidation of this RFQ.
- h) It is the responsibility of the bidder to ensure that NHLS is in possession of the bidder's valid Tax Clearance certificate. The onus is on the bidder to ensure that NHLS receives a valid Tax Certificate as soon as the validity of the said certificate expires.
 - A compulsory clarification site meeting or briefing session will be conducted at: NHLS, No.1 Modderfontein Road, Sandringham, 19 June 2025 at 10:00am.

The tenderer shall inspect and examine the Site and its surroundings and shall satisfy himself/herself before submitting

his/her quotation. The bidder must be represented at the site inspection by a person who is suitably qualified and experiences to comprehend the implications of the work involved.

- The contractor will be responsible for final measurements.
- i) Writing must be in block letters and black ink.
- j) Quotation procedure using the two (2) stage system will apply: **Not applicable**.
- k) Respondents arriving after the allocated time of the briefing session and failing to attend the compulsory RFQ/Site briefing will be disqualified
- No services must be rendered or goods delivered before an official NHLS Purchase Order form has been received.
- m) This RFQ will be evaluated in terms of the 80/20 preference point system prescribed by the Preferential Procurement Regulations, 2022.
- n) All questions regarding this RFQ must be forwarded to the procurementcorporate@nhls.ac.za 24 hours prior the RFQ closing date.
- o) The General Conditions of Contract (GCC) issued by National Treasury are applicable.
- p) In case of bids where Consortia / Joint Ventures, Consortia/Joint Venture agreement signed by both parties must be submitted with bid proposal. Each JV partner must submit all their mandatory documentation.

Quotation must be All-Inclusive

- i. The Supplier shall allow in the quotation for all deliverables as stipulated in the scope, labour, material, consumables, accessories, software, supervision, overhead costs, profit, royalties, all taxes, levies, duties, variations in exchange rates (if applicable), disbursements and everything necessary for the execution and completion of the works in accordance with the quotation documents.
- ii. Value Added Tax (VAT) shall be excluded from the rates and prices and provided for as the total VAT on the cost of the Works in the Summary of Schedule of Rates and Prices.



- iii. The Supplier rates and prices shall be fixed for the duration of the contract and not subject to adjustment except as provided for in the conditions of contract.
- iv. The offer must be in ZAR currency.
- v. The NHLS reserve the right to do due diligence on the quotations and to benchmark prices quoted.
- vi. Quotes should be submitted on an official letterhead and duly signed.

Delays in the supplier's performance

- Delivery of the goods and performance of services shall be made by the supplier in accordance with the time schedule prescribed by the purchaser in the contract.
- ii. If at any time during performance of the contract, the supplier or its subcontractor(s) should encounter conditions impeding timely delivery of the goods and performance of services, the supplier shall promptly notify the purchaser in writing of the fact of the delay, its likely duration, and its cause(s). As soon as practicable after receipt of the supplier's notice, the purchaser shall evaluate the situation and may at his discretion extend the supplier's time for performance, with or without the imposition of penalties, in which case the extension shall be ratified by the parties by amendment of contract.
- iii. The right is reserved to procure outside of the contract small quantities or to have minor essential services executed if an emergency arises, the supplier's point of supply is not situated at or near the place where the supplies are required, or the supplier's services are not readily available.
- iV. Except as provided under GCC Clause 25, a delay by the supplier in the performance of its delivery obligations shall render the supplier liable to the imposition of penalties, pursuant to GCC Clause 22, unless an extension of time is agreed upon pursuant to GCC Clause 22.2 without the application of penalties.
- V. Upon any delay beyond the delivery period in the case of a supplies contract, the purchaser shall, without cancelling the contract, be entitled to purchase supplies of a similar Functionality and up to the same quantity in substitution of the goods not supplied in conformity with the contract and to return any goods delivered later at the supplier's expense and risk, or to cancel the contract and buy such goods as may be required to complete the contract and without prejudice to his other rights, be entitled to claim damages from the supplier.

Penalties

i. Subject to GCC Clause 25, if the supplier fails to deliver any or all of the goods or to perform the services within the period(s) specified in the contract, the purchaser shall, without prejudice to its other remedies under the contract, deduct from the contract price, as a penalty, a sum calculated on the delivered price of the delayed goods or unperformed services using the current prime interest rate calculated for each day of the delay until actual delivery or performance. The purchaser may also consider termination of the contract pursuant to GCC Clause 23.

FOR HAND DELIVERIES OF RESPONSES, PLEASE SUBMIT THE RFQ DOCUMENT TO NHLS RFQ BOX, NO:1 MODDERFONTEIN ROAD, SANDRINGHAM.

The Bidder accepts the above terms and conditions and	Accept	Do not accept
the General Conditions of Contract on NHLS website as		
per hyperlink GCC Document or visit NHLS website		
https://www.nhls.ac.za/supply-chain/, click on supply		
chain management tab then select General Conditions of		
Contract		



3. SCOPE OF WORKS

FORM OF QUOTATION SUPPLIER NAME:	

DESCRIPTION: RENOVATIONS TO IT MAIN BUILDING AT SANDRINGHAM

Item	Description	Unit	Quantity	Rate	Amount
	IT networking area Bill No.1				
1.1	Removal Safely remove the existing kitchenette including sink, basin and taps safely close the water supply and waste pipes using suitable stoppers Bill No 2	item	1		
2.1	Aluminium and glass Partition Supply and fit new 6mm thick 2200mm high x1600mm wideX1700mm frosted shutter proof glasses division for office cubical on 50mm aluminium frame all around and fitted to floor and against the wall L-Shape Supply and fit new 6mm thick 2200mm high x3200mm	no	3		
2.2	wideX1700mm frosted shutter proof glasses division for office cubical on 50mm aluminium frame all around and fitted to floor and against the wall T-shape	no	2		
3	Bill No 3 Bench	no	1		
3.1	Supply and install new 32 ^{mm} steel square tubing frames 800 ^{mm} wide and 870 ^{mm} high as per specification	m	3.6		
3.2	Supply and install 32mmx900mm wide long Formica post form top colour to match the furniture as per specification	m	3.6		
	Bill No 4				
4.1	Electrical works Supply and fit 2 Compartment type metal powder coated power skirting, allow for bends and end caps as per specification				
4.2	Surface mounted power skirting Supply and fit 15 amp standard power skirting plug points, wire from distribution board to prevent overloading including circuit breakers and wiring as per specification	m	10		
	Fitted to the power skirting	no	10		
	Micro Soft				
	Room IT/6				
	Bill No 1				
1	Aluminium and glass Partition				
1.1	Supply and fit new 6mm thick 2200mm high x1600mm wideX1700mm frosted shutter proof glasses division for office cubical on 50mm aluminium frame all around and fitted to floor and against the well I. Shore	no	6		
1.2	and fitted to floor and against the wall L-Shape Supply and fit new 6mm thick 2200mm high x3200mm wideX1700mm frosted shutter proof glasses division for office cubical on 50mm aluminium frame all around	no	1		



Bill No 2 Bench Supply and install new 32**** steel square tubing frames 800*** wide and 870*** high as per specification Supply and install 32**mmx800mm wide long Formica post form top colour to match the furniture as per specification Bill No 3 Tilling works Remove the existing tiles, Supply and fit 800***Mx8000**** x10**** ceramic "A grade" floor tiles using tile cement and light grey grouting Layed on the concrete floor Remove the existing skirting, Supply and fit 800**** x10*** x10	LA	BUKAI	ORY SERVICE	SANDRINGHAIVI CAIVIPUS			
2 Bench Supply and install new 32*** steel square tubing frames 800*** wide and 870*** high as per specification Supply and install 32mmx900mm wide long Formica post form top colour to match the furniture as per specification Bill No3 3 Tiling works Remove the existing tiles, Supply and fit 600****Remove the existing tiles, Supply and fit 1.1 decement and light grey grouting Layed on the concrete floor Remove the existing skirting, Supply and fit 600****Rom**x10****rearamic "A grade" floor tiles using tile cement and light grey grouting Fitted against the wall Room IT/8 Bill No1 1 Aluminium and glass Partition Supply and fit new 6mm thick 2200mm high x1600mm widex1700mm frosted shutter proof glasses division for office cubical on 50mm aluminium frame all around and fitted to floor and against the wall L-Shape Bill No2 2 Bench Supply and install new 32**** steel square tubing frames 800**** wide and 870**** high as per specification Supply and install 32mmx900mm wide long Formica post form top colour to match the furniture as per specification Bill No3 3 Tilling works IT/8 and office Remove the existing tiles, Supply and fit 600***x10****x10****mcseramic "A grade" floor tiles using tile cement and light grey grouting Layed on the concrete floor Remove the existing skirting, Supply and fit 600***x10***x10****mcseramic "A grade" floor tiles using tile cement and light grey grouting Fitted against the wall IT Support Bill No1 Removal Safely remove the existing dry wall partition and make good Safely remove the existing damaged door, replace			and fitted	to floor and against the wall T-shape			
Supply and install new 32 ^{mm} steel square tubing frames 800 ^{mm} wide and 870 ^{mm} high as per specification Supply and install 32mmx900mm wide long Formica 2.2 post form top colour to match the furniture as per specification Bill No3 3 Tilling works Remove the existing tiles, Supply and fit 600 ^{mm} x10 ^{mm} ceramic 'A grade' floor tiles using tile cement and light grey grouting Layed on the concrete floor Remove the existing skirting, Supply and fit 600 ^{mm} x10 ^{mm} ceramic 'A grade' floor tiles skirting using tile cement and light grey grouting Fitted against the wall Room IT/8 Bill No1 1 Aluminium and glass Partition Supply and fit ew 6mm thick 2200mm high x1600mm wideX1700mm frosted shutter proof glasses division for office cubical on 50mm aluminium frame all around and fitted to floor and against the wall L-Shape Bill No2 2 Bench Supply and install new 32 ^{mm} steel square tubing frames 800 ^{mm} wide and 870 ^{mm} high as per specification Supply and install 32mmx900mm wide long Formica post form top colour to match the furniture as per specification Bill No3 3 Tiling works IT/8 and office Remove the existing skirting, Supply and fit 600 ^{mm} x100 ^{mm} x10 ^{mm} ceramic 'A grade' floor tiles using tile cement and light grey grouting Layed on the concrete floor Remove the existing skirting, Supply and fit 600 ^{mm} x10 ^{mm} x10 ^{mm} ceramic 'A grade' floor tiles using tile cement and light grey grouting Fitted against the wall IT Support Bill No1 Removal Safely remove the existing dry wall partition and make good 2.5 Safely remove the existing damaged door, replace		2					
Supply and install 32mmx900mm wide long Formica psecification Bill No3 Tiling works Remove the existing tiles, Supply and fit 600°**x600°**x10°***ceramic 'A grade' floor tiles using tile cement and light grey grouting Layed on the concrete floor Remove the existing skirting, Supply and fit 600°**x10°**x10°***ceramic 'A grade' floor tiles skirting using tile cement and light grey grouting Fitted against the wall Room IT/8 Bill No1 Aluminium and glass Partition Supply and fit new 6mm thick 2200mm high x1600mm widex1700mm frosted shutter proof glasses division for office cubical on 50mm aluminium frame all around and fitted to floor and against the wall L-Shape Bill No2 Bench Supply and install new 32°** steel square tubing frames 800°** wide and 870°** high as per specification Supply and install and and 870°** high as per specification Supply and install 32mmx900mm wide long Formica post form top colour to match the furniture as per specification Bill No3 Tiling works IT/8 and office Remove the existing tiles, Supply and fit 600°**x600°**x10°**x10°*** or amic 'A grade' floor tiles using tile cement and light grey grouting Layed on the concrete floor Remove the existing skirting, Supply and fit 600°**x10°**x10°*** or cemanic 'A grade' floor tiles skirting using tile cement and light grey grouting Fitted against the wall IT Support Bill No1 Removal Safely remove the existing dry wall partition and make good 25 Safely remove the existing damaged door, replace		_	Supply at	300 ^{mm} wide and 870 ^{mm} high as per	m	4.6	
Tiling works Remove the existing tiles, Supply and fit 600""x600""x10"" ceramic "A grade" floor tiles using tile cement and light grey grouting Layed on the concrete floor Remove the existing skirting, Supply and fit 600""x100""x10"" ceramic "A grade" floor tiles skirting using tile cement and light grey grouting Fitted against the wall Room IT/8 Bill No1 1 Aluminium and glass Partition Supply and fit new 6mm thick 2200mm high x1600mm wide/x1700mm frosted shutter proof glasses division for for fore cubical on 50mm aluminium frame all around and fitted to floor and against the wall L-Shape Bill No2 Bench Supply and install new 32"" steel square tubing frames 800"" wide and 870" high as per specification Supply and install 32mmx900mm wide long Formica post form top colour to match the furniture as per specification Bill No3 3 Tilling works IT/8 and office Remove the existing tiles, Supply and fit 600""x600""x10"" ceramic "A grade" floor tiles using tile cement and light grey grouting Layed on the concrete floor Remove the existing skirting, Supply and fit 600""x600""x600""x10"" ceramic "A grade" floor tiles skirting using tile cement and light grey grouting Fitted against the wall IT Support Bill No1 Removal Safely remove the existing dry wall partition and make good 32 Safely remove the existing damaged door, replace	2	2.2	Supply an	nd install 32mmx900mm wide long Formica top colour to match the furniture as per	m	4.6	
Remove the existing tiles, Supply and fit 600mmx600mmx10mm ceramic "A grade" floor tiles using tile cement and light grey grouting Layed on the concrete floor Remove the existing skirting, Supply and fit 600mmx100mmx10mm ceramic "A grade" floor tiles skirting using tile cement and light grey grouting Fitted against the wall Room IT/8 Bill No1 1 Aluminium and glass Partition Supply and fit new 6mm thick 2200mm high x1600mm wideX1700mm frosted shutter proof glasses division for office cubical on 50mm aluminium frame all around and fitted to floor and against the wall L-Shape Bill No2 Bench Supply and install new 32mm steel square tubing frames 800mm wide and 870mm high as per specification Supply and install 32mmx900mm wide long Formica post form top colour to match the furniture as per specification Bill No3 Tiling works IT/8 and office Remove the existing tiles, Supply and fit 600mmx,600mmx10mm ceramic "A grade" floor tiles using tile cement and light grey grouting Fitted against the wall IT Support Bill No1 Removal Safely remove the existing dry wall partition and make good Safely remove the existing damaged door, replace			Bill No3				
SolommyReDommx10mm ceramic "A grade" floor tiles using tile cement and light grey grouting Layed on the concrete floor Remove the existing skirting. Supply and fit Solommy 100mmx10mm ceramic "A grade" floor tiles skirting using tile cement and light grey grouting Fitted against the wall Room IT/8 Bill No1 Aluminium and glass Partition Supply and fit new 6mm thick 2200mm high x1600mm widex1700mm frosted shutter proof glasses division for office cubical on 50mm aluminium frame all around and fitted to floor and against the wall L-Shape Bill No2 Bench Supply and install new 32mm steel square tubing frames 800mm wide and 870mm high as per specification Supply and install 32mmx900mm wide long Formica post form top colour to match the furniture as per specification Bill No3 Tilling works IT/8 and office Remove the existing tiles, Supply and fit 600mmx600mmx10mm ceramic "A grade" floor tiles using tile cement and light grey grouting Layed on the concrete floor Remove the existing skirting, Supply and fit 800mmx10mm ceramic "A grade" floor tiles skirting using tile cement and light grey grouting Fitted against the wall T Support Bill No1 Removal Safely remove the existing dry wall partition and make good Safely remove the existing damaged door, replace Tolomator Tol		3	Tiling wo	orks			
Remove the existing skirting, Supply and fit 6000mm/x100mm/x100mm caramic "A grade" floor tiles skirting using title cement and light grey grouting Fitted against the wall Room IT/8 Bill No1 1 Aluminium and glass Partition Supply and fit new 6mm thick 2200mm high x1600mm wideX1700mm frosted shutter proof glasses division for office cubical on 50mm aluminium frame all around and fitted to floor and against the wall L-Shape Bill No2 Bench Supply and install new 32mm steel square tubing frames 800mm wide and 870mm high as per specification Supply and install 32mmx900mm wide long Formica post form top colour to match the furniture as per specification Bill No3 Tilling works IT/8 and office Remove the existing tiles, Supply and fit 600mm/x600mm/x10mm ceramic "A grade" floor tiles using tile cement and light grey grouting Layed on the concrete floor Remove the existing skirting, Supply and fit 600mm/x100mm/x10mm ceramic "A grade" floor tiles skirting using tile cement and light grey grouting Fitted against the wall TSupport Bill No1 Removal Safely remove the existing dry wall partition and make good 3 Safely remove the existing damaged door, replace	3	3.1	600 ^{mm} x60	00 ^{mm} x10 ^{mm} ceramic "A grade" floor tiles using			
Room IT/8 Bill No1 Aluminium and glass Partition Supply and fit new 6mm thick 2200mm high x1600mm wideX1700mm frosted shutter proof glasses division for office cubical on 50mm aluminium frame all around and fitted to floor and against the wall L-Shape Bill No2 Bench Supply and install new 32mm steel square tubing frames 800mm wide and 870mm high as per specification Supply and install 32mmx900mm wide long Formica post form top colour to match the furniture as per specification Bill No3 Tiling works IT/8 and office Remove the existing tiles, Supply and fit 600mmx600mmx10mm ceramic "A grade" floor tiles using tile cement and light grey grouting Layed on the concrete floor Removet he existing skirting, Supply and fit 600mmx100mmx10mm ceramic "A grade" floor tiles skirting using tile cement and light grey grouting Fitted against the wall IT Support Bill No1 Removal Safely remove the existing dry wall partition and make good Safely remove the existing damaged door, replace	3	3.2	Remove 600mmx10	the existing skirting, Supply and fit 00 ^{mm} x10 ^{mm} ceramic "A grade" floor tiles	m ²	50	
Bill No1 Aluminium and glass Partition Supply and fit new 6mm thick 2200mm high x1600mm wideX1700mm frosted shutter proof glasses division for office cubical on 50mm aluminium frame all around and fitted to floor and against the wall L-Shape Bill No2 Bench Supply and install new 32mm steel square tubing frames 800mm wide and 870mm high as per specification Supply and install 32mmx900mm wide long Formica post form top colour to match the furniture as per specification Bill No3 Tiling works IT/8 and office Remove the existing tiles, Supply and fit 600mmx600mmx10mm ceramic "A grade" floor tiles using tile cement and light grey grouting Layed on the concrete floor Remove the existing skirting, Supply and fit 600mmx100mmx10mm ceramic "A grade" floor tiles skirting using tile cement and light grey grouting Fitted against the wall TSupport Bill No1 Removal Safely remove the existing dry wall partition and make good Safely remove the existing damaged door, replace					m	31	
Aluminium and glass Partition Supply and fit new 6mm thick 2200mm high x1600mm wideX1700mm frosted shutter proof glasses division for office cubical on 50mm aluminium frame all around and fitted to floor and against the wall L-Shape Bill No2 Bench Supply and install new 32mm steel square tubing frames 800mm wide and 870mm high as per specification Supply and install 32mmx900mm wide long Formica post form top colour to match the furniture as per specification Bill No3 Tiling works IT/8 and office Remove the existing tiles, Supply and fit 600mmx600mmx10mm ceramic "A grade" floor tiles using tile cement and light grey grouting Layed on the concrete floor Remove the existing skirting, Supply and fit 600mx100mmx100mm ceramic "A grade" floor tiles skirting using tile cement and light grey grouting Fitted against the wall IT Support Bill No1 Removal Safely remove the existing dry wall partition and make good Safely remove the existing damaged door, replace			Room IT	/8			
Supply and fit new 6mm thick 2200mm high x1600mm wideX1700mm frosted shutter proof glasses division for office cubical on 50mm aluminium frame all around and fitted to floor and against the wall L-Shape Bill No2 2 Bench Supply and install new 32 ^{mm} steel square tubing frames 800 ^{mm} wide and 870 ^{mm} high as per specification Supply and install 32mmx900mm wide long Formica post form top colour to match the furniture as per specification Bill No3 3 Tiling works IT/8 and office Remove the existing tiles, Supply and fit 600 ^{mm} x600 ^{mm} x10 ^{mm} ceramic "A grade" floor tiles using tile cement and light grey grouting Layed on the concrete floor Remove the existing skirting, Supply and fit 600 ^{mm} x10 ^{mm} ceramic "A grade" floor tiles skirting using tile cement and light grey grouting Fitted against the wall IT Support Bill No1 Removal Safely remove the existing dry wall partition and make good Safely remove the existing damaged door, replace			Bill No1				
1.1 wideX1700mm frosted shutter proof glasses division for office cubical on 50mm aluminium frame all around and fitted to floor and against the wall L-Shape Bill No2 2 Bench Supply and install new 32 ^{mm} steel square tubing frames 800 ^{mm} wide and 870 ^{mm} high as per specification Supply and install 32mmx900mm wide long Formica post form top colour to match the furniture as per specification Bill No3 3 Tilling works IT/8 and office Remove the existing tiles, Supply and fit 600 ^{mm} x600 ^{mm} x10 ^{mm} ceramic "A grade" floor tiles using tile cement and light grey grouting Layed on the concrete floor Remove the existing skirting, Supply and fit 600 ^{mm} x100 ^{mm} x10 ^{mm} ceramic "A grade" floor tiles skirting using tile cement and light grey grouting Fitted against the wall IT Support Bill No1 Removal Safely remove the existing dry wall partition and make good Safely remove the existing damaged door, replace		1	Aluminiu	ım and glass Partition			
2.1 Supply and install new 32 ^{mm} steel square tubing frames 800 ^{mm} wide and 870 ^{mm} high as per specification Supply and install 32mmx900mm wide long Formica post form top colour to match the furniture as per specification Bill No3 3 Tiling works IT/8 and office Remove the existing tiles, Supply and fit 600 ^{mm} x10 ^{mm} ceramic "A grade" floor tiles using tile cement and light grey grouting Layed on the concrete floor Remove the existing skirting, Supply and fit 600 ^{mm} x10 ^{mm} ceramic "A grade" floor tiles skirting using tile cement and light grey grouting Fitted against the wall IT Support Bill No1 Removal Safely remove the existing dry wall partition and make good Safely remove the existing damaged door, replace	1	.1	wideX170 for office	00mm frosted shutter proof glasses division cubical on 50mm aluminium frame all around	no	4	
Supply and install new 32 ^{mm} steel square tubing frames 800 ^{mm} wide and 870 ^{mm} high as per specification Supply and install 32mmx900mm wide long Formica post form top colour to match the furniture as per specification Bill No3 Tiling works IT/8 and office Remove the existing tiles, Supply and fit 600 ^{mm} x10 ^{mm} ceramic "A grade" floor tiles using tile cement and light grey grouting Layed on the concrete floor Remove the existing skirting, Supply and fit 600 ^{mm} x10 ^{mm} ceramic "A grade" floor tiles skirting using tile cement and light grey grouting Fitted against the wall m 44 IT Support Bill No1 Removal Safely remove the existing dry wall partition and make good Safely remove the existing damaged door, replace			Bill No2				
frames 800mm wide and 870mm high as per specification Supply and install 32mmx900mm wide long Formica post form top colour to match the furniture as per specification Bill No3 Tiling works IT/8 and office Remove the existing tiles, Supply and fit 600mmx600mmx10mm ceramic "A grade" floor tiles using tile cement and light grey grouting Layed on the concrete floor Remove the existing skirting, Supply and fit 600mmx100mmx10mm ceramic "A grade" floor tiles skirting using tile cement and light grey grouting Fitted against the wall IT Support Bill No1 Removal Safely remove the existing dry wall partition and make good Safely remove the existing damaged door, replace		2	Bench				
Supply and install 32mmx900mm wide long Formica post form top colour to match the furniture as per specification Bill No3 3 Tiling works IT/8 and office Remove the existing tiles, Supply and fit 600mmx600mmx10mm ceramic "A grade" floor tiles using tile cement and light grey grouting Layed on the concrete floor Remove the existing skirting, Supply and fit 600mmx100mmx100mm ceramic "A grade" floor tiles skirting using tile cement and light grey grouting Fitted against the wall IT Support Bill No1 Removal Safely remove the existing dry wall partition and make good Safely remove the existing damaged door, replace	2	2.1	frames 8	00 ^{mm} wide and 870 ^{mm} high as per	m	3	
Tiling works IT/8 and office Remove the existing tiles, Supply and fit 600mmx600mmx10mm ceramic "A grade" floor tiles using tile cement and light grey grouting Layed on the concrete floor Remove the existing skirting, Supply and fit 600mmx100mmx10mm ceramic "A grade" floor tiles skirting using tile cement and light grey grouting Fitted against the wall IT Support Bill No1 Removal Safely remove the existing dry wall partition and make good Safely remove the existing damaged door, replace	2	2.2	Supply a	nd install 32mmx900mm wide long Formica top colour to match the furniture as per	m	3	
Remove the existing tiles, Supply and fit 600mmx600mmx10mm ceramic "A grade" floor tiles using tile cement and light grey grouting Layed on the concrete floor Remove the existing skirting, Supply and fit 600mmx100mmx10mm ceramic "A grade" floor tiles skirting using tile cement and light grey grouting Fitted against the wall IT Support Bill No1 Removal Safely remove the existing dry wall partition and make good Safely remove the existing damaged door, replace			Bill No3				
Remove the existing tiles, Supply and fit 600mmx600mmx10mm ceramic "A grade" floor tiles using tile cement and light grey grouting Layed on the concrete floor Remove the existing skirting, Supply and fit 600mmx100mmx10mm ceramic "A grade" floor tiles skirting using tile cement and light grey grouting Fitted against the wall IT Support Bill No1 Removal Safely remove the existing dry wall partition and make good Safely remove the existing damaged door, replace		3	Tiling wo	orks IT/8 and office			
Layed on the concrete floor Remove the existing skirting, Supply and fit 600mmx100mmx10mm ceramic "A grade" floor tiles skirting using tile cement and light grey grouting Fitted against the wall IT Support Bill No1 Removal Safely remove the existing dry wall partition and make good Safely remove the existing damaged door, replace Bill No1 1 Removal Safely remove the existing damaged door, replace Do 1	3	3.1	Remove 600mmx60	the existing tiles, Supply and fit 00 ^{mm} x10 ^{mm} ceramic "A grade" floor tiles using			
3.2 600mmx100mmx10mm ceramic "A grade" floor tiles skirting using tile cement and light grey grouting Fitted against the wall m 44 IT Support Bill No1 1 Removal Safely remove the existing dry wall partition and make good Safely remove the existing damaged door, replace no 1					m²	64	
IT Support Bill No1 Removal Safely remove the existing dry wall partition and make good Safely remove the existing damaged door, replace	3	3.2	600 ^{mm} x10	00 ^{mm} x10 ^{mm} ceramic "A grade" floor tiles			
Bill No1 1 Removal 1.1 Safely remove the existing dry wall partition and make good Safely remove the existing damaged door, replace			Fitted aga	ainst the wall	m	44	
1 Removal 1.1 Safely remove the existing dry wall partition and make good Safely remove the existing damaged door, replace			IT Suppo	<u>ort</u>			
1.1 Safely remove the existing dry wall partition and make good Safely remove the existing damaged door, replace			_				
good 11 good 12 good 12 good 13 good 14 good 15 good 1		1					
Safely remove the existing damaged door, replace	1	.1		move the existing dry wall partition and make	m	4	
	1	.2	Safely re		no	1	



-	Dill N. O.		Ì	1	1
•	Bill No2				
2	Aluminium and glass Partition Supply and fit new 6mm thick 2200mm high x1600mm wideX1700mm frosted shutter proof glasses division for office cubical on 50mm aluminium frame all around and fitted to floor and against the wall L-Shape Bill No3	no	9		
3	Aluminium and glass Partition IT/17				
3.1	Supply and fit new 6mm thick 2200mm high x1600mm wideX1700mm frosted shutter proof glasses division for office cubical on 50mm aluminium frame all around and fitted to floor and against the wall L-Shape	no	2		
4	Bill No4				
4.1	Bench Supply and install new 32 ^{mm} steel square tubing frames 800 ^{mm} wide and 870 ^{mm} high as per specification Supply and install 32mmx900mm wide long Formica	m	4		
4.2	post form top colour to match the furniture as per specification	m	4		
	IT Service Desk				
	Bill No1				
1	Removal				
1.1	Safely remove the existing floor power skirting, complete with plugs and refit elsewhere	item	1		
	Aluminium and glass Partition				
1.2	Supply and fit new 6mm thick 2200mm high x1600mm wideX1500mm frosted shutter proof glasses division for office cubical on 50mm aluminium frame all around and fitted to floor and against the wall L-Shape Prepare and frost the existing aluminium sliding door	no m²	12 6		
	with mist frost				
	Communal works				
1	Bill No.1 Paintwork Previously painted plastered surfaces Prepare and paint walls with Plascon Velvaglo or similar white 2 coats as per specification				
1.2	On Internal walls Previously painted surfaces Prepare and paint ceiling with Plascon polvin or similar white 2 coats as per specification	m²	2270		
	On ceiling Previously painted windows	m²	1375		
1.3	Prepare and paint 1250mx1450m steel window 2 white enamel coats as per specification Prepare and paint 1000mx1450m steel window 2 white	no	36		
1.4	enamel coats as per specification	no	6		
1.5	Prepare and paint 1600mx1450m steel window 2 white enamel coats as per specification	no	4		
1.6 1.7	Previously painted doors Prepare and paint wooden doors and steel frames 2 white enamel coats as per specification Previously Varnished doors	no	22		



1.8	Prepare and varnish wooden doors and frames 2 white enamel coats as per specification	no	7	
2	Bill No.2 Window Blinds			
2.1	Removal of the existing window blinds, Supply and fit 1260 ^{mm} wide x 1460 ^{mm} high material vertical window blinds to match the existing and colour to be confirmed on appointment Installed to the window opening	no	36	
2.2	Removal of the existing window blinds, Supply and fit 1000 ^{mm} wide x 1460 ^{mm} high material vertical window blinds to match the existing and colour to be confirmed on appointment Installed to the window opening	no	6	
2.3	Removal of the existing window blinds, Supply and fit 1600 ^{mm} wide x 1450 ^{mm} high material vertical window blinds to match the existing and colour to be confirmed on appointment			
1	Installed to the window opening Kitchen area Bill no.1	no	4	
1.1	Remove the existing kitchen cupboards, sink and cart away			
1.2	Supply and fit new melamine under bench cupboards, 900mm wide x750mm with doors, hinges and handles colour to be discussed on appointment	No	3	
1.3	Supply and fit new melamine under bench cupboards, 450mm wide x698mm with drawers and handles colour to be discussed on appointment	No	2	
1.4	Supply and fit new melamine wall cupboards, 500mm wide x 698mm with doors, hinges and handles colour to be discussed on appointment	No	3	
1.5	Supply and fit new melamine microwave holder cupboard to accommodate 42L microwave	No	2	
1.6	Supply and fit 16 mmx600mm wide kitchen granite top to the kitchen area, allow for tiling between top and cupboards	m	4	
1.7	Supply and fit 1200mm x 500mm drop-in stainless steel double bowl sink, connect to water supply and drainage, supply and fit cobra swivel sink mixer, with a splash back tiles above the top	No	1	
1.8	Supply and install 10L Hydro boil, install above sink, includes all connection to water supply and wired to the isolator, and water supply.	No	1	
1.9	Supply and install 50L geyser, complete with all fittings, fitted outside and connect to water supply, and electrical wired to the isolator. To CDW area	no	1	
1.10	Supply and fit (4x2)30 Amp D/P isolator, fed from distribution board with curve 1- 25amp single pole	no	2	



	ainevit has alone Allery for a strike w	, ,	
	circuit breakers. Allow for cabling		
1.1	Passage and kitchen Tiling works Bill No 1 Removal of the existing floor tiles and cart away, Supply and lay 600mm x 600mm x 10mm "A" grade porcelain non slippery floor tiles with light gray grouting as per specifications	m²	211
1.2	Supply and fit 200mm high porcelain tile skirting complete with strip as per specification to all areas	m	280
1 1.1	Board room Bill No 1 Remove the existing carpets and cart away, Supply and fit 8mm commercial laminated wooden flooring with under cushion, colour to be confirmed upon appointment to office complete with all fittings as per specification colour to be confirmed upon appointment to finance board room	m²	30
2	Supply and fit laminated wooden skirting 75mm high and door strip	m	22
	Toilets facilities		
1 .1	Bill no.1 Gents toilets facilities Remove the existing tiles, Supply and fit 600mmx600mmx10mm ceramic "A grade" floor tiles using tile cement and light grey grouting to gents' toilet area	m2	28
2	Remove the existing wall tiles and cart away, prepare wall to rough finish, supply and fit 200mmx600mmx10mm ceramic "A grade" wall tiles to door height using tile cement and white grouting including boarder tile to gents' toilet area	m2	88
}	Remove the existing basin, Supply and fit new ceramic hand wash basins including swivel mixer taps, connect to hot and Coldwater supply and drainage, basins must be halfway sunken in to Stone type top to gents	no	2
4	Supply and fit 32mmx600mm Stone type Mable top(granite) on support stand/heavy duty wall mounted steel brackets to gents toilet area	m	3
5	Supply and fit 32mmx300mm side cover Stone type Mable(granite) to gents toilet area	m	4
6	Remove the existing mirrors, Supply and fit new 1200mmx800mm mirror to the wall	no	1
7	Remove the existing toilets, old flushing cistern, and cart away, Supply and fit new Ceramic toilet including side flush cistern, toilet paper holder, wooden toilet seat cover, including re-piping for new connect to existing water and drain to gents toilet area	no	3



1.8	Supply and fit new porcelain PREMIUM Duravit Fizz Urinals Wall Hung with flush masters, bottle trap to each urinal, connect to existing water and drainage supply to male toilet to gents toilet area complete with 1000mmx600mm dividers	no	4	
1.9	Prepare and paint wall with 1 coat of damp seal, 1 coat of plaster primer and plascon Velvaglo or similar white 2 coats as per specifications	m2	44	
1.10	Prepare and paint ceiling with 1 coat of damp seal, 1 coat of plaster primer Prepare and paint ceiling with plascon polvin or similar white 2 coats as per specifications	m2	28	
1.11	Prepare and paint steel doors and frame two coats to match the existing colour	no	4	
1.12	Prepare and paint steel window frame two coats to match the existing colour	no	4	
1.13	Supply and fit new 35kw industrial window extractor fan to the toilet cubical connected to the light switch to gents toilet area	no	1	
1.14	Supply and install to waterproof light fittings with as per specification to the toilet area	no	3	
2	Bill no.2			
2	Ladies Toilets facilities			
2.1	Remove the existing tiles, Supply and fit 600mmx600mmx10mm ceramic "A grade" floor tiles using tile cement and light grey grouting to ladies toilet area	m2	34	
2.2	Remove the existing wall tiles and cart away, prepare wall to rough finish, supply and fit 200mmx600mmx10mm ceramic "A grade" wall tiles to door height using tile cement and white grouting including boarder tile to ladies toilet area	m2	98	
2.3	Remove the existing basin, Supply and fit new ceramic	no	3	



	hand wash basins including swivel mixer taps, connect to hot and cold water supply and drainage, basins must be half way sunken in to Stone type top to ladies			
2.4	Supply and fit 16mmx600mm Stone type Mable top(granite) on support stand/heavy duty wall mounted steel brackets to ladies toilet area	m	4	
2.5	Supply and fit 32mmx300mm side cover Stone type Mable(granite) to ladies toilet area	m	5	
2.6	Remove the existing mirrors, Supply and fit new 1200mmx800mm mirror to the wall	no	2	
2.7	Remove the existing toilets, old flushing cistern, and cart away, Supply and fit new Ceramic toilet including side flush cistern, toilet paper holder, toilet seat, including re-piping for new connect to existing water and drain to ladies toilet area	no	5	
2.8	Prepare and paint wall with 1 coat of damp seal, 1 coat of plaster primer and plascon Velvaglo or similar white 2 coats as per specifications	m2	48	
2.9	Prepare and paint ceiling with 1 coat of damp seal, 1 coat of plaster primer Prepare and paint ceiling with plascon polvin or similar white 2 coats as per specifications	m2	34	
2.10	Prepare and paint steel doors and frame two coats to match the existing colour	no	6	
2.11	Prepare and paint steel window frame two coats to match the existing colour	no	3	
2.12	Supply and fit new 35kw industrial window extractor fan to the toilet cubical connected to the light switch to ladies toilet area	no	1	
2.15	Supply and install to waterproof light fittings with as per specification to the toilet area	no	3	
	Compliance Supply Electrical certificate of compliance on completion (COC) Supply plumbing certificate of compliance on completion (COC)	item item	1 1	
	Contingency Provide the sum of R 30 000.00 (Thirty Rand) for contingencies and design contingency, to be used as instructed by the project manager in terms of clause 17 of the Principal Building Agreement. shall be expended at the sole discretion of the Client, and can be deducted in whole or in part if not required	item	1	R30 000.00
	Estimated time to complete project		0115	
			SUB	

SUB TOTAL		
VAT		
GRAND TOT	AL	



NB

The following are deemed as mandatory and regulatory requirements and failure to comply will result in the invalidation of a proposal. No unanswered questions will be allowed. If a response to a question has been indicated as comply but no proof is submitted, it shall be regarded as mandatory non-performance/non-compliance, and the bid WILL be disqualified.

Bidders are required to indicate compliance by marking with an "X" adjacent to each requirement in the column. Where bidders mark both the "comply" and "not comply" column it will be regarded as non-compliant, and the bid will be disqualified

Mandatory requirements					
No	Legislative	Comply	Do not comply		
1	CIDB grading (2GB or higher)				
2	Electrical Wire man's license				
3	Letter of good standing COIDA				
4	Industry regulator registration <i>Plumbing Industry Registration Board</i> (PIRB)				
5	Three (3) copies of contactable reference or completion certificate, on client's letterhead, with contact details				
6	5-year company Experience in related field, attach either CK, registration documents, old references which are older as a proof				
7	Provide copy of CV and Certificate of 5 years experienced project manager/supervisor to manage the project				
8	Electrical trade Test				
9	Plumbing Trade test				

Important Note:

- Always read specification in conjunction with Bill of Quantities and Plan (if plan is applicable and supplied).
- All Quantities measured are indicative and will be re-measured on completion.
- Specific products to be used, to be confirmed in Bill of Quantities.
- All materials and products to be used, to be ISO 9001 accredited.
- Due to the nature of our labs (operation 24 hours) the contractor will be expected to work after hours and over the weekend.
- Variation orders can only be approved in writing (via the email) by the NHLS Project Manager
- No additional or extra work done will be paid for unless the project manager has issued a variation order
- NHLS Project Manager will conduct all inspections.
- The contractor should be required to move the equipment (furniture, benches, etc.) and put them back requested.
- Only material installed will be paid and not for any wastage (no material on site will be paid).
- NHLS delegates can also and contact the client or visit the work done as referred on the completion certificate.



- Contractor will be requested to provide comprehensive safety file; work will be only allowed to commence after the file has been formally approve by NHLS.
- A contractor is expected to sign a 37(2) Agreement (Form FMI 0008) before commencing with the project.
- No progress payment will be made less than R200,000.00.

References:

- NHLS delegates can also and contact the client or visit the work done as referred on the reference or completion certificate.
- All the contractors will be requested to provides NHLS with the following signed of stamped references
 or completion certificates of similar work done on company or departments letter head, not more than
 five years (5) old as per the table below; Unless specified on the Project Technical evaluations

If QUOTE VALUE	REQUIRED REFERENCE OR COMPLETION CERTIFICATES	CONTRACT VALUE OF PROJECT PREVIOUSLY DONE	
R200,000.00 and above	Three(3) copies of contactable reference or completion certificate, , on client's letterhead, with contact details, valid email address, office telephone, cell phone and business address	· ·	

GUARANTEE, MAINTENANCE, PENALTY AND RETENTION PERIOD

The Guarantee and Maintenance period shall be for 12 months commencing on the date of Practical completion and acceptance of the Installation. During the Guarantee period the Contractor shall repair all defects in the Installation which may arise as a result of inferior quality materials or faulty workmanship. 5% retention of the contract price will be held back for a period of 3 months after date of Practical completion and acceptance of the installation

The fact that the Installation will be used and occupied by the Employer during the guarantee period shall in no way exempt the Contractor from his responsibility under this clause

Should a non-urgent fault occur during the guarantee period the Contractor will be advised and he shall repair the fault in good time

Should a fault occur during the guarantee period, that is in the opinion of the Project Manager of an urgent nature, then the Contractor will be advised and shall proceed immediately to rectify the fault

Should a fault occur during the guarantee period, that is in the opinion of the Project Manager of an urgent nature, and the Contractor is not available, the Employer shall reserve the right to obtain the services of any available Contractor to repair the fault. The cost of such repair work shall be borne by the Contractor in accordance with the escalated rates. In such a case the faulty equipment shall be kept for scrutiny by the Contractor. If this occurs during the retention period and retention money is still due to the Contractor, such claim from the Alternative Contractor, will be deducted from the Retention fund

Should the frequency and breakdown/s, in the opinion of the Project Manager, become so regular as to constitute and unacceptable state of affairs or should the installation or portions thereof prove to be unacceptable, the Contractor shall upon receipt of a written instruction from the Project Manager, replace portions/components or even the entire installation if need be, at his own cost as prescribed by the Project Manager

Where the practical completion is not reached by the date stated in the Tender/ RFQ document or by the revised date granted by the Project Manager, the Contractor shall be liable to a Penalty determent by the Project Manager, which is in this instance .1% (point 1 percent) of the Tender/ RFQ Total value, Per Day



PRELIMINARIES

Tenderer's attention is drawn to the fact that the Hospital and Laboratory will be fully operational during the building process. The work will have to be carried out in phases and at times that must be liaised and agreed to with the Business Manager and Hospital Management. This might result in certain work being carried out at certain times only, even after hours of weekends. Also note that sensitive electronic equipment are in use and no work that cause a vibration can be carried out when these equipment are in operation. Operating theaters in the vicinity of the building work will also be in use during the building program and the Contractor must liaise closely with the Hospital Management and obtain their written consent and permission, before removing and/or servicing equipment/structures, that might interfere with the running of the theaters or any other service/s. The use of certain lifts for moving of material will also have to be agreed to with the Hospital Management. The tenderer must allow for this in his prices since no additional claim will be entertained in this regard

TENDERS SHOULD BE BASED ON THE FOLLOWING SPECIFICATIONS

SITE APPLICATION

Repair to cracks

Repairs to cracks 0.2mm to 2mm

Rake out with a scraped blade.

Remove dust and debris.

Fill with pure acrylic, paintable, flexible crack filler.

Cracks over 2mm

Open out with a carborundum disk into a V shape minimum 3^{mm} wide.

Remove dust and debris.

Wet the crack and fill with damp 1:4 cement/sand mortar properly compacted into the cracks.

Repairs to Mortar Joints

Scrape out unsound mortar

Point solidly with 1:3 cement/sand mortar properly compacted into the joints

Repairs to Painted Wall Surface Coating

Remove loose paint with a sharp paint a scraper or hand-held pneumatic engraving tools fitted with flat chisel heads

Feather edges of tightly bonded paint with a rough to medium grit paper

Built up paint covering flush with general surface area

Preparation - Generally

Materials used in preparation to be types recommended by their manufacturers and the coating manufacturer for the situation and surfaces being prepared.

Apply in strict accordance with the manufacturers specification.

Apply oil based stoppers/fillers after priming. Apply water based stoppers/fillers before priming unless recommended otherwise by manufacturer. Patch prime water based stoppers/fillers when applied after priming.

Ensure that doors and opening windows, etc, are "eased" as necessary before coating. Prime any resulting bare areas.

Plastered surfaces and fibre cement boards to be washed down and allowed to dry completely.

Unfinished concrete surfaces clean with 1:4 solution of spirit of salts: water.

All floors where painting is to be carried out to be swept clean, walls dusted down and unpainted surfaces protected.



Efflorescence

Remove surface salts and other loose material with a stiff brush or coarse dry cloth.

Leave for 48 hours and repeat process if further efflorescence occurs.

Sand glossy surfaces to provide a key for finish.

Ironmongery

Remove from surfaces to be coated and re-fit on completion. Do not remove hinges unless instructed to do so

Previously Uncoated Timber

Ensure that large and loose knots are removed and made good with sound timber of the same species. Sand down flush

Ensure that surfaces are clean and remove all oil, grease and excessive natural oils with suitable solvents Sand to a smooth, even finish with arrises rounded or eased

Remove resinous bleeding by heat, apply two coats of knotting to resinous areas and all knots and allow to dry

Ensure that head of fasteners is countersunk sufficiently to hold stopping/filling. Fill nail and screw holes, joints, cracks, holes, depressions, open or coarse grain with matching coloured stopper/filler worked well in and finished off flush with surface. Sand smooth and remove dust

Sand down to remove all plaster stains pencil marks and other blemishes from timber that is to be oiled or stained

Previously Coated Timber

Strip any existing cracked or flaking varnish back to fresh wood

Sand down any discoloured areas to fresh wood

Ensure that surfaces are clean and remove all oil, grease and excessive natural oils with suitable solvents Sound varnish to be sanded with 360 grit paper

Uncoated Masonry/Render

Remove dirt, surface deposits, loose and faking material with a stiff brush

Fill holes and cracks flush with surface, rub down

Unpainted Plaster

Remove dirt and surface deposits with a stiff brush

Rub down to remove nibs, trowel marks and plaster splashes

Lightly rub over trowelled glossy plaster with worn abrasive paper

Fill depressions, holes and cracks and lightly rub down flush with surface

Steel Generally

Remove all loose and faking paint

Feather edges of tightly bonding paint

Rusted Areas

Clean disk sand and wire brush to remove rust

Clean bare steel patches with a solvent wash

Rust convertor only to be used on small areas where hand cleaning is ineffective

Apply with a stiff brush ensuring penetration into any pitting

Inspect after two hours and recoat areas showing unconverted red rust

Prime surfaces as soon as possible after cleaning, and in any case within four hours

Coating

Painting Generally

Operatives must be appropriately skilled and experienced in the use of specified materials and methods of



application

Do not use materials that show any bittiness when applied. Do not thin or intermix unless specified or recommended otherwise. If materials are found to have been thinned without authorization, the Project Manager may require an additional application of additional coats

Any priming as soon as possible on the same day as preparation is completed, ensure that coats are of adequate thickness and suit surface porosity

Adjacent coats of the same material must be of a different tint to ensure that each coat provides complete coverage

Apply coatings to clean, dust free, suitable dry surfaces in dry atmospheric conditions and after any previous coats have hardened. Lightly abrade between coats as necessary

Apply coatings evenly to give a smooth finish of uniform colour, free from brush marks, nibs, sags, runs and other defects. Cut in neatly and cleanly. Do not splash or mark adjacent surfaces

Keep all surfaces clean and free from dust during coating and drying. Adequately protect completed work from damage

Painted Joinery/woodwork

Before priming preservative treated timber, any cut surfaces to be retreated and all end grain to be liberally coated allowing it to soak in before recoating it

Pre-primed woodwork to be lightly rubbed down and patch prime to match existing

Prime: One coat primer, two coats to end grain which will be painted

Finish: Two coats Alkyd gloss, sanded down between coats

Staining

Check with stain manufacturer if primer is required for the species of timber and type of previously applied treatment.

Apply stain in flowing coats. Redistribute excess material by brushing before stain has set. Allow not less than 12 hours between coats

Varnishing

Thin first coat with white spirits according to manufacturer's recommendations

Brush well in avoiding aeration and lay off

Apply further coats of varnish, rubbing down lightly between coats along the grain

Bead Glazing to Coated Timber

Before Glazing: Apply first two coats to rebates and beads

Concealed Joinery Surfaces

Inaccessible parts of joinery constructions are to be primed and/or coated before assembly

Where one or more additional coats are specified to be applied, they must be applied to all surfaces, including those that will be concealed when incorporated into the building

Wooden Doors

Varnish or paint bottom edges before hanging

Completion

Ensure that opening lights/windows/hinges and other moving parts move freely. Remove all masking tape and temporary coverings afterwards

Protection

Adequately protect all surfaces that are not to be coated

Protect all surfaces from dust and damp

Where doors are delivered to site in a finished condition, provide all necessary protection to the doors when applying coatings to the frames



Plumbing

Only registered Plumbers to be employed for any plumbing & drainage work

Allow for ± 2m2 tiling above each basin and sink

Allow for A Grade Glazed white tiles, 152 x 152mm, 5 - 6.5mm thick

Sinks size: 1350mm x 535mm unless otherwise specified in bill of quantities

Sink mixer for tea room sink to be 15mm chrome plated brass cobra mixer type tap

All basins to be white glazed, each fitted with an approved 32mm chrome plated brass waste fitting with screwed outlet, and a 15mm chrome plated brass elbow action tap connected to water supply

All sinks to be standalone stainless steel sink, work area, splash back on Pre-manufactured 40×32^{mm} stainless steel square tubing frames, 4 legs on adjustable pedestals. Exposed surfaces having a smooth finish, each fitted with an approved 32mm chrome plated brass waste fitting with screwed outlet, and a 15mm chrome plated brass Hospital goose neck tap

Stainless steel grade 316 or Type 304 to be used for stainless steel sinks

All material to be SABS approved

Make sure all existing water pipes and waste is in good working condition

All existing basins and sinks to be washed and cleaned

On each water supply line, a ball valve need to be installed as close as possible to outlet, this includes basins, sinks, toilets

Each tap to be visibly marked with "H" or a "Red" mark for Hot water and "C" or a "Blue" mark for Cold water **Geysers**: Install makes such as Franky, Kwikhot or similar. Install on a drip tray with drain pipe to outside, pressure valve, safety valve, shut off valve, overflow pipe. Isolator to be installed at least 1m from Geyser, hot and cold water supply lines to be bonded and earthed. Isolator to be wired to DB with dedicated double pole circuit breaker.

Toilets: these shall be deemed to include the following: WC Pan, flush valve or 11 litre cistern with flushing apparatus, float valve and flush pipe and all finishings to pipes and cistern. To be the wash down type, approximately 400 high manufactured of white glazed fireclay or vitreous china, each provided with the compatible "P" or "S" –Traps, jointed to Pan. Pans and traps to be set on and encased in Class B concrete not less than 100mm thick at any point or position

Wall mounted bowl urinals: to be of white glazed fireclay or vitreous china, approximately 700 x 380mm in size with back flush entry, secured to wall with at least 2 concealed hanger brackets. Each urinal to be fitted with 38mm chrome plated domical grating, urinal complete with push button assembly, exposed type flush valve with ball-o-stop and wall flange. • Chrome plate finish. • Additional toilet piston screw • Non-hold open feature, spreader and all other necessary chrome plated brass fittings as well as a chrome plated brass bottle trap

Hydroboil installations: Install always above sink (see bill of quantities for size)

Emergency shower: complete body shower with eye station. Flow rate to be 60 liter per minute. At floor level, 700mm below shower head, the radius of water reaching the floor should be 200mm. At the eye station flow rate should be 6 liter per minute at a flow pressure safe enough not to injure the User. This unit to be 1 meter from floor level. Make use of emergency showers as supplied by Broen, Bull Maurice Trading or similar

Electrical

Only registered Electricians to be employed for any electrical work

Wires to be used for sockets outlets; 2.5mm² PVC

Colour for 2- compartment steel/PVC power skirting unless differently specified in bill of quantities (colour to be confirmed)

Normal plugs to be white and dedicated plugs to be red

Electrician to consult with Lab Manager regarding lab equipment when circuit are installed to prevent overloading, new plug points to be wired from distribution board and marked properly

Legend card in DB to be up to date

Electrical Certificate of Completion to be issued on completion

All material to be SABS approved

All installations to comply with SANS10142 installation rules

All additional /replaced plugs, isolators and light switches must be labelled on the cover and Distribution



Board

Circuit breakers to be SABS approved and type and size to be confirmed with Project Manager before installation

Hydroboils: wire from DB Board with 30Amp double pole isolator next to Unit (at least 1m away) and 20Amp circuit breaker in DB board

Doors

All doors to be hung in such a way that the clearance gap between door and frame after hanging shall not exceed 2mm at sides and head. The floor clearance to be preferably 2mm but may be increased to accommodate an uneven floor finish. Exterior doors shall be hung on brass hinges. Aluminium frame glass doors to have 6mm safety laminated glass fitted, to be hung on aluminium hinges, not less than 4 hinges on a 2 100mm high door. On higher doors at least 5 hinges should be fitted. The glass door must have a mid-rail with bottom half either glass or solid aluminium, the aluminium door profile must be 90mm all-round All exterior doors to be fitted with an aluminium and rubber weather strip at the bottom. Each door to be equipped with 2 door handles. Type to be confirmed by Project Manager. Behind every door a door stop should be installed on top of the floor to prevent the door handle making contact with the wall – clearance between wall and door handle to be approximately 20mm.

Paint

Two final coats of White paint to all surfaces, ceiling and walls. Door colours to be confirmed by Project Manager, if not varnished

Existing pipes against wall must be colour coded painted, for example gas, water, oxygen

Rhino board surface to receive Rhinolite to a smooth finish on dry walls

Before painting can commence, every defect/uneven surface must be repaired

Patch prime new and exposed plaster areas with 1 coat and allow drying. Coat 1 may be thinned up to 10% with mineral turpentine to aid absorption. Allow 4 hours drying time at 23° c . Three (3) coats of paint to dry wall. Paint texture and type to match existing, Colour for walls and steel frames to be white unless otherwise confirmed by Project Manager

One coat metal primer to steel work and two coats final oil based enamel

Paint to be Plascon double velvet, Dulux, Prominent or similar

TILE Floors

Ensure that the sub-floor is completely smooth, level, hard, dry and clean before laying commences Only use A Grade Acid resisting Ceramic/ porcelain tiles, 10mm thick, 600^{mm} x 600^{mm} for floors and 600^{mm} x 200^{mm} for walls in size or as per BOQ

All tiles need to have "Aluminium Tile Edge Trim" where necessary. Bull nose or square one may be used Use SABS approved tile cement and apply as per Manufacturers instructions (colour to be confirmed by Project Manager)

Use SABS approved water proof Acid resistant grout. Gaps 5 – 10mm (colour grey)

Skirtings to be 100mm high where required, coved at junction with floor and rounded on top edge

CARPET Floors

Ensure that the sub-floor is completely smooth, level, hard, dry and clean before laying commences. Installation to be done by an approved Installer in accordance with the Manufacturer's specifications

TILE Walls

Ensure that the wall is completely smooth, level, hard, dry and clean before laying commences Only use A Grade Acid resisting Ceramic tiles, 10mm thick, 600 x 200mm in size

Use SABS approved tile cement and apply as per Manufacturers instructions (colour to be confirmed by Project Manager)

All tiles need to have "Aluminium Tile Edge Trim" where necessary. Bull nose or square one may be used Use SABS approved water proof Acid resistant grout. Gaps 5 – 10mm (colour grey)

All edges and corners to be finished off with PVC edging strips. Colour to be confirmed per job depending on tile colour.



Glazing

All Internal glass in panes not exceeding 1.5m² of surface area shall be 4mm clear float glass

All Internal glass in panes exceeding 1.5m² of surface area shall be 6mm laminated safety glass with a Manufacturer's warranty against defects and discoloration

All Exterior glass up to a height of 10m in panes not exceeding 2.9m²of surface area shall be 6.38mm PVB Laminated annealed safety glass. Above 10m the Project Manager should appoint a Glazing Competent Person

Mirrors to comply with SABS requirements. Unframed mirrors to have polished edges

All glass in aluminium doors and frames to be fitted with 6mm laminated safety glass

All exterior facing windows to be tinted with Klingshield or similar product, unless otherwise stipulated. Colour to be confirmed by Project Manager

Blinds

Vertical Group 3 blinds to be installed (colour to be confirmed by Project Manager)

Blinds to be re-measured on site before manufacturing and installation

Vertical blinds to be 127mm

Horizontal blinds 50mm

Horizontal blinds to be either Aluminium/ Wood Venetian conformation on the BOQ

Measurements given is only for tendering purpose

Suspended ceilings

Install suspended ceilings as per Manufacturers instructions such as Donn Products or similar. Panels to be vinyl cladded smooth white panels, $1200 \times 600 \times 12.5$ mm on suspended pre-painted exposed tee trusses, including main and cross tees, hangers, grids, etc., all level and properly secured. At edges use 25mm pre-painted shadow line aluminium cornices

Partitioning

Drywall partitioning construction and support frame system including finishes to be as per Manufacturer's specifications

Minimum requirement GPG Gypsum Gyproe Standard 40 Db, ½ hour fire rating with a stud (63.5mm) and track system. Positioning at 600mm cc fixed to 63.5mm top & bottom track clad on both sides with 12.5mm taper edged rhino board affixed with 25mm drywall screws at 220mm cc

All corners to be finished off with drywall corner strips. All joints to be taped, jointed and smoothed before painting

Aluminium skirtings to be affixed to all drywall partitioning unless otherwise specified

Door and window frames fitted in drywall partitioning to be installed as per Manufacturer's specifications

PLEASE TAKE NOTE THAT THE ABOVE SPECIFICATIONS AND MEASUREMENTS ARE SUBJECT TO CHANGE AS MAY BE DETERMINED BY THE FINAL APPROVED DRAWINGS OR COMPULSARY SITE MEETING FOR THE JOB IN QUESTION

WORKS AGREEMENT

Contractor: The contactor shall:

- Provide adequate supervision and management of the works at all times.
- Provide toilet facilities for use by his workers except where provided by the client (NHLS).
- Storage space is not always available for material and sufficient arrangements should be catered for and included in pricing.
- Submit all local authority notices by the works.



- Comply with all statutes, regulations and bylaws of local or other authorities having jurisdiction regarding the execution of the works and obtain all certificates and other documents required by such authorities.
- Notify the Project Manager where compliance with any statute, regulation or bylaw requires a change or variation to the works upon which such change shall be deemed to be a contract instruction.
- Immediately begin the works and continue at a rate of progress satisfactory to the Project Manager in terms of the agreement.
- Comply with all contract instructions in good time.
- Bring the works, within the constructed period, to practical completion in terms of completion.
- Bring the works to final completion.
- Surplus material and waste to be carted away to a suitable dumping site to be found by the Contractor, outside the boundary of the site

Completion

Practical Completion

- The Project Manager shall inspect the works from time to time to give the contractor interpretations and guidance on the standard and state of completion of the works which he will require the contractor to achieve for practical completion
- The contractor shall inform the Project Manager of the date on which he expects to achieve practical completion
- The Project Manager shall inspect the works on or before the date requested by the contractor Where the works:
- Has reached practical completion the Project Manager shall at once issue a certificate of practical completion to the contractor
- Has not reached practical completion the Project Manager shall issue a practical completion list to the contractor detailing the outstanding work to be done and defects to be rectified to achieve practical completion
- Is not ready for practical completion inspection the Project Manager shall issue a list as a general guide
 to the contractor of the outstanding areas of work and defects to be attended to before he can request
 a further inspection

Final Completion

- Within seven calendar days of practical completion the Project Manager shall prepare and issue to the contractor a final completion list detailing the incomplete work and defects to be rectified within a reasonable period
- The defects liability period of fourteen calendar days shall start on the date of practical completion
- On the expiry of the defects liability period the Project Manager shall immediately inspect the works for final completion. Where the works:
- Has reached final completion the Project Manager shall at once issue a certificate of final completion to the contractor
- Has not reached final completion the Project Manager shall issue a defects list to the contractor detailing any incomplete work and defects to be rectified before the Project Manager will undertake a further inspection
- Where the contractor has achieved final completion the latent defects liability period shall end three years from the date of final completion

Employer: The employer shall:

- Hand over the site to the contractor by the date stated in the schedule. The construction period and latent defects liability period shall commence with the handover of the site.
- Arrange for water, sewer and electrical connections as required and pay all fees concerning this
- Provide water and electricity as required for the execution of the works free of charge.



Not issue instructions to, interfere with, hinder or obstruct any of the contractor's workers or any other
persons employed or acting on behalf of the contractor.

Risk and Insurance

- The Contractor indemnifies the NHLS against any loss in respect of claims from other parties arising out of or due to the execution of the works or occupation of the site by the contractor consequent upon:
 - Death or bodily injury or illness of any person.
 - o Physical loss and damage to any property other than the works.
 - o Removal of or interference with lateral support of an adjoining property.
- The contractor shall take out insurances in respect of his employees as are required by law.
- Where, in the opinion of the Project Manager, loss and damage to the works due to the contractor's negligence the contractor shall be liable for such loss and damage.
- The contractor shall in all circumstances be at risk for loss of, or damage to his construction plant or vehicles.
- The contractor shall enclose the site along the facades where work is being done. He shall furthermore allow for all the required scaffolding, gantries, hoarding, etc. to safeguard pedestrian traffic on the sidewalks or paths as well as vehicular traffic in the streets
- The form of scaffolding, gantries, hoardings, etc., must be fully detailed in his "method statement" as previously required. It is not the intention to prohibit or deviate pedestrians or traffic during construction and Tenderers are to account for this when pricing the Tender
- Adequate warning signs/ lights/ etc. are to be employed where required. If the Tenderer requires the
 full pavement width and even part of the adjacent street, then he must make all the necessary
 arrangements with local authorities for the pavement and street closure as well as pay for all fees in
 connection therewith including the loss of income due to parking meters
- The existing premises will be occupied at all times and the Contractor will be required to keep all noise to a minimum

Safety

- From the date of site handover to the Contractor until the completed work is handed back to the Employer, the Contractor shall be responsible for maintaining safe working conditions on site
- The Contractor shall be responsible in terms of the Occupational Health and Safety Act, 1993 (Act No 85 of 1993) and the regulations promulgated in terms of the Act or Factories, Machinery and Buildings Work Act, whichever is applicable
- The Contractor shall be responsible for supplying and installing the required safety signs as determined by the Occupational Health and Safety Act, 1993 (Act No 85 of 1993) All safety signs shall comply with the requirements of the latest edition of SANS 11861 as Applicable

Programme

•	The Contractor shall submit his programme of work to the Project Manager not later than 14 days after
	the Contractor has been notified of the acceptance of his tender. If necessary, the Project Manager
	may instruct the Contractor to adjust his programme to suit other activitie

END)



4. PRICING SCHEDULE

No.	Description	Total Price Exc Vat
1.	REQUEST FOR RENOVATIONS FOR IT MAIN BUILDING AT NHLS SANDRINGHAM CAMPUS	
TOTAL PRICE EXCLUSIVE OF VAT		R
VAT %		R
DELIVERY		R
TOTAL PRICE INCLUSIVE OF VAT		R

NB: Delivery cost must be included.



5. FORM OF OFFER (SBD 7) Offer

The employer, identified in the acceptance signature block, has solicited offers to enter into a contract for the procurement of:
The tenderer, identified in the offer signature block, has examined the documents listed in the submission data and addenda
Thereto as listed in the returnable schedules, and by submitting this offer has accepted the condition of tender.
By the representative of the tenderer, deemed to be duly authorized, signing this part of this form offer and acceptance, the tenderer offers to perform all of the obligations and liabilities of the contractor under the contract including compliance with all its terms and conditions according to their true intent and meaning for an amount to be determined in accordance with the conditions of contract identified in the contract data.
THE OFFERED TOTAL OF THE PRICES INCLUSIVE OF VALUE ADDED TAX IS:
Rand
words); R
Signature(s)
for the tenderer
(Name and
address of organization/)



6. RFQ EVALUATION PROCESS AND CRITERIA

The RFQ will be evaluated by the Cross Functional Evaluation Team (CFET) and the successful service provider will be selected based on a three-phased approach (3-Stages):

Stage 1: Administrative Compliance

All incomplete submissions and respondents who do not meet the compliance requirements at quotation submission will be eliminated from further evaluation.

Stage 2: Mandatory technical requirements

All incomplete submissions and respondents who do not meet the minimum technical mandatory requirements at quotation submission will be eliminated from further evaluation.

Stage 3: Price and specific goals

The final evaluation phase will be based on Price and Specific Goals.

Determination of Percentage for Price – 80 percentage, & Determination of level for Specific Goals – 20 percentage.

Stage 1: Administrative Compliance

TAX Compliance Status Letter.

- Administrative compliance/responsiveness will be tested based on returnable documents submitted and signatures on the bid documents.
- At this stage, it must be determined what documents are required to be returned by Bidders. Returnable documents are categorized as follows:

a) Mandatory Returnable Documents (to be returned by Bidders)

4. Tax Clearance Certificate and/or TAX verification Pin and/or Comply

(NOTE: Failure to provide the below listed documents WILL lead to disqualification)

The Service Providers to have to agree with all NHLS	General	Comp	ly	Do Not Comply
Conditions of Bid, RFQ and Conditions of Contract (GCC))			
Substantiation: The Bidder must submit and attach to	the bid	respons	se tl	he signed and accepto
NHLS General Conditions of Bid, RFQ and Conditions	of Cont	ract (GC	CC).	
		_		
Fully completed and signed Declaration of Interest SBD 4		Comp	oly	Do Not Comply
Substantiation: The Bidder must submit and attach to Interest SBD 4	the bid r	espons	e th	ne signed Declaration
Bidder <i>must</i> complete the pricing Schedule.	С	omply	Do	Not Comply
Substantiation: The Bidder must submit and attach to	the bid r	espons	e fu	Illy completed pricing

Substantiation: The Bidder must submit and attach to the bid response a valid TAX Clearance

Do Not Comply



Certificate and/or TAX verification Pin and/or TAX Compliance Status Letter issued by the South African Revenue Services (SARS).

5. The Bidder must provide the CSD (Central	Comply	Do Not Comply				
Supplier Database) Registration number (MAAA						
number) / Attach the CSD Summary Report						
Substantiation: The Bidder must provide the CSD (Central Supplier Database) Registration number						
(MAAA number) / Attach the updated CSD Summary Report.						

B. Essential Returnable Documents (to be returned by Bidders) Not a disqualification factor

6. B-BBEE Certificate and/or Affidavit.	Comply	Do Not Comply
Fully completed and signed preferential points claim form SBD 6.1.		
Substantiation: The bidder must submit and attach to the bid response	e a copy of	B-BBEE
Certificate issued by an authorised body or person, or a sworn Affid	avit presci	ibed by the B-
BBEE Codes of Good Practice.		

Stage 2: Mandatory and regulatory requirements

The following are deemed as mandatory and regulatory requirements and failure to comply will result in the invalidation of a proposal

No	Legislative	Comply	Do not comply
1	CIDB grading (2GB or higher)		
2	Electrical Wire man's license		
3	Letter of good standing COIDA		
4	Industry regulator registration <i>Plumbing Industry</i> Registration Board (PIRB)		
5	Three (3) copies of contactable reference or completion certificate, on client's letterhead, with contact details		
6	5-year company Experience in related field, attach either CK, registration documents, old references which are older as a proof		
7	Provide copy of CV and Certificate of 5 years experienced project manager/supervisor to manage the project		
8	Electrical trade Test		
9	Plumbing Trade test		

Stage 3: Price And Specific Goals Criteria

Bid will be evaluated based on the PPPFA 80/20-point system as presented in the Preferential Procurement Regulations 2022,

for this purpose SBD 6.1 form should be scrutinized, completed and submitted together with your quotation. The 80/20-point system will be as follows:

Price Assessment	80 Points
Specific Goals	20 Points



7. SCHEDULE OF WORK CARRIED OUT BY THE BIDDER

The bidder must indicate in the spaces provided below a complete list of similar contracts awarded over the last five (5) years, including the current contract (if any). This information shall be deemed to be material to the award of this bid.

Company Name	Nature of work	Value of the work	Contact person & contact number	Duration of the project (Start and end date)

Sigr	ature of perso	n authorized to sign the bid:		
D	ate:			



B. DECLARATION OF INTEREST

SBD4

BIDDER'S DISCLOSURE

1. PURPOSE OF THE FORM

Any person (natural or juristic) may make an offer or offers in terms of this invitation to bid. In line with the principles of transparency, accountability, impartiality, and ethics as enshrined in the Constitution of the Republic of South Africa and further expressed in various pieces of legislation, it is required for the bidder to make this declaration in respect of the details required hereunder.

Where a person/s are listed in the Register for Tender Defaulters and / or the List of Restricted Suppliers, that person will automatically be disqualified from the bid process.

2. Bidder's declaration

- 2.1 Is the bidder, or any of its directors / trustees / shareholders / members / partners or any person having a controlling interest1 in the enterprise, employed by the state?

 YES/NO
- 2.1.1 If so, furnish particulars of the names, individual identity numbers, and, if applicable, state employee numbers of sole proprietor/directors/trustees/shareholders/members/partners or any person having a controlling interest in the enterprise, in table below.

Full Name	Identity Number	Name of State institution

2.2	Do you, or	any person	connected with the	bidder, ha	ave a relationship with	any person who
	is	employed	by	the	procuring	institution?
	YES/NO					

¹ the power, by one person or a group of persons holding the majority of the equity of an enterprise, alternatively, the person/s having the deciding vote or power to influence or to direct the course and decisions of the enterprise.



2.2.1	If so, furnish particulars:
2.3	Does the bidder or any of its directors / trustees / shareholders / members / partners or any person having a controlling interest in the enterprise have any interest in any other related enterprise whether or not they are bidding for this contract? YES/NO
2.3.1	If so, furnish particulars:
3 D	ECLARATION
	I, the undersigned, (name) in submitting the accompanying bid, do hereby make the following statements that I certify to be true and complete in every respect:
3.1 3.2	I have read and I understand the contents of this disclosure; I understand that the accompanying bid will be disqualified if this disclosure is found not to be true and complete in every respect;
3.3	The bidder has arrived at the accompanying bid independently from, and without consultation, communication, agreement or arrangement with any competitor. However, communication between partners in a joint venture or consortium2 will not be construed as collusive bidding.
3.4	In addition, there have been no consultations, communications, agreements or arrangements with any competitor regarding the quality, quantity, specifications, prices, including methods, factors or formulas used to calculate prices, market allocation, the intention or decision to submit or not to submit the bid, bidding with the intention not to win the bid and conditions or delivery particulars of the products or services to which this bid invitation relates.
3.4	The terms of the accompanying bid have not been, and will not be, disclosed by the bidder, directly or indirectly, to any competitor, prior to the date and time of the official bid opening or of the awarding of the contract.
3.5	There have been no consultations, communications, agreements or arrangements made by the bidder with any official of the procuring institution in relation to this procurement process prior to and during the bidding process except to provide clarification on the bid submitted where so required by the institution; and the bidder was not involved in the drafting of the specifications or terms of reference for this bid.
3.6	I am aware that, in addition and without prejudice to any other remedy provided to combat any restrictive practices related to bids and contracts, bids that are suspicious will be reported to the Competition Commission for investigation and possible imposition of administrative penalties in terms of section 59 of the Competition Act No 89 of 1998 and or may be reported to the National Prosecuting Authority (NPA) for criminal investigation and or may be restricted from conducting business with the public sector for a period not exceeding ten (10) years in terms of the Prevention and Combating of Corrupt Activities Act No 12 of 2004 or any other applicable legislation.

2 Joint venture or Consortium means an association of persons for the purpose of combining their expertise, property, capital, efforts, skill and knowledge in an activity for the execution of a contract



I CERTIFY THAT THE INFORMATION FURNISHED IN PARAGRAPHS 1, 2 and 3 ABOVE IS CORRECT. I ACCEPT THAT THE STATE MAY REJECT THE BID OR ACT AGAINST ME IN TERMS OF PARAGRAPH 6 OF PFMA SCM INSTRUCTION 03 OF 2021/22 ON PREVENTING AND COMBATING ABUSE IN THE SUPPLY CHAIN MANAGEMENT SYSTEM SHOULD THIS DECLARATION PROVE TO BE FALSE.

Signature	Date
Position	Name of bidder



SBD 6.1

PREFERENCE POINTS CLAIM FORM IN TERMS OF THE PREFERENTIAL PROCUREMENT REGULATIONS 2022

This preference form must form part of all tenders invited. It contains general information and serves as a claim form for preference points for specific goals.

NB: BEFORE COMPLETING THIS FORM, TENDERERS MUST STUDY THE GENERAL CONDITIONS, DEFINITIONS AND DIRECTIVES APPLICABLE IN RESPECT OF THE TENDER AND PREFERENTIAL PROCUREMENT REGULATIONS, 2022

1. GENERAL CONDITIONS

- 1.1 The following preference point systems are applicable to invitations to tender:
 - the 80/20 system for requirements with a Rand value of up to R50 000 000 (all applicable taxes included); and
 - the 90/10 system for requirements with a Rand value above R50 000 000 (all applicable taxes included).

1.2 To be completed by the organ of state

(delete whichever is not applicable for this tender).

- a) The applicable preference point system for this tender/RFQ is the 80/20 preference point system.
- b) The 80/20 preference point system will be applicable in this tender/RFQ. The lowest/ highest acceptable tender will be used to determine the accurate system once tenders are received.
- 1.3 Points for this tender (even in the case of a tender for income-generating contracts) shall be awarded for:
 - (a) Price; and
 - (b) Specific Goals.

1.4 To be completed by the organ of state:

The maximum points for this tender are allocated as follows:

	POINTS
PRICE	80
SPECIFIC GOALS	20
Total points for Price and SPECIFIC GOALS	100



- 1.5 Failure on the part of a tenderer to submit proof or documentation required in terms of this tender to claim points for specific goals with the tender, will be interpreted to mean that preference points for specific goals are not claimed.
- 1.6 The organ of state reserves the right to require of a tenderer, either before a tender is adjudicated or at any time subsequently, to substantiate any claim in regard to preferences, in any manner required by the organ of state.

2. DEFINITIONS

- (a) "tender" means a written offer in the form determined by an organ of state in response to an invitation to provide goods or services through price quotations, competitive tendering process or any other method envisaged in legislation;
- (b) "price" means an amount of money tendered for goods or services, and includes all applicable taxes less all unconditional discounts;
- (c) "rand value" means the total estimated value of a contract in Rand, calculated at the time of bid invitation, and includes all applicable taxes;
- (d) "tender for income-generating contracts" means a written offer in the form determined by an organ of state in response to an invitation for the origination of income-generating contracts through any method envisaged in legislation that will result in a legal agreement between the organ of state and a third party that produces revenue for the organ of state, and includes, but is not limited to, leasing and disposal of assets and concession contracts, excluding direct sales and disposal of assets through public auctions; and
- (e) "the Act" means the Preferential Procurement Policy Framework Act, 2000 (Act No. 5 of 2000).

(f) "Historically Disadvantaged Individual (HDI)"

- Means a South African citizen who, due to the apartheid policy that had been in place, had no franchise in national elections prior to the introduction of the Constitution of the Republic of South Africa, 1983 (Act No. 110 of 1983) or the Constitution of the Republic of South Africa, 1993 (Act No. 200 of 1993) ("The Interim Constitution") and /or
- ii. Who is a female: and/or
- iii. Who has a disability
- (g) "Disability" means, in respect of a person, a permanent impairment of a physical, intellectual, or sensory function, which results in restricted, or lack of, ability to perform an activity in the manner, or within the range, considered normal for a human being.
- (h) "Youth" Has the meaning assigned to it in section 1 of the National Youth Development Agency Act, 2008 (Act No. 54 of 2008)
- (i) "Specific goals" means specific goals as contemplated in section 2(1)(d) of the PPPFA which may include contracting with persons, or group of persons, historically disadvantage by unfair discrimination on the basis of race, gender and disability including the implementation of programmes of the Reconstruction and Development Programme as published in Government Gazette No. 16085 dated 23 November 1994.

3. FORMULAE FOR PROCUREMENT OF GOODS AND SERVICES

3.1. POINTS AWARDED FOR PRICE

3.1.1 THE 80/20 OR 90/10 PREFERENCE POINT SYSTEMS

A maximum of 80 or 90 points is allocated for price on the following basis:



80/20

$$Ps = 80 \left(1 - \frac{Pt - P \min}{P \min}\right)$$

Where

Ps = Points scored for price of tender under consideration

Pt = Price of tender under consideration

Pmin = Price of lowest acceptable tender

3.2. FORMULAE FOR DISPOSAL OR LEASING OF STATE ASSETS AND INCOME GENERATING PROCUREMENT

3.2.1. POINTS AWARDED FOR PRICE

A maximum of 80 or 90 points is allocated for price on the following basis:

80/20

$$Ps = 80 \left(1 + \frac{Pt - P max}{P max}\right)$$

Where

Ps = Points scored for price of tender under consideration Pt

Price of tender under consideration

Pmax = Price of highest acceptable tender

4. POINTS AWARDED FOR SPECIFIC GOALS

- 4.1. In terms of Regulation 4(2); 5(2); 6(2) and 7(2) of the Preferential Procurement Regulations, preference points must be awarded for specific goals stated in the tender. For the purposes of this tender the tenderer will be allocated points based on the goals stated in table 1 below as may be supported by proof/ documentation stated in the conditions of this tender:
- 4.2. In cases where organs of state intend to use Regulation 3(2) of the Regulations, which states that, if it is unclear whether the 80/20 or 90/10 preference point system applies, an organ of state must, in the tender documents, stipulate in the case of—
- (a) an invitation for tender for income-generating contracts, that either the 80/20 or 90/10 preference point system will apply and that the highest acceptable tender will be used to determine the applicable preference point system; or
- (b) any other invitation for tender, that either the 80/20 or 90/10 preference point system will apply and that the lowest acceptable tender will be used to determine the applicable preference point system,

then the organ of state must indicate the points allocated for specific goals for both the 90/10 and 80/20 preference point system.

Points awarded for historically disadvantaged individuals

Preference points for HDI's are calculated on their percentage shareholding in a business, provided that they are actively involved in and exercise control over the enterprise. The following formula is prescribed



$$NEP = NOP \times \frac{EP}{100}$$

Where

NEP = Points awarded for equity ownership by an HDI

NOP = The maximum number of points awarded for equity by an HDI in that specific category

EP = The percentage of equity ownership by an HDI within the enterprise or business, determined in accordance with the definition of HDI's.

A consortium or joint venture (including unincorporated consortia and joint ventures) must submit a consolidated B-BBEE Status Level Verification certificate for every separate tender

Table 1: Specific goals for the tender and points claimed are indicated per the table below.

(Note to organs of state: Where either the 90/10 or 80/20 preference point system is applicable, corresponding points must also be indicated as such.

Note to tenderers: The tenderer must indicate how they claim points for each preference point system.)

The specific goals allocated points in terms of this tender	Number of points allocated (80/20 system) (To be completed by the organ of state)	Percentage Owned (To be completed by the tenderer)	Number of points claimed (80/20 system) (To be completed by the tenderer)
HDI	6	%	
Woman	4	%	
Disabled	1	%	
Youth	4	%	
Locality City of Johannesburg = 5 Gauteng Province = 2 National = 0	5		
Total Points	20		

DECLARATION WITH REGARD TO COMPANY/FIRM

4.3.	Name of compar	ny/firm
------	----------------	---------

4.4. Company registration number:



4 -	TVDE	\sim \sim	COLIDARIA	
4.5.	IYPE	OF.	COMPANY	' FIKIVI

	Partnership/Joint Venture / Consortium
	One-person business/sole propriety
	Close corporation
	Public Company
	Personal Liability Company
	(Pty) Limited
	Non-Profit Company
	State Owned
Com	pany [TICK
APPI	ICABLE BOX1

- 4.6. I, the undersigned, who is duly authorised to do so on behalf of the company/firm, certify that the points claimed, based on the specific goals as advised in the tender, qualifies the company/ firm for the preference(s) shown and I acknowledge that:
 - i) The information furnished is true and correct;
 - ii) The preference points claimed are in accordance with the General Conditions as indicated in paragraph 1 of this form;
 - iii) In the event of a contract being awarded as a result of points claimed as shown in paragraphs 1.4 and 4.2, the contractor may be required to furnish documentary proof to the satisfaction of the organ of state that the claims are correct;
 - iv) If the specific goals have been claimed or obtained on a fraudulent basis or any of the conditions of contract have not been fulfilled, the organ of state may, in addition to any other remedy it may have
 - (a) disqualify the person from the tendering process;
 - (b) recover costs, losses or damages it has incurred or suffered as a result of that person's conduct;
 - (c) cancel the contract and claim any damages which it has suffered as a result of having to make less favourable arrangements due to such cancellation;
 - (d) recommend that the tenderer or contractor, its shareholders and directors, or only the shareholders and directors who acted on a fraudulent basis, be restricted from obtaining business from any organ of state for a period not exceeding 10 years, after the audi alteram partem (hear the other side) rule has been applied; and
 - (e) forward the matter for criminal prosecution, if deemed necessary

	SIGNATURE(S) OF TENDERER(S)
SURNAME AND NAME: DATE:	
ADDRESS:	



9. AUTHORITY FOR SIGNATORY

Signatories for close corporations and companies shall confirm their authority **by attaching to this form** a duly signed and dated copy of the relevant resolution of their members or their board of directors, as the case may be.

An example for a company is shown below:					
" By resolution of the board of directors passed on	_20				
Mrauthorized to sign all documents in connection with the					
Noand any Contract, which ma	y arise there from on behalf of				
SIGNED ON BEHALF OF THE COMPANY:					
IN HIS CAPACITY AS:					
DATE.					
DATE:					
SIGNATURE OF SIGNATORY:					
AS WITNESSES: 1	-				
2					
2	•				