

NMAL UPS SPECIFICATION	COMPLIANT	NON-COMPLIANT
Smart-UPS 3KVA		
GENERAL		
Battery Enclosure Type		
Internal		
Subcategory		
UPS		
Manufacturer		
Schneider Electric		
POWER DEVICE		
Voltage Required		
AC 100 V		
Power Output Connectors Details		
8 x power NEMA 5-15		
2 x power NEMA 5-20		
Output Voltage		
AC 100 V \pm 5% - 47 - 53 / 57 - 63 Hz		
Power Capacity		
1.98 kW / 2200 VA		
Surge Suppression		
yes		
Surge Energy Rating		
510 Joules		
Power Provided		
1.98 kW		
Frequency Required		
50/60 Hz		
Circuit Protection		
circuit breaker		
Form Factor		
external		
UPS Technology		
line interactive		
Voltage Provided		
AC 100 V		
Voltage Provided Margin		
\pm 5%		
Frequency Provided		
47 - 53 / 57-63 Hz		
UPS Output Waveform		
sinewave		
Power Capacity (VA)		
2200 VA		
Input Connector Type		
power NEMA L5-30		

Input Connector Qty		
1		
Output Connector Qty		
10		
Surge Response Time		
0 ms		
Power Device Features		
Automatic Voltage Regulation (AVR), LED indicators, audible alarm, automatic self-test, emergency power off, predictive failure notification		
BATTERY		
Quantity		
1		
Run Time (Up To)		
6.7 min at full load		
Recharge Time		
4.5 hour(s)		
Load Type		
at full load		
NETWORKING		
Remote Management Interface		
RS-232, USB		
INTERFACE PROVIDED		
Qty		
1		
Connector Type		
9 pin D-Sub (DB-9)		
Type		
EPO (emergency power off), management (RS-232), management (USB)		
MISCELLANEOUS		
Color		
black		
Color Category		
black		
ENVIRONMENTAL PARAMETERS		
Min Operating Temperature		
32 °F		
Max Operating Temperature		
104 °F		
Humidity Range Operating		
0 - 95%		
HEADER		
Brand		
APC		
Product Line		
APC Smart-UPS		

Model		
2200		
Country Kits		
Japan		
Packaged Quantity		
1		
Compatibility		
PC		
EXPANSION SLOTS		
Type		
SmartSlot		
Total Qty		
1		
CABLE DETAILS		
Type		
power cable		
Length		
8 ft		
DIMENSIONS & WEIGHT		
Width		
7.7 in		
Depth		
21.4 in		
Height		
17 in		
Weight		
112.66 lbs		
DIMENSIONS & WEIGHT (SHIPPING)		
Width (Shipping)		
15 in		
Depth (Shipping)		
30 in		
Height (Shipping)		
22 in		
Weight (Shipping)		
134.26 lbs		
POWER OUTPUT CONNECTORS DETAILS		
Connector Type		
power NEMA 5-15, power NEMA 5-20		
Connector Qty		
2, 8		
RUN TIME DETAILS		
Run Time (Up To)		
6.7 min		
Load Type		
full load		
UPS		

Batteries Qty		
1		
Battery Technology		
lead acid		
SERVICE & SUPPORT		
Type		
3 years warranty		
SERVICE & SUPPORT DETAILS		
Type		
limited warranty		
Full Contract Period		
3 years		

Handwritten: P. D. Baker 22/08/2025